R-companion to: Estimation of the Thurstonian model for the 2-AC protocol

Rune Haubo Bojesen Christensen,
Hye-Seong Lee &
Per Bruun Brockhoff

November 3, 2026

This document describes how the examples in "Estimation of the Thurstonian model for the 2-AC protocol" (**?**) can be executed in the free statistical software R (**?**) using the free R packages sensR and ordinal (**??**) developed by the authors.

1 Example 1: Estimation of d' and τ

It is assumed that we have $\boldsymbol{n} = (2, 2, 6)$ observations in the three categories. We may estimate τ, d' and their standard errors with the `twoAC` function in the sensR package:

```
> library(sensR)
> fit <- twoAC(c(2, 2, 6))
> fit

Results for the 2-AC protocol with data c(2, 2, 6):
        Estimate Std. Error
tau       0.4160     0.2674
d.prime   0.7743     0.5417

Two-sided 95% confidence interval for d-prime based on the
likelihood root statistic:
         Lower Upper
d.prime -0.271 1.859

Significance test:
 Likelihood root statistic = 1.446718 p-value = 0.14798
 Alternative hypothesis: d-prime is different from 0
```

Alternatively we may compute τ and d' manually:

```
> n <- c(2, 2, 6)
> gamma <- cumsum(n/sum(n))
> z <- qnorm(gamma)[-3]
```

```
> z <- z * sqrt(2)
> (tau <- (z[2] - z[1])/2)

[1] 0.4159726

> (d <- -z[1] - tau)

[1] 0.7742595
```

2 Example 2: Inference for d-prime

The likelihood based confidence intervals and the one-sided discrimination significance test where the null hypothesis is "no sensory difference", i.e., $d'_0 = 0$ using the likelihood root statistic are immediately available using the `twoAC` function:

```
> twoAC(c(2, 2, 6), d.prime0 = 0, conf.level = 0.95, statistic = "likelihood",
      alternative = "greater")

Results for the 2-AC protocol with data c(2, 2, 6):
        Estimate Std. Error
tau       0.4160     0.2674
d.prime   0.7743     0.5417

Two-sided 95% confidence interval for d-prime based on the
likelihood root statistic:
         Lower Upper
d.prime -0.271 1.859

Significance test:
 Likelihood root statistic = 1.446718 p-value = 0.073988
 Alternative hypothesis: d-prime is greater than 0
```

The relative profile likelihood and Wald approximation can be obtained with:

```
> pr <- profile(fit)
> plot(pr)
> z <- pr$d.prime$d.prime
> w <- (coef(fit)[2, 1] - z)/coef(fit)[2, 2]
> lines(z, exp(-w^2/2), lty = 2)
```

3 Example 3: Power calculations

The function `twoACpwr` computes the power for the 2-AC protocol and a significance test of the users choice. The power assuming $\tau = 0.5$, $d' = 1$, the sample size is $N = 20$ for a two-sided preference test with $\alpha = 0.5$ is found with:

```
> twoACpwr(tau = 0.5, d.prime = 1, size = 20, d.prime0 = 0, alpha = 0.05,
      alternative = "two.sided", tol = 1e-05)

     power actual.alpha samples discarded kept    p.1    p.2    p.3
1 0.777677   0.04960103     231        94  137 0.1444 0.2174 0.6382
```




Figure 1: Relative profile likelihood curve (solid) and Wald approximation (dashed) for the data in example 1 and 2. The horizontal lines indicate 95% and 99% confidence intervals based on the likelihood function and the Wald approximation.

Apart from the power, we are told that the actual size of the test, α is close to the nominal 5%. The reason that the two differ is due to the discreteness of the observations, and hence the test statistic. We are also told that with $N = 20$ there are 231 possible outcomes of the 2-AC protocol. In computing the power 94 of these are discarded and power is computed based on the remaining 137 samples. The fraction of samples that are discarded is determined by the `tol` parameter. If we set this to zero, then no samples are discarded, however, the increase in precision is irrelevant:

```
> twoACpwr(tau = 0.5, d.prime = 1, size = 20, d.prime0 = 0, alpha = 0.05,
     alternative = "two.sided", tol = 0)

      power actual.alpha samples discarded kept    p.1    p.2    p.3
1 0.7776788   0.04960103     231         0  231 0.1444 0.2174 0.6382
```

The last three numbers in the output are the cell probabilities, so with $\tau = 0.5$ and $d' = 1$ we should, for example, expect around 22% of the answers in the "no difference" or "no preference" category.

4 Example 4: Estimation and standard errors via cumulative probit models

Estimates of τ and d' and their standard errors can be obtained from a cumulative probit model. We begin by defining the three leveled response variable `resp` and fitting a cumulative link model (CLM) using the function `clm` in package ordinal with weights equal to the observed counts and a probit link. Standard output contains the following coefficient table:

```
> library(ordinal)
> response <- gl(3, 1)
> fit.clm <- clm(response ~ 1, weights = c(2, 2, 6), link = "probit")
> (tab <- coef(summary(fit.clm)))

      Estimate Std. Error    z value   Pr(>|z|)
1|2 -0.8416212  0.4518154 -1.8627547 0.06249679
2|3 -0.2533471  0.4009896 -0.6318047 0.52751451
```

The τ and d' estimates are obtained by:

```
> theta <- tab[, 1]
> (tau <- (theta[2] - theta[1])/sqrt(2))

      2|3
0.4159726

> (d.prime <- (-theta[2] - theta[1])/sqrt(2))

      2|3
0.7742595
```

The variance-covariance matrix of the parameters can be extracted by the `vcov` method and the standard errors computed via the provided formulas:

```
> VCOV <- vcov(fit.clm)
> (se.tau <- sqrt((VCOV[1, 1] + VCOV[2, 2] - 2 * VCOV[2, 1])/2))

[1] 0.2674311

> (se.d.prime <- sqrt((VCOV[1, 1] + VCOV[2, 2] + 2 * VCOV[2, 1])/2))

[1] 0.5416737
```

Observe how these estimates and standard errors are identical to those in Example 1.

We could also have used the `clm2twoAC` function from package sensR which extract estimates and standard errors from a `clm` model fit object:

```
> clm2twoAC(fit.clm)

          Estimate Std. Error  z value Pr(>|z|)
tau      0.4159726  0.2674311 1.555439  0.11984
d-prime 0.7742595  0.5416737 1.429384  0.15289
```

5 Example 5: A regression model for d'

Assume that a study is performed and gender differences in the discrimination ability is of interest. Suppose that $(20, 20, 60)$ is observed for women and $(10, 20, 70)$ is observed for men. The standard output from a cumulative probit model contains the coefficient table:

```
> n.women <- c(2, 2, 6) * 10
> n.men <- c(1, 2, 7) * 10
> wt <- c(n.women, n.men)
> response <- gl(3, 1, length = 6)
> gender <- gl(2, 3, labels = c("women", "men"))
```

```
> fm2 <- clm(response ~ gender, weights = wt, link = "probit")
> (tab2 <- coef(summary(fm2)))

            Estimate Std. Error   z value     Pr(>|z|)
1|2       -0.8887474  0.1346051 -6.602627 4.039349e-11
2|3       -0.2283095  0.1238663 -1.843194 6.530068e-02
gendermen  0.3205403  0.1741445  1.840658 6.567176e-02
```

The estimate of τ (assumed constant between genders) and the gender specific estimates of d' can be extracted by:

```
> theta <- fm2$alpha
> (tau <- (theta[2] - theta[1])/sqrt(2))

      2|3
0.4670001

> (d.women <- (-theta[2] - theta[1])/sqrt(2))

      2|3
0.7898785

> (d.men <- d.women + fm2$beta * sqrt(2))

     2|3
1.243191
```

Again we could use the `clm2twoAC` function to get the coefficient table for the 2-AC model from the CLM-model:

```
> clm2twoAC(fm2)

            Estimate Std. Error  z value   Pr(>|z|)
tau       0.4670001 0.06700014 6.970135 3.1664e-12
d-prime   0.7898785 0.17021271 4.640538 3.4750e-06
gendermen 0.4533125 0.24627746 1.840658   0.065672
```

Observe that d' for women is given along with the difference in d' for men and women rather than d' for each of the genders.

The Wald test for gender differences is directly available from the coefficient table with $p = 0.0657$. The corresponding likelihood ratio test can be obtained by:

```
> fm3 <- update(fm2, ~. - gender)
> anova(fm2, fm3)

Likelihood ratio tests of cumulative link models:

    formula:          link:  threshold:
fm3 response ~ 1      probit flexible
fm2 response ~ gender probit flexible

    no.par    AIC  logLik LR.stat df Pr(>Chisq)
fm3      2 358.59 -177.29
fm2      3 357.19 -175.59  3.3997  1    0.06521 .
---
Signif. codes:  0 ‘***’ 0.001 ‘**’ 0.01 ‘*’ 0.05 ‘.’ 0.1 ‘ ’ 1
```

which is slightly closer to significance. The 95% profile likelihood confidence interval for the difference between men and women on the d'-scale is:

```
> confint(fm2) * sqrt(2)

                2.5 %    97.5 %
gendermen -0.02850933 0.9372283
```

The likelihood ratio test for the assumption of constant τ is computed in the following. The likelihood ratio statistic and associated p-value are

```
> logLik(fm2)

'log Lik.' -175.593 (df=3)

> tw <- twoAC(n.women)
> tm <- twoAC(n.men)
> (LR <- 2 * (tw$logLik + tm$logLik - fm2$logLik))

[1] 0.7682623

> pchisq(LR, 1, lower.tail = FALSE)

[1] 0.3807552
```

The Pearson X^2 test of the same hypothesis is given by

```
> freq <- matrix(fitted(fm2), nrow = 2, byrow = TRUE) * 100
> Obs <- matrix(wt, nrow = 2, byrow = TRUE)
> (X2 <- sum((Obs - freq)^2/freq))

[1] 0.7657565

> pchisq(X2, df = 1, lower.tail = FALSE)

[1] 0.381533
```

so the Pearson and likelihood ratio tests are very closely equivalent as it is so often the case.

6 Regression model for replicated 2-AC data

The data used in example 6 are not directly available at the time of writing. Assume however, that data are available in the R `data.frame` `repData`. Then the cumulative probit mixed model where preference depends on reference and consumers (`cons`) are random can be fitted with:

```
> fm3.agq <- clmm2(preference ~ reference, random = cons, nAGQ = 10,
     data = repData, link = "probit", Hess = TRUE)
> summary(fm3.agq)

Cumulative Link Mixed Model fitted with the adaptive Gauss-Hermite
quadrature approximation with 10 quadrature points

Call:
clmm2(location = preference ~ reference, random = cons, data = repData,
    Hess = TRUE, link = "probit", nAGQ = 10)
```

```
Random effects:
          Var  Std.Dev
cons 1.367074 1.169219

Location coefficients:
           Estimate Std. Error z value Pr(>|z|)
referenceB 0.4059   0.1002     4.0519  5.0808e-05

No scale coefficients

Threshold coefficients:
    Estimate Std. Error z value
A|N 0.4823   0.1130     4.2679
N|B 0.8488   0.1166     7.2800

log-likelihood: -668.9122
AIC: 1345.824
Condition number of Hessian: 36.7984
```

Here we asked for the accurate 10-point adaptive Gauss-Hermite quadrature approximation. The 2-AC estimates are available using the `clm2twoAC` function:

```
> clm2twoAC(fm3.agq)

             Estimate Std. Error   z value   Pr(>|z|)
tau         0.2592192 0.02902574  8.930665 < 2.22e-16
d-prime    -0.9412298 0.15975317 -5.891775 3.8207e-09
referenceB  0.5740295 0.14167002  4.051877 5.0808e-05
```

The standard deviation of the consumer-specific d's is given by:

```
> fm3.agq$stDev * sqrt(2)

    cons
1.653526
```

The profile likelihood curve can be obtained using the profile method:

```
> pr <- profile(fm3.agq, range = c(0.7, 1.8))
```

And then plottet using:

```
> plpr <- plot(pr, fig = FALSE)
> plot(sqrt(2) * plpr$stDev$x, plpr$stDev$y, type = "l", xlab = expression(sigma[delta]),
     ylab = "Relative profile likelihood", xlim = c(1, 2.5), axes = FALSE)
> axis(1)
> axis(2, las = 1)
> abline(h = attr(plpr, "limits"))
> text(2.4, 0.17, "95% limit")
> text(2.4, 0.06, "99% limit")
```

The resulting figure is shown in Figure 2. The profile likelihood confidence intervals are obtained using:

```
> confint(pr, level = 0.95) * sqrt(2)

         2.5 %  97.5 %
stDev 1.362331 2.00148
```




Figure 2: Profile likelihood for σ_δ Horizontal lines indicate 95% and 99% confidence limits.

The probabilities that consumers prefer yoghurt A, have no preference or prefer yoghurt B can, for an average consumer be obtained by predicting from the CLMM:

```
> newdat <- expand.grid(preference = factor(c("A", "N", "B"), levels = c("A",
      "N", "B"), ordered = TRUE), reference = factor(c("A", "B")))
> pred <- predict(fm3.agq, newdata = newdat)
```

The predictions for the extreme consumers have to be obtained by hand. Here we ask for the predictions for the 5th percentile and 95th percentile of the consumer population for reference A and B:

```
> q95.refA <- diff(c(0, pnorm(fm3.agq$Theta - qnorm(1 - 0.05) *
      fm3.agq$stDev), 1))
> q05.refA <- diff(c(0, pnorm(fm3.agq$Theta - qnorm(0.05) * fm3.agq$stDev),
      1))
> q95.refB <- diff(c(0, pnorm(fm3.agq$Theta - fm3.agq$beta - qnorm(1 -
      0.05) * fm3.agq$stDev), 1))
> q05.refB <- diff(c(0, pnorm(fm3.agq$Theta - fm3.agq$beta - qnorm(0.05) *
      fm3.agq$stDev), 1))
```

Plotting follows the standard methods:

```
> par(mar = c(0, 2, 0, 0.5) + 0.5)
> plot(1:3, pred[1:3], ylim = c(0, 1), axes = FALSE, xlab = "",
      ylab = "", pch = 19)
> axis(1, lwd.ticks = 0, at = c(1, 3), labels = c("", ""))
> axis(2, las = 1)
> points(1:3, pred[4:6], pch = 1)
> lines(1:3, pred[1:3])
> lines(1:3, pred[4:6], lty = 2)
> text(2, 0.6, "Average consumer")
> legend("topright", c("Reference A", "Reference B"), lty = 1:2,
      pch = c(19, 1), bty = "n")
```




Figure 3: The probabilities of prefering yoghurt A, having no preference, or prefering yoghurt B for an average consumer ($b = 0$) and for fairly extreme consumers ($b = \pm 1.64\sigma_b$).

```
> par(mar = c(0, 2, 0, 0.5) + 0.5)
> plot(1:3, q05.refA, ylim = c(0, 1), axes = FALSE, xlab = "",
    ylab = "", pch = 19)
> axis(1, lwd.ticks = 0, at = c(1, 3), labels = c("", ""))
> axis(2, las = 1)
> points(1:3, q05.refB, pch = 1)
> lines(1:3, q05.refA)
> lines(1:3, q05.refB, lty = 2)
> text(2, 0.6, "5th percentile consumer")

> par(mar = c(2, 2, 0, 0.5) + 0.5)
> plot(1:3, q95.refA, ylim = c(0, 1), axes = FALSE, xlab = "",
    ylab = "", pch = 19)
> axis(1, at = 1:3, labels = c("prefer A", "no preference", "prefer B"))
> axis(2, las = 1)
> points(1:3, q95.refB, pch = 1)
> lines(1:3, q95.refA)
> lines(1:3, q95.refB, lty = 2)
> text(2, 0.6, "95th percentile consumer")
```

The resulting figure is shown in Fig. 3.

7 End note

Versions details for R and the packages sensR and ordinal appear below:

```
> sessionInfo()

R version 4.5.3 (2026-03-11)
Platform: x86_64-conda-linux-gnu
Running under: Debian GNU/Linux 13 (trixie)

Matrix products: default
BLAS/LAPACK: /opt/mamba/envs/r/lib/libopenblasp-r0.3.34.so;  LAPACK version 3.12.0

locale:
 [1] LC_CTYPE=C.UTF-8       LC_NUMERIC=C           LC_TIME=C.UTF-8
 [4] LC_COLLATE=C.UTF-8     LC_MONETARY=C.UTF-8    LC_MESSAGES=C.UTF-8
 [7] LC_PAPER=C.UTF-8       LC_NAME=C              LC_ADDRESS=C
[10] LC_TELEPHONE=C         LC_MEASUREMENT=C.UTF-8 LC_IDENTIFICATION=C

time zone: America/New_York
tzcode source: system (glibc)

attached base packages:
[1] stats     graphics  grDevices utils     datasets  methods   base

other attached packages:
[1] ordinal_2026.7-26 sensR_1.5-4

loaded via a namespace (and not attached):
 [1] numDeriv_2016.8-1.1 codetools_0.2-20    multcomp_1.4-32
 [4] Matrix_1.7-6        lattice_0.23-1      TH.data_1.1-5
 [7] splines_4.5.3       zoo_1.9-0           ucminf_1.2.3
[10] mvtnorm_1.4-2       grid_4.5.3          sandwich_3.1-3
[13] compiler_4.5.3      tools_4.5.3         nlme_3.1-170
[16] survival_3.8-12     MASS_7.3-66
```