

Timings of common tasks using the **data.table** package in R

Matthew Dowle

Revised: November 25, 2011
(A later revision may be available on the [homepage](#))

* WORK IN PROGRESS *

This document contains a series of tests, followed by a summary table of various timings and comparisons. Please go straight to the summary table first <here> in which each row has a link back to the test.

This document is reproducible. Simply run the .Rnw file yourself in your environment to confirm the results. Also see ?vignette, which says that edit(vignette("datatable-timings")) will extract the code from this document so you can easily work with it.

The .Rnw included in the package has N=10,000,000. This is a small number so that 'R CMD build' completes in a reasonable time (about 5 minutes). We don't want the nightly builds on R-Forge and CRAN to slow down just to run long timing comparisons. We have increased this to N=100,000,000 ourselves, and included the output on the datatable homepage (<link>).

Contents

1 Timing tests	1
1.1 Extraction	1
1.2 Grouping	2
1.3 Test 3	3
1.4 Test 4	3
1.5 Test 5	3
2 Summary table	3

1 Timing tests

1.1 Extraction

This is a repeat of the test in section 1 of the Introduction vignette. The syntax is explained there. This demonstrates the large difference in speed between vector scans and binary search. Therefore, please avoid using == in the i expression.

```
> n = ceiling(1e7/26^2) # 10 million rows
> DF = data.frame(x=rep(LETTERS,each=26*n),
+                   y=rep(letters,each=n),
+                   v=rnorm(n*26^2))
> DT = data.table(DF,key="x,y")
> tables()

      NAME      NROW   MB COLS KEY
[1,] DT    10,000,068 153 x,y,v x,y
Total: 153MB

> tt=system.time(ans1 <- DF[DF$x=="R" & DF$y=="h",]); tt
```

```

      user  system elapsed
12.517    0.940  13.489

> head(ans1)

      x y          v
6642058 R h  0.92031035
6642059 R h  0.53499397
6642060 R h  2.01841546
6642061 R h  0.06539105
6642062 R h -0.90705812
6642063 R h  0.52108277

> dim(ans1)
[1] 14793      3

> ss=system.time(ans2 <- DT[J("R","h")]); ss

      user  system elapsed
0.024    0.000   0.026

> head(ans2)

      x y          v
[1,] R h  0.92031035
[2,] R h  0.53499397
[3,] R h  2.01841546
[4,] R h  0.06539105
[5,] R h -0.90705812
[6,] R h  0.52108277

> dim(ans2)
[1] 14793      3

> identical(ans1$v,ans2$v)
[1] TRUE

```

1.2 Grouping

This is a repeat of the test in section 2 of the Introduction vignette. The syntax is explained there.

```

> ttt=system.time(ans1 <- tapply(DF$v,DF$x,sum)); ttt

      user  system elapsed
17.053    1.049  18.180

> head(ans1)

      A          B          C          D          E          F
-174.12181  50.21609 -286.71590 -24.29142  806.03068  314.42153

> sss=system.time(ans2 <- DT[,sum(v),by=x]); sss

      user  system elapsed
0.480    0.212   0.689

> head(ans2)

```

```

      x      V1
[1,] A -174.12181
[2,] B  50.21609
[3,] C -286.71590
[4,] D -24.29142
[5,] E  806.03068
[6,] F  314.42153

> identical(as.vector(ans1), ans2$V1)

[1] TRUE

```

1.3 Test 3

1.4 Test 4

1.5 Test 5

2 Summary table

```

> ans

      base data.table times faster
==    13.489      0.026      518
tapply 18.180      0.689       26

> toLatex(sessionInfo())

```

- R version 2.14.0 (2011-10-31), i686-pc-linux-gnu
- Locale: LC_CTYPE=en_GB.UTF-8, LC_NUMERIC=C, LC_TIME=en_GB.UTF-8, LC_COLLATE=C, LC_MONETARY=en_GB.UTF-8, LC_MESSAGES=en_GB.UTF-8, LC_PAPER=C, LC_NAME=C, LC_ADDRESS=C, LC_TELEPHONE=C, LC_MEASUREMENT=en_GB.UTF-8, LC_IDENTIFICATION=C
- Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- Other packages: data.table~1.7.3
- Loaded via a namespace (and not attached): tools~2.14.0