

Package ‘juice’

September 9, 2005

Title Dynamic Systems Estimation - juice extensions

Description Multivariate Time Series - extensions

Depends R (>= 2.0.0), setRNG (>= 2004.4-1), tframe (>= 2005.9-1), dse1 (>= 2005.9-1)

Version 2005.9-1

LazyLoad yes

License Free. See the LICENCE file for details.

Author Paul Gilbert <pgilbert@bank-banque-canada.ca>

Maintainer Paul Gilbert <pgilbert@bank-banque-canada.ca>

URL <http://www.bank-banque-canada.ca/pgilbert>

R topics documented:

00Intro.juice	2
canonical.prediction	2
checkConsistentDimensions.TSmodelconcentrate	3
checkResiduals.TSdataconcentrate	4
concentrated.checkResiduals	4
concentratedDimension	5
concentrated.nseriesInput	5
concentratedSeriesNames	6
concentrated.tfplot	7
concentrateOnly	7
concentrateOriginal	8
concentrate	9
concentrator	10
end.TScanonicalPrediction	11
estConcentratedModel	12
estProjection	13
l.TSmodelconcentrate	14
nseriesInput.TSmodelconcentrate	14
percentChange.TScanonicalPrediction	15
plot2by2	15
print.concentrate	16
reconstitute	16

selectSeries.concentrate	17
tfplot.concentrate	18
tfprint.concentrate	19
tframed.concentrate	19
tfwindow.concentrate	20
TSdata.TSdataconcentrate	20

Index	22
--------------	-----------

00Intro.juice	<i>Juice</i>
---------------	--------------

Description

The attempted approach is that a model of type `TSmodelconcentrate` should work like KF and ARMA model, so that `plot`, `residual`, etc., produce results for the full (reconstituted) data set. Special methods (eg. `concentrated.tfplot`, `concentrated.checkResiduals`) do the equivalent thing using the reduced dimensional data as the `TSdata` and dropping the fact that the model is of class `TSmodelconcentrate`.

The `outputData` for a concentrated object is the original data, but for a reconstituted object it is the reconstituted data. So, for example, `tfplot(ConcentratedDataObject)` will plot the original data (as well as the reconstructed data) whereas `tfplot(reconstitute(ConcentratedDataObject))` plots only the reconstituted data. (To plot the concentrated series use `concentrated.tfplot(ConcentratedDataObject)`).

Typically one should not work with a reconstituted object unless it is explicitly needed, as the original data is "hidden".

The concentrated data is extracted from both `TSdataconcentrate` and `TSdatareconstitute` using the function `concentrated.outputData`.

canonical.prediction	<i>Canonical Prediction</i>
----------------------	-----------------------------

Description

Use canonical correlation with input data as the independent variables used to predict output data.

Usage

```
canonical.prediction(d, conc=concentrator(d),
                    q=min(concentrated.nseriesInput(d),
                          concentrated.nseriesOutput(d)))
is.TScanonicalPrediction(x)
```

Arguments

<code>d</code>	a <code>TSdataconcentrate</code> object as returned by <code>concentrate</code> .
<code>conc</code>	a <code>concentrator</code> .
<code>q</code>	integer indicating the number of canonical variates to keep.
<code>x</code>	any object.

Details

Data `d` as returned by `concentrate`. Alternately, a different `conc` (`proj`) can be used. Use `q` canonical variates from input data as predictors of `q` canonical variates from output data and then use these to reconstruct output data. (ref T.W. Anderson p491) `q` cannot exceed `min(concentrated.nseriesInput(d), concentrated.nseriesOutput(d))`

Value

A `TScanonicalPrediction` object.

See Also

[concentrate](#) [concentrator](#)

Examples

```
data("egl.DSE.data.diff", package="dse1")
z <- canonical.prediction(concentrate(egl.DSE.data.diff))
is.TScanonicalPrediction(z)
```

`checkConsistentDimensions.TSmodelconcentrate`
checkConsistentDimensions Specific Methods

Description

See the generic function description.

Usage

```
## S3 method for class 'TSmodelconcentrate':
checkConsistentDimensions(obj1, obj2=NULL)
```

Arguments

`obj1` a `TSmodelconcentrate` object.
`obj2` a matrix of time series or a `TSdata` object.

See Also

[checkConsistentDimensions](#)

```
checkResiduals.TSdataconcentrate
      checkResiduals Specific Methods
```

Description

See the generic function description.

Usage

```
## S3 method for class 'TSdataconcentrate':
checkResiduals(obj, ...)
## S3 method for class 'TSdatareconstitute':
checkResiduals(obj, ...)
## S3 method for class 'concentrated':
checkResiduals(obj, ...)
```

Arguments

obj a TSdataconcentrate object.
 ... arguments passed to checkResiduals.

See Also

[checkResiduals concentrated.checkResiduals](#)

```
concentrated.checkResiduals
      Check Residuals of Concentrated Data
```

Description

The TSdataconcentrate is passed to checkResiduals as simple TSdata in the reduced dimension space (not expanded).

Usage

```
concentrated.checkResiduals(data, ...)
```

Arguments

data a TSdataconcentrate object.
 ... arguments passed to checkResiduals.

Value

x

See Also

[checkResiduals concentrate](#)

```
concentratedDimension  
Concentrated Dimension
```

Description

The dimension (number of series) in concentrate data. This is the dimension onto which the original series has been projected.

Usage

```
concentratedDimension(x)  
## S3 method for class 'concentrate':  
concentratedDimension(x)
```

Arguments

x a concentrated data object.

Value

Depends on the argument. For a simple concentrated data object the result is an integer.

See Also

[concentrated.nseriesInput](#) [concentrated.nseriesOutput](#) [concentrate](#)

Examples

```
data("egl.DSE.data", package="dse1")  
require("stats")  
z <- concentrate(egl.DSE.data)  
concentratedDimension(outputData(z))  
concentrated.nseriesOutput(z)
```

```
concentrated.nseriesInput  
Concentrated Dimension of TSdata
```

Description

The dimension (number of series) in concentrate data. This is the dimension onto which the original series has been projected.

Usage

```
concentrated.nseriesInput(x)  
concentrated.nseriesOutput(x)
```

Arguments

`x` A concentrated TSdata object.

Value

An integer.

See Also

[concentratedDimension](#) [concentrate](#)

Examples

```
data("egl.DSE.data", package="dse1")
require("stats")
z <- concentrate(egl.DSE.data)
concentrated.nseriesOutput(z)
```

concentratedSeriesNames

Concentrated Series Names

Description

The names of series in concentrate data.

Usage

```
concentratedSeriesNames(x)
## S3 method for class 'concentrate':
concentratedSeriesNames(x)
## S3 method for class 'TSdata':
concentratedSeriesNames(x)
concentratedSeriesNamesInput(x)
concentratedSeriesNamesOutput(x)
```

Arguments

`x` A concentrated data object.

Value

Depends on the argument. For a simple concentrated data object the result is a vector of strings.

See Also

[seriesNames](#) [seriesNamesInput](#) [seriesNamesOutput](#) [concentratedDimension](#)
[concentrate](#)

Examples

```
data("egl.DSE.data", package="dse1")
require("stats")
z <- concentrate(egl.DSE.data)
concentratedSeriesNames(z)
```

`concentrated.tfplot`*Plot Concentrated Series*

Description

The concentrate data is plotted.

Usage

```
concentrated.tfplot(x, ...)
```

Arguments

<code>x</code>	A concentrated data object.
<code>...</code>	arguments to be passed to other tfplot.

Value

Depends on the argument. For a simple concentrated data object the result is a vector of strings.

See Also

[tfplot](#)

Examples

```
data("egl.DSE.data", package="dse1")
require("stats")
z <- concentrate(egl.DSE.data)
concentrated.tfplot(z)
```

`concentrateOnly`*Extract Concentrate*

Description

`concentrateOnly`

Usage

```

concentrateOnly(d)
## S3 method for class 'concentrate':
concentrateOnly(d)
## S3 method for class 'TSdataconcentrate':
concentrateOnly(d)
## S3 method for class 'TSdatareconstitute':
concentrateOnly(d)
## S3 method for class 'TSestModel':
concentrateOnly(d)
## S3 method for class 'TSmodelconcentrate':
concentrateOnly(d)

```

Arguments

`d` a concentrate object.

Details

The concentrated data set is returned as a TSdata object, stripped of the fact that it is a concentrate.

Value

A TSdata object.

See Also

[concentrate](#) [concentrator](#) [concentrateOriginal](#)

Examples

```

data("egl.DSE.data", package="dse1")
require("stats")
z <- concentrate(egl.DSE.data)
z <- concentrateOnly(z)

```

concentrateOriginal

Extract Original Series

Description

concentrateOriginal

Usage

```

concentrateOriginal(d)
## S3 method for class 'TSdataconcentrate':
concentrateOriginal(d)
## S3 method for class 'TSdatareconstitute':
concentrateOriginal(d)
## S3 method for class 'concentrate':

```

```
concentrateOriginal(d)
## S3 method for class 'TScanonicalPrediction':
concentrateOriginal(d)
```

Arguments

`d` A concentrate object.

Details

The original data set is returned as a TSdata object, stripped of the fact that it is a concentrate.

Value

A TSdata object.

See Also

[concentrate](#) [concentrator](#) [concentrateOnly](#)

Examples

```
data("egl.DSE.data", package="dse1")
require("stats")
z <- concentrate(egl.DSE.data)
z <- concentrateOriginal(z)
```

concentrate

Concentrate Series in a TSdata Object

Description

Calculate a reduced dimension version of the data using principal components (or canonical correlation for TSdata with input and output).

Usage

```
concentrate(d, conc=NULL, center=TRUE, scale=TRUE, ...)
## Default S3 method:
concentrate(d, conc=NULL, center=TRUE, scale=TRUE, n=1, ...)
## S3 method for class 'TSdata':
concentrate(d, conc=NULL, center=TRUE, scale=TRUE, m=1, p=1, ...)
is.concentrate(x)
is.TSdataconcentrate(x)
is.TSmodelconcentrate(x)
```

Arguments

d	a matrix or TSdata object.
...	arguments to be passed to other methods.
conc	object containing the concentrator (projection) matrix used for the reduction
center	center the observations to mean zero first (passed to estProjection).
scale	scale the observations to SD one first (passed to estProjection).
n	dimension of the concentrated series (passed to estProjection).
m	dimension of the concentrated input series (passed to estProjection).
p	dimension of the concentrated output series (passed to estProjection).
x	any object.

Value

A matrix or TSdata object.

See Also

[estProjection](#) [reconstitute](#) [prcomp](#)

Examples

```
data("egl.DSE.data", package="dse1")
require("stats")
z <- concentrate(egl.DSE.data)
is.concentrate(z)
```

concentrator

Data Concentrator

Description

concentrator

Usage

```
concentrator(d)
## S3 method for class 'concentrate':
concentrator(d)
## S3 method for class 'concentrator':
concentrator(d)
## S3 method for class 'TSdata':
concentrator(d)
## S3 method for class 'TSdataconcentrator':
concentrator(d)
## S3 method for class 'TSmodelconcentrate':
concentrator(d)
is.concentrator(x)
is.TSdataconcentrator(x)
```

Arguments

`d` a concentrate or concentrator object.
`x` any object.

Details

The concentrator is extracted from a concentrated data object.

Value

A concentrator.

See Also

[concentrate](#) [concentrateOnly](#) [concentrateOriginal](#)

Examples

```
data("egl.DSE.data", package="dse1")
require("stats")
z <- concentrate(egl.DSE.data)
concentrator(z)
is.concentrator(concentrator(z))
```

end.TScanonicalPrediction

Specific Methods for TScanonicalPrediction

Description

See the generic function description.

Usage

```
## S3 method for class 'TScanonicalPrediction':
end(x, ...)
## S3 method for class 'TScanonicalPrediction':
start(x, ...)
## S3 method for class 'TScanonicalPrediction':
periods(x)
## S3 method for class 'TScanonicalPrediction':
frequency(x, ...)
```

Arguments

`x` An object containing TSdata.
`...` (further arguments, currently disregarded).

Value

Depends.

See Also

[end start periods frequency](#)

```
estConcentratedModel
```

Estimate a Concentrated Model

Description

estConcentratedModel

Usage

```
estConcentratedModel(data, estimation="estVARXls",
                      estimation.args=NULL, ...)
## S3 method for class 'TSdata':
estConcentratedModel(data, estimation="estVARXls",
                      estimation.args=NULL, m=1, p=1, center=TRUE, scale=TRUE, ...)
## S3 method for class 'TSdataconcentrate':
estConcentratedModel(data,
                      estimation="estVARXls", estimation.args=NULL, warn=TRUE, ...)
```

Arguments

data	A TSdata or TSdataconcentrate object.
estimation	Estimation method.
estimation.args	Estimation method arguments.
m, p	dimension of the concentrated series.
center	center the observations to mean zero first.
scale	scale the observations to SD one first.
warn	logical indicating if certain warning messages should be printed.
...	arguments to be passed to other methods.

Details

A concentrated version of the data (reduced dimension) is used to estimate a reduced dimension model. The projections for concentrating the data are retained so that model predictions can be expanded to the full dimension data space.

If data is TSdataconcentrate then the concentrator with that data is used and m, p, center and scale are not used. For TSdata these arguments are used to first estimate a concentrated version of the data.

Value

A TSmodelconcentrate.

See Also

[concentrate](#) [concentrator](#) [estProjection](#)

Examples

```
data("egl.DSE.data.diff", package="dse1")
model <- estConcentratedModel(egl.DSE.data.diff)
```

estProjection	<i>Calculate Projection from Concentrating Series.</i>
---------------	--

Description

Calculate the projection to use for a reduced dimension version of the data using principal components (or canonical correlation for TSdata with input and output).

Usage

```
estProjection(data, center=TRUE, scale=TRUE, ...)
## Default S3 method:
estProjection(data, center=TRUE, scale=TRUE, n=1, ...)
## S3 method for class 'TSdata':
estProjection(data, center=TRUE, scale=TRUE, m=1,p=1, ...)
```

Arguments

data	a matrix for the default method or TSdata object.
n	dimension of the concentrated series.
m	dimension of the concentrated input series.
p	dimension of the concentrated output series.
center	logical indicating center the observations to mean zero first.
scale	logical indicating scale the observations to SD one first.
...	arguments passed to other methods.

Value

An object containing matrix (conc) to use to concentrate the data.

See Also

[estConcentratedModel](#) [concentrate](#) [reconstitute](#) [prcomp](#)

Examples

```
data("egl.DSE.data", package="dse1")
require("stats")
z <- estProjection(egl.DSE.data)
```

l.TSmodelconcentrate

Specific Methods for l

Description

See the generic function description.

Usage

```
## S3 method for class 'TSmodelconcentrate':
l(obj1, obj2, sampleT=nrow(outputData(obj2)),
  predictT=sampleT, result=NULL, warn=TRUE, ...)
```

Arguments

obj1	a TSmodelconcentrate model object.
obj2	a TSdataconcentrate data object.
sampleT	an integer indicating the number of periods of data to use.
predictT	an integer to what period forecasts should be extrapolated.
result	if non-NULL then the returned value is only the sub-element indicated by result. result can be a character string or integer.
warn	if FALSE then certain warning messages are turned off.
...	arguments passed to other methods.

See Also

[l l.ARMA l.SS](#)

nseriesInput.TSmodelconcentrate

Specific Methods for input/nseriesOutput

Description

See the generic function description.

Usage

```
## S3 method for class 'TSmodelconcentrate':
nseriesInput(x)
## S3 method for class 'TSmodelconcentrate':
nseriesOutput(x)
```

Arguments

x	a TSdata or TSmodelconcentrate object.
---	--

See Also

[nseriesInput](#) [nseriesOutput](#)

percentChange.TScanonicalPrediction
Specific Methods for percentChange

Description

See the generic function description.

Usage

```
## S3 method for class 'TScanonicalPrediction':
percentChange(obj,
              base=NULL, lag=1, cumulate=FALSE, e=FALSE, ...)
```

Arguments

obj	see the generic function.
e	see the generic function.
base	see the generic function.
lag	see the generic function.
cumulate	see the generic function.
...	arguments passed to other methods.

See Also

[percentChange](#)

plot2by2	<i>plot2by2</i>
----------	-----------------

Description

plot data series one vs another, two at a time (that is, data[,i] vs data[,j] for all i,j (not on time axis)).

Usage

```
plot2by2(data, ...)
## Default S3 method:
plot2by2(data, pch=".", ...)
## S3 method for class 'TSdata':
plot2by2(data, ...)
```

Arguments

data	a matrix of time series or a TSdata object.
pch	character to be used for plotting.
...	arguments passed to tfplot.

Value

None.

`print.concentrate` *Print Specific Methods*

Description

See the generic function description.

Usage

```
## S3 method for class 'concentrate':
print(x, ...)
```

Arguments

`x` a concentrate object.
`...` arguments to be passed to other methods.

See Also

[print](#)

`reconstitute` *Reconstitute*

Description

`reconstitute`

Usage

```
reconstitute(d, conc=NULL, names=NULL)
## Default S3 method:
reconstitute(d, conc=NULL, names=seriesNames(d))
## S3 method for class 'concentrate':
reconstitute(d, conc=concentrator(d),
              names=seriesNames(d))
## S3 method for class 'TSdataconcentrate':
reconstitute(d, conc=concentrator(d),
              names=seriesNames(d))
is.TSdatareconstitute(x)
```

Arguments

`d` a concentrated data object.
`conc` a concentrator.
`names` series names for the result.
`x` any object.

Details

A concentrated data object is used to reconstruct the full dimension data. Thus the result has the same dimension as the original data, but will not be exactly the same because some information is lost when the data is concentrated (unless the concentrate has the full dimension of the original data, which would usually be pointless).

Value

Depends on the argument.

See Also

[concentrate](#)

Examples

```
data("egl.DSE.data", package="dse1")
require("stats")
z <- concentrate(egl.DSE.data)
z <- reconstitute(z)
is.TSdatareconstitute(z)
```

selectSeries.concentrate

Specific Methods for selectSeries

Description

See the generic function description.

Usage

```
## S3 method for class 'concentrate':
selectSeries(x,
             series = seq(nrow(concentrator(x)$proj)))
```

Arguments

x	a concentrate data object.
series	vector of strings or integers indicating series to select.

See Also

[selectSeries](#)

tfplot.concentrate *tfplot Specific Methods*

Description

See the generic function description.

Usage

```
## S3 method for class 'concentrate':
tfplot(x,
       tf=NULL, start=tfstart(tf), end=tfend(tf),
       series=seq(nseries(x)),
       Title=NULL, xlab=NULL, ylab=NULL,
       graphs.per.page=5, mar=par()$mar, reset.screen=TRUE, ...)
## S3 method for class 'TScanonicalPrediction':
tfplot(x,
       tf=NULL, start=tfstart(tf), end=tfend(tf),
       series=seq(nseries(x)),
       Title=NULL, xlab=NULL, ylab=NULL,
       graphs.per.page=5, mar=par()$mar, reset.screen=TRUE, ...)
## S3 method for class 'TSdataconcentrate':
tfplot(x,
       tf=NULL, start=tfstart(tf), end=tfend(tf),
       select.inputs = seq(length = nseriesInput(x)),
       select.outputs = seq(length = nseriesOutput(x)),
       Title = NULL, xlab = NULL, ylab = NULL,
       graphs.per.page = 5, mar=par()$mar, reset.screen =TRUE, ...)
## S3 method for class 'TSdatareconstitute':
tfplot(x, ...)
```

Arguments

<code>x</code>	an object to plot.
<code>start</code>	see the generic <code>tfplot</code> .
<code>end</code>	see the generic <code>tfplot</code> .
<code>tf</code>	see the generic <code>tfplot</code> .
<code>series</code>	see the generic <code>tfplot</code> .
<code>select.inputs</code>	see the generic <code>tfplot</code> .
<code>select.outputs</code>	see the generic <code>tfplot</code> .
<code>Title</code>	see the generic <code>tfplot</code> .
<code>xlab</code>	see the generic <code>tfplot</code> .
<code>ylab</code>	see the generic <code>tfplot</code> .
<code>graphs.per.page</code>	see the generic <code>tfplot</code> .
<code>mar</code>	see the generic <code>tfplot</code> .
<code>reset.screen</code>	see the generic <code>tfplot</code> .
<code>...</code>	arguments to be passed to other methods.

See Also[tfplot](#)

`tfprint.concentrate`*Tfprint Specific Methods*

Description

See the generic function description.

Usage

```
## S3 method for class 'concentrate':
tfprint(x, ...)
```

Arguments

`x` a concentrate object to print.
`...` arguments to be passed to other methods.

See Also[tfprint](#)

`tframed.concentrate`*Construct a Tframed Object*

Description

Create a tframed object or set the tframe of an object.

Usage

```
## S3 method for class 'concentrate':
tframed(x, tf=NULL, names = NULL)
## S3 method for class 'concentrate':
tframe(x) <- value
```

Arguments

`x` a (tframed) concentrate object or a concentrate object to be tframed.
`tf` a tframe attribute to be applied to `x`.
`names` optional (new) series names to be applied to `x`.

Details

See the generic.

Value

A tframed object.

See Also

[tframe](#)

`tfwindow.concentrate`
tfwindow Specific Methods

Description

See the generic function description.

Usage

```
## S3 method for class 'concentrate':
tfwindow(x, tf=NULL,
         start=tfstart(tf), end=tfend(tf), warn=TRUE)
```

Arguments

<code>x</code>	a concentrate object to truncate.
<code>start</code>	A start date of a format compatible with the time series
<code>end</code>	An end date of a format compatible with the time series
<code>tf</code>	A tframe or tframed object
<code>warn</code>	A logical indicating if warning should be produced

See Also

[tfwindow](#)

`TSdata.TSdataconcentrate`
TSdata Specific Methods

Description

See the generic function description.

Usage

```
## S3 method for class 'TSdataconcentrate':
TSdata(data, names=NULL, ...)
```

Arguments

<code>data</code>	a <code>TSdataconcentrate</code> object from which to get <code>TSdata</code> .
<code>names</code>	series names for the result.
<code>...</code>	arguments to be passed to other methods.

Details

Uses `reconstitute` to build `TSdata`.

See Also

[reconstitute TSdata](#)

Index

- *Topic **internal**
 - tframed.concentrate, 19
- *Topic **programming**
 - tframed.concentrate, 19
- *Topic **ts**
 - 00Intro.juice, 1
 - canonical.prediction, 2
 - checkConsistentDimensions.TSmodelconcentrate, 3
 - checkResiduals.TSdataconcentrate, 3
 - concentrate, 9
 - concentrated.checkResiduals, 4
 - concentrated.nseriesInput, 5
 - concentrated.tfplot, 6
 - concentratedDimension, 4
 - concentratedSeriesNames, 6
 - concentrateOnly, 7
 - concentrateOriginal, 8
 - concentrator, 10
 - end.TScanonicalPrediction, 11
 - estConcentratedModel, 11
 - estProjection, 12
 - l.TSmodelconcentrate, 13
 - nseriesInput.TSmodelconcentrate, 14
 - percentChange.TScanonicalPrediction, 14
 - plot2by2, 15
 - print.concentrate, 15
 - reconstitute, 16
 - selectSeries.concentrate, 17
 - tfplot.concentrate, 17
 - tfprint.concentrate, 18
 - tfwindow.concentrate, 19
 - TSdata.TSdataconcentrate, 20
- *Topic **utilities**
 - tframed.concentrate, 19
 - 00Intro.juice, 1
 - canonical.prediction, 2
 - checkConsistentDimensions, 3
 - checkConsistentDimensions.TSmodelconcentrate, 3
 - checkResiduals, 3, 4
 - checkResiduals.concentrated (*checkResiduals.TSdataconcentrate*), 3
 - checkResiduals.TSdataconcentrate, 3
 - checkResiduals.TSdatareconstitute (*checkResiduals.TSdataconcentrate*), 3
 - concentrate, 2, 4–6, 8, 9, 10, 12, 13, 16
 - concentrated.checkResiduals, 3, 4
 - concentrated.nseriesInput, 5, 5
 - concentrated.nseriesOutput, 5
 - concentrated.nseriesOutput (*concentrated.nseriesInput*), 5
 - concentrated.tfplot, 6
 - concentratedDimension, 4, 5, 6
 - concentratedSeriesNames, 6
 - concentratedSeriesNamesInput (*concentratedSeriesNames*), 6
 - concentratedSeriesNamesOutput (*concentratedSeriesNames*), 6
 - concentrateOnly, 7, 8, 10
 - concentrateOriginal, 8, 8, 10
 - concentrator, 2, 8, 10, 12
 - end, 11
 - end.TScanonicalPrediction, 11
 - estConcentratedModel, 11, 13
 - estProjection, 9, 12, 12
 - frequency, 11
 - frequency.TScanonicalPrediction (*end.TScanonicalPrediction*), 11
 - is.concentrate (*concentrate*), 9
 - is.concentrator (*concentrator*), 10

is.TScanonicalPrediction
 (*canonical.prediction*), 2
 is.TSdataconcentrate
 (*concentrate*), 9
 is.TSdataconcentrator
 (*concentrator*), 10
 is.TSdatareconstitute
 (*reconstitute*), 16
 is.TSmodelconcentrate
 (*concentrate*), 9

 l, 13
 l.ARMA, 13
 l.SS, 13
 l.TSmodelconcentrate, 13

 nseriesInput, 14
 nseriesInput.TSmodelconcentrate,
 14
 nseriesOutput, 14
 nseriesOutput.TSmodelconcentrate
 (*nseriesInput.TSmodelconcentrate*),
 14

 percentChange, 14
 percentChange.TScanonicalPrediction,
 14
 periods, 11
 periods.TScanonicalPrediction
 (*end.TScanonicalPrediction*),
 11
 plot2by2, 15
 prcomp, 9, 13
 print, 15
 print.concentrate, 15

 reconstitute, 9, 13, 16, 20

 selectSeries, 17
 selectSeries.concentrate, 17
 seriesNames, 6
 seriesNamesInput, 6
 seriesNamesOutput, 6
 start, 11
 start.TScanonicalPrediction
 (*end.TScanonicalPrediction*),
 11

 tfplot, 7, 18
 tfplot.concentrate, 17
 tfplot.TScanonicalPrediction
 (*tfplot.concentrate*), 17
 tfplot.TSdataconcentrate
 (*tfplot.concentrate*), 17

 tfplot.TSdatareconstitute
 (*tfplot.concentrate*), 17
 tfprint, 18
 tfprint.concentrate, 18
 tframe, 19
 tframe<- .concentrate
 (*tframed.concentrate*), 19
 tframed.concentrate, 19
 tfwindow, 20
 tfwindow.concentrate, 19
 TSdata, 20
 TSdata.TSdataconcentrate, 20