

TNO report
PG/VGZ/00.038

Multivariate Imputation by Chained Equations

MICE V1.14 User's manual

TNO Prevention and Health

Public Health
Wassenaarseweg 56
P.O.Box 2215
2301 CE Leiden
The Netherlands

Tel + 31 71 518 18 18
Fax + 31 71 518 19 20

Date

September 2005

Author(s)

S. van Buuren
C.G.M. Oudshoorn

The Quality System of the
TNO Institute Prevention
and Health has been certified in
accordance with ISO 9001

All rights reserved.

In case this report was drafted on
instructions, the rights and obligations of
contracting parties are subject to either
the Standard Conditions for Research
Instructions given to TNO, or the relevant
agreement concluded between the
contracting parties. Submitting the report
for inspection to parties who have a direct
interest is permitted.

© 2000 TNO

Author

S. van Buuren, C.G.M. Oudshoorn

Project number

011.40684/01.01

ISBN-number

90-6743-677-1

GRANT OF PERMISSION

PERMISSION IS GRANTED TO USE, COPY AND DISTRIBUTE THIS SOFTWARE FOR NON-COMMERCIAL AND SCIENTIFIC PURPOSES, SO LONG AS NO FEE IS CHARGED AND SO LONG AS THE COPYRIGHT NOTICE ABOVE, THIS GRANT OF PERMISSION, AND THE DISCLAIMER BELOW APPEAR IN ALL COPIES MADE; AND SO LONG AS THE NAME OF TNO IS NOT USED IN ANY ADVERTISING OR PUBLICITY PERTAINING TO THE USE OR DISTRIBUTION OF THIS SOFTWARE WITHOUT SPECIFIC, WRITTEN PRIOR AUTHORIZATION.

PERMISSION TO MODIFY OR OTHERWISE CREATE DERIVATIVE WORKS OF THIS SOFTWARE IS NOT GRANTED.

DISCLAIMER

THIS SOFTWARE IS PROVIDED AS IS, WITHOUT REPRESENTATION AS TO ITS FITNESS FOR ANY PURPOSE, AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. TNO SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WITH RESPECT TO ANY CLAIM ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE SOFTWARE, EVEN IF IT HAS BEEN OR IS HEREAFTER ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

This report can be ordered from TNO-PG by transferring *f* 21 (incl. VAT) to account number 99.889 of TNO-PG Leiden. Please state TNO-PG publication number PG/VGZ/00.038

Contents

Contents.....	3
1Introduction.....	5
2Installation.....	6
3A simple example.....	7
4Specification of the imputation model.....	10
4.1Elementary imputation methods.....	10
4.2Adding your own imputation functions.....	11
4.3Transformations and index variables	12
4.4Visiting scheme.....	14
4.5Choice of predictors.....	14
4.6General advice in choosing predictors.....	15
5Running mice.....	17
5.1Studying convergence.....	17
5.2Step by step.....	18
5.3Running problems.....	19
5.4Studying the initial solution.....	19
5.5Using (starting) imputations created by other software.....	20
6After mice.....	21
6.1Overview.....	21
6.2Extracting imputed data.....	21
6.3Complete data analysis.....	22
6.4Pooling.....	22
References.....	24

1 Introduction

Multiple imputation (Rubin, 1987, 1996) is the method of choice for complex incomplete data problems. Schafer (1999) contains introductory material about the use of multiple imputation (MI). Other information about MI can be found in *Multiple Imputation Online* at

www.multiple-imputation.com

This document describes the `mice` library, which runs under S-Plus V4.5 and S-Plus 2000 for Windows. The library assists in performing the steps required in a full multiple imputation (MI) analysis: generation of imputations, repeated analyses on the imputed data, and pooling of the results.

Specific features of the software are:

- columnwise specification of the imputation model;
- arbitrary patterns of missing data;
- transformations and index variables;
- subset selection of predictors;
- supports standard `lm` and `glm` complete-data methods;
- automated pooling using the Barnard-Rubin adjustment;
- callable user-written imputation functions;
- online help files.

This document describes how the tools of the `mice` library can be used. The software was programmed in the S-Plus programming language.

The intended audience of the software consists of S-Plus users with S-Plus programming experience and with sound statistical capabilities who wish to solve incomplete data problems in a principled way. This document does not discuss problems of incomplete data in general (see the books by Little & Rubin, 1987 or Schafer, 1997), the technique of multiple imputation (see the book by Rubin, 1987 and the 1996-article) or Gibbs sampling methodology (see Gelfand and Smith, 1990).

2 Installation

The `mice` library runs under S-Plus 4.5 and S-Plus 2000. The simplest way to install `mice` is to copy the `mice` directory into the standard library directory, under Windows NT typically something like `C:/Program Files/sp2000/library`. The following S-plus command makes the functions available to the current session:

```
> library(mice)
```

It is also possible to install `mice` outside the standard S-Plus library, which might be useful for example if S-Plus runs on a network. The library can then be attached with a statement like

```
> library(mice, lib.loc = "C:\\mylib")
```

where the distributed `mice` directory is assumed to be located in the directory `C:\\mylib`.

The library is 'pure S-Plus' and does not use any compiled code. It should therefore also work on other systems, but this has not been tested. Check the documentation of your local system on attaching libraries.

3 A simple example

The data frame `nhanes` in the `mice` library contains example data from Schafer (1997, page 237). Suppose that the incomplete data are collected in either a matrix or data frame, where missing values are coded as NA's.

```
> nhanes
  age  bmi hyp chl
1   1   NA  NA  NA
2   2 22.7   1 187
3   1   NA   1 187
4   3   NA  NA  NA
5   1 20.4   1 113
...

```

The number of the NA's can be counted and visualized as follows:

```
> md.pattern(nhanes)
  age hyp bmi chl
13  1  1  1  1  0
  1  1  1  0  1  1
  3  1  1  1  0  1
  1  1  0  0  1  2
  7  1  0  0  0  3
    0  8  9 10 27

```

There are 13 (out of 25) rows that are complete, there is one for which only `bmi` is missing, and there are seven cases for which only `age` is known. The total number of missing values is equal to $(7*3)+(1*2)+(3*1)+(1*1) = 27$. Most missing values (10) occur in `chl`.

The imputation algorithm is implemented in a function called `mice`. The function is invoked as

```
> imp <- mice(nhanes)
...

```

which results in the object `imp` of a special class `mids` for storing multiple imputations. To see the results of the imputation, type

```
> imp
Multiply imputed data set
Call:
mice(data = nhanes)
Number of multiple imputations: 5
Missing cells per column:
  age bmi hyp chl
   0  9  8 10

```

```

Imputation methods:
  age  bmi  hyp  chl
  ""  "pmm" "pmm" "pmm"
VisitSequence:
  bmi hyp chl
  2   3   4
PredictorMatrix:
  age bmi hyp chl
age  0  0  0  0
bmi  1  0  1  1
hyp  1  1  0  1
chl  1  1  1  0
Random generator seed value:  0

```

Imputations are generated according to the default method, which is predictive mean matching (pmm) here. Entries `VisitSequence` and `PredictorMatrix` are algorithmic options that will be discussed later. Imputations for `bmi` are stored in

```

> imp$imp$bmi
  1  2  3  4  5
1 29.6 35.3 33.2 35.3 27.5
3 30.1 30.1 29.6 29.6 29.6
4 24.9 27.2 24.9 24.9 24.9
6 24.9 24.9 20.4 24.9 25.5
10 22.7 26.3 22.7 26.3 27.4
11 30.1 29.6 29.6 27.5 30.1
12 22.7 26.3 28.7 26.3 26.3
16 30.1 30.1 33.2 33.2 27.5
21 33.2 20.4 30.1 20.4 33.2

```

Each row corresponds to a missing entry in the `bmi` variable. The columns contain the different, multiple imputations. The default number of multiple imputations is equal to five. The first completed data set can be obtained as

```

> complete(imp, 1)
  age  bmi hyp chl
1  1 29.6  1 187
2  2 22.7  1 187
3  1 30.1  1 187
4  3 24.9  1 184
5  1 20.4  1 113
...

```

Note that the missing entries in `nhanes` have now been filled by the values from the first imputation.

Suppose that our complete-data analysis involves a linear regression of `chl` on `age` and `hyp`. For this purpose, an adapted function `lm.mids` is available that works on the imputed data:

```
> fit<-lm.mids(chl~age+hyp, imp)
```

which repeatedly calls the standard regression function `lm`. The `fit` object contains the results of five complete-data analyses. These can be pooled as follows:

```
> pool(fit)
Call: pool(object = fit)

Pooled coefficients:
(Intercept)      age      hyp
  136.2802  18.32603  20.59693
```

```
Fraction of information about the coefficients missing due to
nonresponse:
(Intercept)      age      hyp
  0.2504597  0.3239345  0.4771509
```

More extensive output can be obtained, as usual, with the `summary` function, i.e.,

```
> summary(pool(fit))
              est      se      t      df      Pr(>|t|)
(Intercept) 136.28021 28.12605 4.8453373 13.551184 0.0002844227
      age   18.32603 12.45221 1.4717092 11.131217 0.1687990086
      hyp   20.59693 27.84369 0.7397343  7.302421 0.4825601408
              lo 95      hi 95 missing      fmi
(Intercept)  75.767847 196.79257      NA 0.2504597
      age   -9.041727  45.69378      0 0.3239345
      hyp  -44.694201  85.88807      8 0.4771509
```

This completes the full multiple imputation analysis.

4 Specification of the imputation model

4.1 Elementary imputation methods

Data sets typically contain variables with various coding types, e.g., numerical, categorical or binary. Some authors (Brand, 1999; Van Buuren *et al*, 1993, 1999; Raghunathan *et al.*, 1998) have proposed to specify an *elementary imputation method* for each variable that is to be imputed. Given the availability of these, some form of iteration can be used for obtaining imputations. Attractive aspects of this strategy are that model specification takes place on a level that is typically well understood by the user (i.e. the individual variable), and that many methods for creating univariate imputations are available. A disadvantage is that the properties of the combined multivariate distribution of the resulting imputations may not be known, which complicates the assessment of convergence. See Appendix A for more details.

In `mice`, the user can specify an elementary imputation method for each incomplete data column. The elementary imputation method takes a set of (at that moment) complete predictors, and returns a single imputation for each missing entry in the incomplete target column. Multiple imputations are created by repeated calls to the function. The `mice` library supplies a number of built-in elementary imputation models, which are given in Table 4.4.1.

Table 4.4.1 Built-in elementary imputation methods in `mice`.

Method	Description	Type of target
<code>impute.norm</code>	Bayesian linear regression	Numeric
<code>impute.pmm</code>	Predictive mean matching	Numeric
<code>impute.mean</code>	Unconditional mean imputation	Numeric
<code>impute.logreg</code>	Logistic regression	2 categories
<code>impute.logreg2</code>	Logistic regression (direct minimization)	2 categories
<code>impute.polyreg</code>	Polytomous logistic regression	>= 2 categories
<code>impute.lda</code>	Linear discriminant analysis	>= 2 categories
<code>impute.sample</code>	Random sample from the available observed values	Any

The default methods used in the `mice` function are `impute.pmm` for numeric data, `impute.logreg` for binary data (=factors with two categories), and `impute.polyreg` for categorical variables (=factors with more than two categories). These defaults can be changed by the `defaultImputationMethod` argument to the `mice` function. For example

```
> mice(nhanes, defaultImp = c("norm", "logreg", "polyreg"))
```

changes the default method for numerical data to `impute.norm`, while leaving the defaults for binary and categorical data unchanged. The `imputationMethod` argument specifies the imputation method per column and overrides the default. This argument can be either a

string or a vector of strings with length `ncol(data)`. If `imputationMethod` is specified as one string, then all visited columns will be imputed by the technique specified by this string. So

```
> mice(nhanes, imputationMethod = "norm")
```

specifies that `impute.norm` is to be applied on all columns. If `imputationMethod` is vector of strings of length `ncol(data)`, then each column will be imputed by the method indicated by the position in the vector. Columns that need not be imputed have method `"`. For example,

```
> mice(nhanes, imputationMethod = c("", "norm", "pmm", "mean"))
```

uses different methods for different columns. The `nhanes2` data frame contains one polytomous, one binary and two numeric variables. Imputations might be created as

```
> imp <- mice(nhanes2, im=c("polyreg", "pmm", "logreg", "norm"))
```

where `polyreg` is used for the first (categorical) variable, `ppm` for the second (numeric), `logreg` for the third (binary) and `norm` for the fourth variable (numeric). The `im` parameter is a legal S-plus abbreviation of the `imputationMethod` argument. Note: Running this example produces a list of warning messages because the sample size of 25 is actually too small relative to the number of parameters.

If the data contains factors that are used for imputing other variables, the algorithm creates dummy variables and fills these from the corresponding factor variable. The dummy variables are created automatically (and discarded) within the main algorithm, and are automatically imputed where necessary.

Appendix B describes the arguments of the major functions of the `mice` library.

4.2 Adding your own imputation functions

It is possible to write one's own elementary imputation function, and call this function from within the Gibbs sampling algorithm. The easiest way to write such a function is to copy and modify an existing `impute` function, for example `impute.norm`. Note that this only works if the argument list is kept intact. For more information about the proper function arguments, see the help on `impute.norm` or other `impute` functions, e.g. by typing

```
> ?impute.norm
```

The new function can be called by the Gibbs sampler by the `imputationMethod` argument. For example, calling the function `impute.myfunc` for each column can be done by typing

```
> mice(nhanes, imputationMethod="myfunc").
```

4.3 Transformations and index variables

There is often a need for transformed, combined or recoded versions of the data. In the case of incomplete data, one could 1) impute the original, and transform the completed original afterwards, or 2) transform the incomplete original and impute the transformed version. If, however, both the original and the transform are needed within the imputation algorithm, neither of these approaches work because one cannot be sure that the transformation holds between the imputed values of the original and transformed versions.

The `mice` function uses a special mechanism, called 'passive imputation', to deal with such situations. Passive imputation maintains the consistency among different transformations of the same data. The method can be used to ensure that the transform always depends on the most recently generated imputations in the original untransformed data. Passive imputation is invoked by specifying a "~" as the first character of the imputation method. The entire string, including the "~" is interpreted as the formula argument in a call to `model.frame(formula, data[!r[,j],])`. This provides a simple method for specifying a large variety of dependencies among the variables, such as transformed variables, recodes, interactions, sum scores, and so on, that may themselves be needed in other parts of the algorithm. As an example,

```
> imp <- mice(nhanes, imp=c("", "pmm", "pmm", "~log(bmi)"))
```

replaces the missing values in the fourth column by the log of `bmi`, the second column. The result is

```
> complete(imp)
  age  bmi hyp      chl
1   1 29.6  1  3.387774
2   2 22.7  1 187.000000
3   1 30.1  1 187.000000
4   3 24.9  1  3.214868
...
> complete(imp, 2)
  age  bmi hyp      chl
1   1 29.6  1  3.387774
2   2 22.7  1 187.000000
3   1 30.1  1 187.000000
4   3 25.5  2  3.238678
```

Missing entries 1 and 4 in `chl` were replaced by the log of `bmi`. Note that entry 4 takes the imputed values of `bmi` into account. Note also that the nonmissing values in `chl` are simply copied from the data, so as a whole, the column now contains nonsensical data. One easy way

to create consistency is by coding all entries in `chl` as `NA`, but for large data sets, this can be inefficient. Another way is to apply the log transform using available cases beforehand, followed by coding the remainder as `NA`.

An index of more variables can be specified by means of the `I()` operator, e.g. `"~I(0.5*log(age)+hyp)"` computes the sum of half `log(age)` and hypertension status:

```
imp <- mice(cbind(nhanes, index=NA), imp=c("", "pmm", "pmm", "pmm",  
"~I(0.5*log(age)+hyp)"))
```

a discretized version of the imputed variable can be obtained by

```
> imp_mice(cbind(nhanes, obese=NA), imp=c("", "pmm", "pmm", "pmm",  
"~cut(bmi, breaks=c(0, 30, 35, 100))"))
```

and an interaction term of two variables can be created as

```
> imp_mice(cbind(nhanes, int=NA), imp=c("", "pmm", "pmm", "pmm",  
"~I((bmi-25)*hyp)"))
```

so that it is available for imputation.

There are two specific points that need attention when defining transformations through the `"~"` mechanism. First, deterministic relations between columns remain synchronized if the target variable is updated immediately after any of its predictors are imputed. So in the last example above, column `int` should then be updated each time after `bmi` or `hyp` is imputed. This can be done by changing the sequence in which the algorithm visits the columns. See section 4.4 for more details. Second, the `"~"` mechanism may easily lead to linear dependencies among predictors, which produces in a fatal error if both the original and the transformed variables are simultaneously used for imputation. One can circumvent this problem by defining the set of predictors such that original and transformed do not jointly occur. Section 4.5 described how to do this.

In S-Plus 4.5, the `mice` function will error if any column consists entirely of `NA`'s. The `cbind(nhanes, index=NA)` arguments creates such a data set. A workaround to the problem is to compute the values of `index` for the nonmissing cases before entering the `mice` function.

4.4 Visiting scheme

The standard algorithm imputes each incomplete column in the data from left to right. The visitation scheme of the Gibbs sampler is essentially irrelevant as long as each column is visited often enough, but some schemes are more efficient than others. Also, as indicated in sec-

tion 4.3, the visiting scheme plays a role in keeping relations between variables synchronised and consistent with the current set of imputations.

It is possible to alter the default visiting scheme by the `visitSequence` argument of the `mice` function. This is a vector of integers of arbitrary length, specifying the visiting sequence, that is, the column order that is used to impute the data during one iteration of the algorithm. Note that a given column may be visited more than once within the same iteration. All columns with missing data that are used as predictors should be visited, or else the function will stop with an error.

Continuing the interaction example of section 4.3, we can take care that the interaction term is always up to date by the following command:

```
> imp_mice(cbind(nhanes, int=NA), imp=c("", "pmm", "pmm", "pmm",
"~I((bmi-25)*hyp)"), visitSequence=c(2, 5, 3, 5, 4))
```

Using the statement, the algorithm will visit column 5 immediately after column 2 or column 3.

4.5 Choice of predictors

The argument `predictorMatrix` of the `mice` function is a square matrix of size `ncol(data)` containing 0/1 data. This matrix specifies the set of predictors to be used for each incomplete column. If `diagnostics=T`, then the object returned by `mice` contains the predictor matrix used for imputation, e.g.

```
> imp$predictorMatrix
      age  bmi  hyp  chl
age    0    0    0    0
bmi    1    0    1    1
hyp    1    1    0    1
chl    1    1    1    0
```

Rows correspond to incomplete target variables, in the sequence as they appear in data. A value of '1' indicates that the column variable is used as a predictor for the target (row) variable. Thus, in the above example, `age`, `hyp` and `chl` are predictors for imputing `bmi`. The diagonal of `predictorMatrix` is zero. The default setting implies that for every incomplete column all other columns are used as predictors. However, for variables that are complete (`age` in the above example) predictors are automatically removed.

The user can specify a `predictorMatrix`, thereby effectively limiting the number of predictors per variable. For example, suppose that `bmi` is not needed as a predictor. Setting all entries in the `bmi` column to zero removes it from the predictor set of all other variables, e.g.

```
> my.predictorMatrix
      age  bmi  hyp  chl
age    0    0    0    0
bmi    1    0    1    1
hyp    1    0    0    1
chl    1    0    1    0
```

will not use `bmi` as a predictor, but still impute it. The `predictorMatrix` argument is especially useful when dealing with data sets with a large number of variables. The next section contains some advice regarding the selection of predictors.

4.6 General advice in choosing predictors

As a general rule, using every available bit of available information yields multiple imputations that have minimal bias and maximal certainty. This principle implies that the number of predictors in should be chosen as large as possible. Some authors observed that including as many predictors as possible tends to make the MAR assumption more plausible, thus reducing the need to make special adjustments for NMAR mechanisms.

However, data sets often contain several hundreds of variables, all of which can potentially be used to generate imputations. It is not feasible (because of multicollinearity and computational problems) to include all these variables. It is also not necessary. In our experience, the increase in explained variance in linear regression is typically negligible after the best, say, 15 variables have been included. For imputation purposes, it is expedient to select a suitable subset of data that contains no more than 15 to 25 variables. Van Buuren et al (1999) provide the following strategy for selecting predictor variables from a large data base:

1. Include all variables that appear in the complete-data model. Failure to do so may bias the complete-data analysis, especially if the complete-data model contains strong predictive relations. Note that this step is somewhat counter-intuitive, as it may seem that imputation would artificially strengthen the relations of the complete-data model, which is clearly undesirable. If done properly however, this is not the case. On the contrary, not including the complete-data model variables will tend to bias the results towards zero.
2. In addition, include the variables that appear in the response model. Factors that are known to have influenced the occurrence of missing data (stratification, reasons for nonresponse) are to be included on substantive grounds. Others variables of interest are those for which the distributions differ between the response and nonresponse groups. These can be found by inspecting their correlations with the response indicator of the target variable (i.e. the variable to be imputed). If the magnitude of this correlation exceeds a certain level, then the variable is included.


3. In addition, include variables that explain a considerable amount of variance of the target variable. Such predictors help to reduce the uncertainty of the imputations. They are crudely identified by their correlation with the target variable.
4. Remove from the variables selected in steps 2 and 3 those variables that have too many missing values within the subgroup of incomplete cases. A simple indicator is the percentage of observed cases within this subgroup, the percentage of usable cases.

Typically, many predictors used for imputation are incomplete themselves. In principle, one could apply the above modelling steps for each incomplete predictor in turn, but this may lead to a cascade of auxiliary imputation problems. In doing so, one runs the risk that every variable needs to be included after all. In practice, there is often a small set of key variables, for which imputations are needed, which suggests that steps 1 through 4 are to be performed for key variables only. This was the approach taken in Van Buuren, Boshuizen and Knook (1999), but it may miss important second level predictors in the data. A safer and more efficient, though more laborious, strategy is to perform the modeling steps for all incomplete level-1 predictors. This is done in Oudshoorn et al. (1999). We expect that it is rarely necessary to go beyond this level.

5 Running mice

5.1 Studying convergence

There is no clear-cut method for determining whether the Gibbs sampling algorithm has converged. Plotting the `mids` object (as produced by `mice`) yields a graphic display of the mean and standard deviation of the *imputations*. On convergence, the traces should be intermingled with each other, without showing any definite trends. Stated more precisely: convergence is diagnosed when the variance between different sequences is no larger than the variance with each individual sequence. Here is an example of the display that `mice` produces after 5 iterations:



The means (of the imputed values only) per iteration-imputation combination are plotted on the left, the standard deviations of the imputations (within the same replication) on the right. The plots are a bit crude because the number of missing entries is small (9, 11 and 10). It is somewhat hard to assess convergence in this case. Plotting longer iteration sequences of more missing entries will generally convey a better idea whether the between-imputation variability has stabilized and whether the estimates are free of trend.

Note that one iteration of the algorithm involves a lot of work, e.g. for each variable and each multiple imputation a statistical model is fitted, imputations are drawn and data are updated. The needed number of main iterations in `mice` is typically much lower than is common in modern Markov Chain simulation techniques, that often require thousands of iterations. No iterations need to be wasted for achieving independence in the imputations themselves, since elementary imputation procedures create imputations that are already statistically independent for a given value of the regression parameters. Thus, the primary function of the Gibbs sampler as implemented here, is to create independence between the posterior distributions of the regression coefficients. The main question is whether the number of iterations is enough to stabilize the distributions of the parameters. Brand's simulation was based on moderate amounts of missing data and was done with just 5 iterations with satisfactory performance. (Brand, 1999). For large amounts of missing data, convergence can be slower though. In general, we obtained good results with as few as 5 or 10 iterations.

Note that the plot focuses on the mean and variance of the imputations. This may not correspond to the parameter of most interest. Section 5.2 describes a more refined method for studying convergence.

5.2 Step by step

This `mice.mids` function enables the user to split up the computations of the Gibbs sampler into smaller parts by providing a stopping point after every full iteration. There are various circumstances in which this might be useful:

- Due to the way in which S-Plus handles loops, RAM memory may become easily exhausted if the number of iterations is large. Returning to prompt/session level may alleviate these problems;
- The user may want to compute special convergence statistics at specific points, e.g. after each iteration, for monitoring convergence;
- For computing a 'few extra iterations'.

The imputation model itself is specified in the `mice()` function and cannot be changed with `mice.mids`. The state of the random generator is saved with the `mids`-object.

As a simple example, the statements

```
> imp1 <- mice(nhanes,maxit=1)
> ... anything you like to do here
> imp2 <- mice.mids(imp1)
```

yield the same result as

```
> imp <- mice(nhanes,maxit=2)
```

To check convergence of an arbitrary parameter of interest, one could write a function that loops over `mice.mids`, and that extracts imputed data with the `complete` function, and that recomputes the parameter after each iteration using the current imputations. More in particular, one could set `maxit` to 1, generate imputations, compute the statistic of interest on the completed data, save the result, compute the second iteration using `mice.mids`, and so on.

5.3 Running problems

The `mice` function was programmed for flexibility, and not to minimise the use of time or resources. Combined with the greedy nature of S-Plus in general and that fact that method does not use compiled functions, this poses some limits to the size of the data sets and the type of data that can be analysed. The time that `mice` needs depends primarily on the choice of the elementary imputation methods. Methods like `impute.norm` or `impute.pmm` are fairly fast, while others, `impute.polyreg` in particular, can be slow. To give an idea of the time needed, we successfully imputed a 4000 by 20 matrix containing a variety of levels in about 15 minutes on a 400 MHz processor.

Collinearity and instability problems occur in the `impute`-functions if the predictors are (almost) linearly related. For example, if one predictor can be written as a linear combination of some others, then this results in messages like `Error in solve.qr(a): apparently singular matrix and Length of longer object is not a multiple of the length of the shorter object in: beta + rv %*% rnorm(ncol(rv))`. The solution is to eliminate duplicate information, for example by specifying a reduced set of predictors. Finding the pair of nearly dependent variables can prove to be difficult and laborious. One trick that we use in practice is to study the last eigenvector of the covariance matrix of the incomplete data. Variables with high values on that factor often cause the problems. Alternatively, one could revert to collinearity diagnostics like the VIF (Kleinbaum et al, 1988) or graphical displays (Cook and Weisburg, 1999). Pedhazur (1973) provides a good discussion on multicollinearity. The ambitious user might like to write elementary imputation functions that are less sensitive to collinearity, for example, based on ridge regression.

5.4 Studying the initial solution

It is possible to create a `mice` object without doing any Gibbs sampling. Simply specify `maxit=0` as an argument to the `mice` function. This allows you to get hold of the initial imputations (starting values).

5.5 Using (starting) imputations created by other software

It is possible to transform data from other imputation software into a `mids` object. First create a `mids` object by calling `mice` on the incomplete data using `maxit=0`. Then, manually replace the starting imputations in the `mids` object by the values generated by the other software. It is essential that external imputations are stored in the proper format of the `mids` object. The altered `mids` object can then be used as input for the Gibbs sampler by calling the `mice.mids` function. Note that this requires *all* empty cells to be imputed, otherwise the sampler will error on empty cells. Alternatively, the altered `mids` object can be used for repeated complete data analyses (by calling the `lm.mids` or `glm.mids` functions). For this use, it is allowed that only a subset of empty cells is imputed, and that the complete data software handles the remaining incomplete records.

6 After mice

6.1 Overview

The `mice` library defines three data classes:

- `mids`: multiply imputed data set (= result of imputation)
- `mira`: multiply imputed repeated analyses (= results of repeated complete data analyses)
- `mipo`: multiple imputed pooled analysis (= result of pooling the repeated analyses)

The table below contains a short description of the key functions in the `mice` library.

Function	Input	Output	Description
<code>md.pattern</code>	<code>data.frame</code>	<code>matrix</code>	summarizes the pattern of the missing data
<code>mice</code>	<code>data.frame</code>	<code>mids</code>	creates a multiply imputed data set
<code>complete</code>	<code>mids</code>	<code>data.frame</code>	converts <code>mids</code> into completed data
<code>lm.mids</code>	<code>mids</code>	<code>mira</code>	linear regression for imputed data
<code>glm.mids</code>	<code>mids</code>	<code>mira</code>	generalized linear model for imputed data
<code>pool</code>	<code>mira</code>	<code>mipo</code>	pools the repeated analyses

6.2 Extracting imputed data

The `complete` function extracts imputed data sets from a `mids` object, and returns the completed data as a data frame. For example,

```
> complete(imp, 3)
```

extracts the third complete data set from a multiply imputed data in `imp`. Specifying

```
> complete(imp, "long")
```

produces a long matrix where the m completed data matrices are vertically stacked and padded with the imputation number. This form is convenient for making point estimates and for exporting multiply imputed data to other software. Other options are "broad" and "repeated", which produce complete data in formats that are convenient for investigating between-imputation patterns.

6.3 Complete data analysis

The `mice` library provides two functions for complete-data analysis on a `mids` object: `lm.mids` and `glm.mids`. These functions are analogues to the standard `lm` and `glm` functions. Their main contribution is that they repeated call the complete data function, and store the resulting fits in an object of class `mira`, which stands for *multiply imputed repeated analyses*. So

```
> fit5<-lm.mids(chl~age+hyp, imp)
```

repeatedly calls the standard regression function `lm`. The `fit5` object contains the results of five complete-data analyses. The expression

```
> fit5$analyses[[1]]
```

returns the `fit` object of the first repeated analysis. It is easy to adapt the `lm.mids` function to other types of complete data analysis.

6.4 Pooling

The function averages the estimates of the complete data model, computes the total variance over the repeated analyses, and computes the relative increase in variance due to nonresponse and the fraction of missing information.

The function takes an object of class `mira`, and returns an object of class `mipo`, which stands for *multiply imputed pooled analysis*. For example,

```
> result <- pool(fit5)
> result
Call: pool(object = fit5)
```

```
Pooled coefficients:
(Intercept)      age      hyp
  136.2802  18.32603  20.59693
```

```
Fraction of information about the coefficients missing due to
nonresponse:
```

```
(Intercept)      age      hyp
  0.2504597  0.3239345  0.4771509
```

produces an object `result` of class `mira`, which contains the pooling results. The command `summary(result)` provides a more extensive overview of the results.

The function `pool` implements the method based on the adjusted degrees of freedom as in Barnard & Rubin (1999). The function relies on the availability of

- the estimates of the model, typically present as 'coefficients' in the fit object;
- an appropriate estimate of the variance-covariance matrix of the estimates per analysis.

The latter is estimated from the fit-object by the `Varcov` function taken from Harrell's `design` library (Alzola & Harrell, 1999). Currently, `Varcov` functions exists for the S-Plus standard `lm` and `glm` function, as well as for `design`'s specific analysis functions. For other complete data methods, the user should define an appropriate `Varcov` function.

Note that not all information from the analyses is pooled. If one wants, for example, a combined estimate of the residual variance around the regression line, this cannot be computed by the `pool` function. It is however easy to adapt the `pool` function to other measures of interest.

Meng & Rubin (1992) describe a procedure for calculating the pooled log-likelihood ratio test and corresponding p-value for statistical analyses on multiply imputed data. This procedure can be used for modelling purposes in the context of generalized linear models. Appendix C contains a worked-out example that one may adapt to apply the procedure.

References

- [1] ALZOLA CF & HARRELL FE. An introduction to S-Plus and the Hmisc and Design Libraries, 1999. <http://hesweb1.med.virginia.edu/biostat/s/index.html>
- [2] ARNOLD BC, CASTILLO E, SARABIA JM. Conditional specification of statistical models. New York: Springer, 1999.
- [3] BARNARD J & RUBIN DB. Small sample degrees of freedom with multiple imputation. *Biometrika*, 86, 948-955, 1999.
- [4] BRAND JPL. Design and implementation of a missing data machine. Academic thesis, Erasmus University, Rotterdam /TNO Prevention and Health, Leiden, 1999.
- [5] COOK RD & WEISBERG S. Applied regression including computing and graphics. New York: Wiley, 1999.
- [6] GELFAND AE & SMITH AFM. Sampling-based approaches to calculating marginal densities, *Journal of the American Statistical Association*, 85, 398-409, 1990.
- [7] KENNICKELL AB. Imputation of the 1989 survey of consumer finances: Stochastic relaxation and multiple imputation, ASA 1991 Proceedings of the Section on Survey Research Methods, 1-10. Alexandria: ASA, 1991.
- [8] KLEINBAUM DG, KUPPER LL & MULLER KE. Applied regression analysis and other multivariate methods. 2nd Ed. Boston: PWS-Kent, 1988.
- [9] LITTLE RJA & RUBIN DB. Statistical analysis with missing data. New York: John Wiley and Sons, 1987.
- [10] MENG XL & Rubin DB. Performing likelihood ratio tests with multiple-imputed data sets. *Biometrika*, 79, 103-111, 1992.
- [11] OUDSHOORN CGM, VAN BUUREN S & VAN RIJCKEVORSEL. Flexible multiple imputation by chained equations of the AVO-95 Survey. Leiden: TNO Prevention and Health. Report PG/VGZ/99.045, 1999.
- [12] PEDHAZUR EJ. Multiple regression in behavioral research. 2nd Ed. New York: Holt, Rinehart and Winston, 1973.
- [13] RAGHUNATHAN TE, SOLENBERGER PW, VAN HOEWYK J. IVEware: Imputation and Variance Estimation Software: Installation Instructions and User Guide. Survey Research Center, Institute of Social Research, University of Michigan, 1998. <http://www.isr.umich.edu/src/smp/ive/>
- [14] RUBIN DB. Multiple Imputation for Nonresponse in Surveys. New York: John Wiley and Sons, 1987.
- [15] RUBIN DB. Multiple imputation after 18+ years (with discussion), *Journal of the American Statistical Association*, 91, 473-518, 1996.

- [16] RUBIN DB & SCHAFER JL. Efficiently creating multiple imputations for incomplete multivariate normal data, ASA 1990 Proceedings of the Statistical Computing Section, 83-88. Alexandria: ASA, 1990.
- [17] SCHAFER JL. Analysis of incomplete multivariate data. London: Chapman & Hall, 1997.
- [18] SCHAFER JL. Multiple imputation: A primer *Statistical Methods in Medical Research*, 8:3-15, 1999.
- [19] VAN BUUREN S, VAN RIJCKEVORSEL JLA & RUBIN DB. Multiple imputation by splines. Bulletin of the International Statistical Institute, Contributed Papers II, 503-504, 1993.
- [20] VAN BUUREN S, BOSHUIZEN HC & KNOOK DL. Multiple imputation of missing blood pressure covariates in survival analysis. *Statistics in Medicine*, 18, 681-694, 1999.
- [21] VAN BUUREN S & OUDSHOORN CGM. Flexible multivariate imputation by MICE. Leiden: TNO Preventie en Gezondheid, TNO/PG 99.054, 1999.

Appendix A Imputation algorithm

Let $X = (X_1, X_2, \dots, X_k)$ be a set of k random variables, where each variable $X_j = (X_j^{\text{obs}}, X_j^{\text{mis}})$ may be partially observed, with $j = 1, \dots, k$. The imputation problem is to draw from $P(X)$, the unconditional multivariate density of X . Let t denote an iteration counter. Assuming that data are missing at random, one may repeat the following sequence of Gibbs sampler iterations:

For X_1 : draw imputations X_1^{t+1} from $P(X_1 | X_2^t, X_3^t, \dots, X_k^t)$
 For X_2 : draw imputations X_2^{t+1} from $P(X_2 | X_1^{t+1}, X_3^t, \dots, X_k^t)$
 :
 For X_k : draw imputations X_k^{t+1} from $P(X_k | X_1^{t+1}, X_2^{t+1}, \dots, X_{k-1}^t)$,

i.e., condition each time on the most recently drawn values of all other variables. Properties of this general iteration scheme have been described by Gelfand and Smith (1990). Rubin and Schafer (1990) show that if $P(X)$ is multivariate normal, then iterating linear regression models like $X_1 = X_2'\beta_{12} + X_3'\beta_{13} + \dots + X_k'\beta_{1k} + \varepsilon_1$ with $\varepsilon_1 \sim N(0, \sigma_1^2)$ will produce a random draw from the desired distribution. Schafer (1997) generalizes this results to other multivariate distributions.

The implemented algorithm differs slightly from Schafer's approach in that the conditional models can be specified directly, thus without the need to choose an encompassing multivariate model for the entire data set. It is *assumed* that a multivariate distribution exists, and that draws from it can be generated by iteratively sampling from the conditional distributions. In this way, the multivariate problem is split into a series of univariate problems. Similar ideas have been applied by Kennickell (1991), Brand (1999), Van Buuren *et al* (1993, 1999) and Raghunathan *et al.* (1998). Rubin coined the term 'incompatible Gibbs' to refer to these kinds of algorithms.

It is not always certain whether the multivariate distribution actually exists. It is possible that the specification of two conditional distributions $P(X_1|X_2)$ and $P(X_2|X_1)$ are incompatible, so that no joint distribution $P(X_1, X_2)$ exists. Arnold *et al.* (1999) deal with this problem from a mathematical-statistical point of view. Very little is known about the properties of the Gibbs sampler under a given incompatible specification. It could be that, since there is no distribution to converge to, the algorithm will alternate between isolated conditional distributions. In that case, the final result will depend on the precise stopping point, which is clearly undesirable. Things may be worse if variables are related in a nonlinear way. Brand (1999) studied the performance of a variety of actual algorithms based on possibly incompatible conditionals, with quite encouraging results. By and large, the subject of incompatible Gibbs is still somewhat of an open research problem, and more work is needed to establish its properties.

Appendix B Function arguments

This appendix describes the arguments of the major functions of the `mice` library. For more details on a specific function, use the standard help mechanism, e.g. by typing `?complete`.

FUNCTIONS

complete Produces imputed flat files from multiply imputed data set (`mids`)

DESCRIPTION:

Takes an object of type `mids`, fills in the missing data, and returns the completed data in a specified format.

USAGE

```
data.frame <- complete(x, action=1)
```

REQUIRED ARGUMENTS:

`x` An object of class 'mids' (created by the function `mice()`).

OPTIONAL ARGUMENTS:

`action`

If `action` is a scalar between 1 and `x$m`, the function returns the data with the `action`'s imputation filled in. Thus, `action=1` returns the first completed data set. The can also be one of the following strings: "long", "broad", "repeated". This has the following meaning:

`action="long"` produces a long matrix with `n*m` rows, containing all imputed data plus two additional variables "`_ID_`" (containing the row.names) and "`_IMP_`" (containing the imputation number).

`action="broad"` produces a broad matrix with `m` times the number of columns in the original data. The first `ncol(x$data)` columns contain the first imputed data matrix. Column names are changed to reflect the imputation number.

`action="repeated"` produces a broad matrix with `m` times `ncol(x$data)` columns. The first `m` columns give the filled-in first variable. Column names are changed to reflect the imputation number.

VALUE:

A data frame with the imputed values filled in.

glm.mids Generalized linear regression on multiply imputed data

DESCRIPTION:

Performs repeated glm on a multiply imputed data set

USAGE:

```
glm.mids(formula=formula(data), family=gaussian, data=sys.parent(), weights,  
subset, na.action, start=eta, control=glm.control(...), method="glm.fit",  
model=F, x=F, y=T, contrasts=NULL, ...)
```

REQUIRED ARGUMENTS:

`formula` a formula expression as for other regression models, of the form

response ~ predictors. See the documentation of `lm` and `formula` for details.

`data` An object of type 'mids', which stands for 'multiply imputed data set', typically created by function `mice()`.

OPTIONAL ARGUMENTS:

`family` see `glm`
`weights`
`subset`
`na.action`
`start`
`control`
`method`
`model`
`x`
`y`
`contrasts`

VALUE:

An objects of class 'mira', which stands for 'multiply imputed repeated analysis'.
This object contains `m` `glm`.objects, plus some descriptive information.

impute.lda Elementary imputation method: Linear Discriminant Analysis

DESCRIPTION:

Imputes univariate missing data using linear discriminant analysis

USAGE:

```
imp <- impute.lda(y, ry, x)
```

REQUIRED ARGUMENTS:

`y` Incomplete data vector of length `n`
`ry` Vector of missing data pattern (F=missing, T=observed)
`x` Matrix (`n x p`) of complete covariates.

VALUE:

`imp` A vector of length `nmis` with imputations.

impute.logreg Elementary imputation method: Logistic Regression

DESCRIPTION:

Imputes univariate missing data using logistic regression.

USAGE:

```
imp <- impute.logreg(y, ry, x)
```

REQUIRED ARGUMENTS:

`y` Incomplete data vector of length `n`
`ry` Vector of missing data pattern of length `n` (F=missing, T=observed)
`x` Matrix (`n x p`) of complete covariates.

VALUE:
imp A vector of length nmis with imputations (0 or 1).

impute.logreg2 Elementary imputation method: Logistic Regression

DESCRIPTION:
Imputes univariate missing data using logistic regression.

USAGE:
imp <- impute.logreg2(y, ry, x)

REQUIRED ARGUMENTS:

y Incomplete data vector of length n
ry Vector of missing data pattern of length n (F=missing, T=observed)
x Matrix (n x p) of complete covariates.

VALUE:
imp A vector of length nmis with imputations (0 or 1).

impute.mean Elementary imputation method: Simple mean imputation

DESCRIPTION:
Imputes the arithmetic mean of the observed data

USAGE:
imp <- impute.mean(y, ry, x=NULL)

REQUIRED ARGUMENTS:

y Incomplete data vector of length n
ry Vector of missing data pattern (F=missing, T=observed)

OPTIONAL ARGUMENTS:

x Matrix (n x p) of complete covariates.

VALUE:
imp A vector of length nmis with imputations.

impute.norm Elementary imputation method: Linear Regression Analysis

DESCRIPTION:
Imputes univariate missing data using linear regression analysis

USAGE:
 imp <- impute.norm(y, ry, x)

REQUIRED ARGUMENTS:

y Incomplete data vector of length n
ry Vector of missing data pattern (F=missing, T=observed)
x Matrix (n x p) of complete covariates.

VALUE:
imp A vector of length nmis with imputations.

impute.pmm Elementary imputation method: Linear Regression Analysis

DESCRIPTION:
 Imputes univariate missing data using predictive mean matching

USAGE:
 imp <- impute.pmm(y, ry, x)

REQUIRED ARGUMENTS:

y Incomplete data vector of length n
ry Vector of missing data pattern (F=missing, T=observed)
x Matrix (n x p) of complete covariates.

VALUE:
imp A vector of length nmis with imputations.

impute.polyreg Elementary imputation method: Polytomous Regression

DESCRIPTION:
 Imputes missing data in a categorical variable using polytomous regression

USAGE:
 imp <- impute.polyreg(y, ry, x)

REQUIRED ARGUMENTS:

y Incomplete data vector of length n
ry Vector of missing data pattern (F=missing, T=observed)
x Matrix (n x p) of complete covariates.

VALUE:
imp A vector of length nmis with imputations.

impute.sample Elementary imputation method: Simple random sample

DESCRIPTION:

Imputes a random sample from the observed y data

USAGE:

```
imp <- impute.sample(y, ry, x=NULL)
```

REQUIRED ARGUMENTS:

y Incomplete data vector of length n

ry Vector of missing data pattern (F=missing, T=observed)

OPTIONAL ARGUMENTS:

x Matrix (n x p) of complete covariates.

VALUE:

imp A vector of length nmis with imputations.

lm.mids Linear regression on multiply imputed data

DESCRIPTION:

Performs repeated linear regression on multiply imputed data set

USAGE:

```
fit <- lm.mids(formula, data, weights, subset, na.action, method="qr",  
model=F,  
                  x=F, y=F, contrasts=NULL, ...)
```

REQUIRED ARGUMENTS:

formula

a formula object, with the response on the left of a ~ operator, and the terms, separated by + operators, on the right.

data

An object of type 'mids', which stands for 'multiply imputed data set', typically, created by function mice().

OPTIONAL ARGUMENTS:

weights see lm

subset see lm

na.action see lm

method see lm

model see lm

x see lm

y see lm

contrasts see lm

VALUE:

An objects of class 'mira', which stands for 'multiply imputed repeated analysis'.
This object contains m lm.objects, plus some descriptive information.

md.pattern Missing data pattern

DESCRIPTION:

Computes the missing data pattern of a matrix or data.frame.

USAGE:

```
pat <- md.pattern(x)
```

REQUIRED ARGUMENTS:

x A data frame or a matrix containing the incomplete data.
Missing values are coded as NA's.

VALUE:

A matrix with `ncol(x)+1` columns, in which each row corresponds to a missing data pattern (1=observed, 0=missing). Rows and columns are sorted in increasing amounts of missing information. The last column and row contain row and column counts, respectively.

mice.mids Multivariate Imputation by Chained Equations (iteration step)

DESCRIPTION:

Takes a "mids"-object, and produces an new object of class "mids".

USAGE:

```
mice.mids(obj, maxit=1, diagnostics=T, printFlag=T)
```

REQUIRED ARGUMENTS:

obj An object of class "mids", typically produces by a previous call to `mice()` or `mice.mids()`

OPTIONAL ARGUMENTS:

maxit The number of additional Gibbs sampling iterations.

diagnostics

A Boolean flag. If TRUE, diagnostic information will be appended to the value of the function. If FALSE, only the imputed data are saved. The default is TRUE.

printFlag

A Boolean flag. If TRUE, diagnostic information during the Gibbs sampling iterations will be written to the command window. The default is TRUE.

VALUE:

An object of class `mids`, which stands for 'multiply imputed data set'.

mice Multivariate Imputation by Chained Equations

DESCRIPTION:

Produces an object of class "mids", which stands for 'multiply imputed data set'.

USAGE:

```
object <- mice(data, m = 5,
  imputationMethod = vector("character",length=ncol(data)),
  predictorMatrix = (1 - diag(1, ncol(data))),
  visitSequence = (1:ncol(data))[apply(is.na(data),2,any)],
  defaultImputationMethod=c("pmm","logreg","polyreg"),
  maxit = 5,
  diagnostics = T,
  printFlag = T,
  seed = NA)
```

REQUIRED ARGUMENTS:

data

A data frame or a matrix containing the incomplete data. Missing values are coded as NA's.

OPTIONAL ARGUMENTS:

m

Number of multiple imputations. If omitted, m=5 is used.

imputationMethod

Can be either a string, or a vector of strings with length ncol(data), specifying the elementary imputation method to be used for each column in data. If specified as a single string, the given method will be used for all columns. The default imputation method (when no argument is specified) depends on the measurement level of the target column and are specified by the defaultImputationMethod argument. Columns that need not be imputed have method "". Built-in methods are:

norm	Bayesian linear regression	Numeric
pmm	Predictive mean matching	Numeric
mean	Unconditional mean imputation	Numeric
logreg	Logistic regression	2 categories
logreg2	Logistic regression (direct minimization)	2 categories
polyreg	Polytomous logistic regression	>= 2 categories
lda	Linear discriminant analysis	>= 2 categories
sample	Random sample from the observed values	Any

For example, for the j'th column, the impute.norm function that implements the Bayesian linear regression method can be called by specifying the string "norm" as the j'th entry in the vector of strings.

The user can write his or her own imputation function, say impute.myfunc, and call it for all columns by specifying imputationMethod="myfunc", or for specific columns by specifying imputationMethod=c("norm","myfunc",...).

Special method: If the first character of the elementary method is a "~", then the string is interpreted as the formula argument in a call to model.frame(formula, data [!r[,j],]). This provides a simple mechanism for specifying a large variety of dependencies among the variables, for example transformed versions of imputed variables, recodes, interactions, sum scores, and so on, that may themselves be needed in other parts of the algorithm. Note that the "~" mechanism works only on those entries which have missing values in the target column. The user should make sure that the combined observed and imputed parts of the target column make sense. One easy way to create consistency is by coding all entries in the target as NA, but for large data sets, this could be inefficient.

Though not strictly needed, it is often useful to specify visitSequence such that the column that is imputed by the "~" mechanism is visited each time after one of its predictors was visited. In that way, deterministic relation between columns will always be synchronized.

predictorMatrix

A square matrix of size ncol(data) containing 0/1 data specifying the set of predictors to be used for each target column. Rows correspond to target variables (i.e. variables to be imputed), in the sequence as they appear in data. A value of '1' means that the column variable is used as a predictor for the target variable (in the rows). The diagonal of predictorMatrix must be zero. The default for predictorMatrix is that all other columns are used as predictors (sometimes called massive imputation).

visitSequence

A vector of integers of arbitrary length, specifying the column indices of the visiting sequence. The visiting sequence is the column order that is used to impute the data during one iteration of the algorithm. A column may be visited more than once. All incomplete columns that are used as predictors should be visited, or else the function will stop with an error. The default sequence `1:ncol(data)` implies that columns are imputed from left to right.

defaultImputationMethod=c("pmm","logreg","polyreg")

A vector of three strings containing the default imputation methods for numerical columns, factor columns with 2 levels, and factor columns with more than two levels, respectively. If nothing is specified, the following defaults will be used:

<code>pmm</code>	predictive mean matching	numeric data	
<code>logreg</code>	logistic regression imputation	binary data	(factor with 2 levels)
<code>polyreg</code>	polytomous regression imputation	categorical data	(factor \geq 2 levels)

maxit

A scalar giving the number of iterations. The default is 5.

diagnostics

A Boolean flag. If TRUE, diagnostic information will be appended to the value of the function. If FALSE, only the imputed data are saved. The default is TRUE.

seed

An integer between 0 and 1000 that is used by the `set.seed` function for offsetting the random number generator. Default is to leave the random number generator alone.

VALUE:

An object of class `mids`, which stands for 'multiply imputed data set'. For a description of the object, see the documentation on `"mids.object"`.

pool Multiple imputation pooling**DESCRIPTION:**

Pools the results of `m` repeated complete data analysis

USAGE:

```
y <- pool(x, dfmethod="smallsample")
```

REQUIRED ARGUMENTS:**object**

An object of class `'mira'`, produced by functions like `lm.mids` or `glm.mids`.

OPTIONAL ARGUMENTS:**dfmethod**

A string describing the method to compute the degrees of freedom. The default value is `"smallsample"`, which specifies the is Barnard-Rubin adjusted degrees of freedom (Barnard & Rubin, 1999) for small samples. Specifying a different string produces the conventional degrees of freedom as in Rubin (1987).

VALUE:

An object of class `'mipo'`, which stands for 'multiple imputation pooled'.

DATA OBJECTS**mids** multiply imputed data set**DESCRIPTION**

An object containing a multiply imputed data set

GENERATION

The "mids" object is generated by the mice and mice.mids functions.

METHODS

The "mids" class of objects has methods for the following generic functions: print, summary, plot.

STRUCTURE

An object of class mids is a list of the following components:

- call The call that created the object.
- data A copy of the incomplete data set.
- m The number of imputations.
- nmis An array containing the number of missing observations per column.
- imp A list of nvar components with the generated multiple imputations. Each part of the list is a nmis[j] by m matrix of imputed values for variable j.
- imputationMethod A vector of strings of length(nvar) specifying the elementary imputation method per column.
- predictorMatrix A square matrix of size ncol(data) containing 0/1 data specifying the predictor set.
- visitSequence The sequence in which columns are visited.
- seed The seed value of the solution.
- iteration Last Gibbs sampling iteration number.
- lastSeedValue The most recent seed value.
- chainMean A list of m components. Each component is a length(visitSequence) by maxit matrix containing the mean of the generated multiple imputations. The array can be used for monitoring convergence. Note that observed data are not present in this mean.
- chainCov A list with similar structure of itermean, containing the covariances of the imputed values.
- pad A list containing various settings of the padded imputation model, i.e. the imputation model after creating dummy variables. Normally, this array is only useful for error checking.

mipo multiply imputed pooled analysis

DESCRIPTION

An object containing the m fit objects of a complete data analysis, plus some additional information.

GENERATION

The "mipo" object is generated by the `lm.mids` and `glm.mids` functions.

METHODS

The "mipo" class of objects has methods for the following generic functions: `print`, `summary`.

STRUCTURE

An object of class `mipo` is a list of the following components:

`call` The call that created the `mipo` object.

`call1` The call that created the `mira` object that was used in 'call'.

`call2` The call that created the `mids` object that was used in 'call1'.

`nmis` An array containing the number of missing observations per column.

`m` Number of multiple imputations.

`qhat` An $m \times npar$ matrix containing the complete data estimates for the $npar$ parameters of the m complete data analyses.

`u` An $m \times npar \times npar$ array containing the variance-covariance matrices of the m complete data analyses.

`qbar` The average of complete data estimates.

`ubar` The average of the variance-covariance matrix of the complete data estimates.

`b` The between imputation variance-covariance matrix.

`t` The total variance-covariance matrix.

`r` Relative increases in variance due to missing data

`df` Degrees of freedom associated with the t-statistics.

`f` Fractions of missing information.

mira multiply imputed repeated analysis

DESCRIPTION

An object containing the m fit objects of a complete data analysis, plus some additional information.

GENERATION

The "mira" object is generated by the `lm.mids` and `glm.mids` functions.

METHODS

The "mira" class of objects has methods for the following generic functions: `print`, `summary`.

STRUCTURE

An object of class `mira` is a list of the following components:

`call` The call that created the object.

`call1` The call that created the `mids` object that was used in 'call'.

nmis An array containing the number of missing observations per column.

analyses A list of m components containing the individual fit objects
from each of the m complete data analyses.

Appendix C Likelihood ratio test

```

##
## Reference: (1992) Meng, X., Rubin, D.B., Performing likelihood ratio tests with
multiply-imputed datasets
## Biometrika, 79, pp 103-111.

imp_mice(nhanes2)
fit1_glm.mids(hyp~chl+age+bmi,data=imp)
fit0_glm.mids(hyp~age+bmi,data=imp)
formula1_hyp~chl+age+bmi
formula0_hyp~age+bmi

#### Calculate for each imputed dataset the deviance for the model
#### with and without the variable (this example: chl).
#### devM is the mean of these deviances (mean(d)'_m from the article of Meng).

deviance_0
for (i in (1:(imp$m))) {
  data.i_complete(imp,i)
  model.0_model.matrix(formula0,data=data.i)%%coef(fit0$analyses[[i]])
  model.1_model.matrix(formula1,data=data.i)%%coef(fit1$analyses[[i]])
  deviance<-deviance+deviance.logistic(data.i$hyp,logistic(model.1))-de-
viance.logistic(data.i$hyp,logistic(model.0))
}
devM<-deviance/imp$m

#### Calculate the pooled coefficients for the "large" and "small" model.
####
result1_pool(fit1)
result0_pool(fit0)
k<-length(result1$qbar)-length(result0$qbar)

#### Calculate now the deviance for each imputed dataset with the pooled coefficients
#### The five deviances will then be pooled: devL (mean(d)_L in the article of Meng).

deviance_0
for (i in (1:(imp$m))) {
  data.i_complete(imp,i)
  model.0_model.matrix(formula0,data=data.i)%%result0$qbar
  model.1_model.matrix(formula1,data=data.i)%%result1$qbar
  deviance<-deviance+deviance.logistic(data.i$hyp,logistic(model.1))-de-
viance.logistic(data.i$hyp,logistic(model.0))
}
devL<-deviance/imp$m

loglikelihoodratio(k,imp$m,devL,devM) ## The pooled loglikelihoodratio
pooled.p.deviance(k,imp$m,devL,devM) ## The pooled p-value of the loglikelihoodra-
tio.

##### functions needed
#####
deviance.logistic<-function(yvector,fittedprobs){
  yvector<-as.numeric(yvector)-1
  term1_term2_rep(0,length(yvector))
  term1[yvector!=0]<-yvector[yvector!=0]*log(yvector[yvector!=0]/fittedprobs
[yvector!=0])
  term2[yvector==0]<-(1-yvector[yvector==0])*log((1-yvector[yvector==0])/(1-
fittedprobs[yvector==0]))
  return(-(2*sum(term1+term2)))}

####
logistic<-function(mu) exp(mu)/(1+exp(mu))

####
#### Calculation teststatistic D_L .

```

```
loglikelihoodratio<-function(k,nimp,devL,devM){
  r.L<-((nimp+1)/(k*(nimp-1)))*(devM-devL)
  return(devL/(k*(1+r.L)))}

pooled.p.deviance<-function(k,nimp,devL,devM){
  r.L<-((nimp+1)/(k*(nimp-1)))*(devM-devL)
  D.L<-devL/(k*(1+r.L))
  nu<-k*(nimp-1)
  if (nu>4) w<-4+(nu-4)*((1+(1-nu/2)*(1/r.L))^2) else w<-nu*(1+1/k)*((1+1/r.L)
^2)/2
  return(p.value<-1-pf(D.L,k,w))}
```