

R package npmlreg – Manual

alldist	1
dkern	8
family.glmmNPML	9
gqz	10
hosp	11
irlsuicide	12
missouri	13
weightslogl.calc.w	14
npmlreg-package	14
plot.glmmNPML	16
post	17
predict.glmmNPML	19
summary.glmmNPML	21
tolfind	22

alldist	<i>NPML estimation or Gaussian quadrature for overdispersed GLM's and variance component models</i>
---------	---

Description

Fits a random effect model using Gaussian quadrature (Hinde, 1982) or nonparametric maximum likelihood (Aitkin, 1996a). The function `alldist` is designed to account for overdispersion, while `allvc` fits variance component models.

Usage

```
alldist(formula,
        random = ~1,
        family = gaussian(),
        data,
        k = 4,
        random.distribution = "np",
        tol = 0.5,
        offset,
        weights,
        pluginz,
        na.action,
        EMmaxit = 500,
        EMdev.change = 0.001,
        lambda = 0,
        damp = TRUE,
        damp.power = 1,
        spike.protect = 0,
        sdev,
        shape,
```

```

        plot.opt = 3,
        verbose = TRUE,
        ...)

allvc(formula,
      random = ~1,
      family = gaussian(),
      data,
      k = 4,
      random.distribution = "np",
      tol = 0.5,
      offset,
      weights,
      pluginz,
      na.action,
      EMmaxit = 500,
      EMdev.change = 0.001,
      lambda=0,
      damp = TRUE,
      damp.power = 1,
      spike.protect=0,
      sdev,
      shape,
      plot.opt = 3,
      verbose = TRUE,
      ...)

```

Arguments

<code>formula</code>	a formula defining the response and the fixed effects (e.g. $y \sim x$).
<code>random</code>	a formula defining the random model. In the case of <code>alldist</code> , set <code>random = ~1</code> to model overdispersion, and for instance <code>random = ~x</code> to introduce a random coefficient <code>x</code> . In the case of <code>allvc</code> , set <code>random=~1 PSU</code> to model overdispersion on the upper level, where <code>PSU</code> is a factor for the primary sampling units, e.g. groups, clusters, classes, or individuals in longitudinal data, and define random coefficients accordingly.
<code>family</code>	conditional distribution of responses. "gaussian", "poisson", "binomial", or "Gamma" can be set. If "gaussian" or "Gamma", then equal component dispersion parameters are assumed, except if the optional parameter <code>lambda</code> is modified.
<code>data</code>	the data frame (mandatory, even if it is attached to the workspace!).
<code>k</code>	the number of mass points/integration points (supported are up to 30 mass points).
<code>random.distribution</code>	the mixing distribution, Gaussian Quadrature (<code>gq</code>) or NPML (<code>np</code>) can be set.
<code>tol</code>	the <code>tol</code> scalar (usually, $0 < \text{tol} \leq 1$)

<code>offset</code>	an optional offset to be included in the model.
<code>weights</code>	optional prior weights for the data.
<code>pluginz</code>	optional numerical vector of length <code>k</code> specifying the starting mass points of the EM algorithm.
<code>na.action</code>	a function indicating what should happen when NA's occur, with possible arguments <code>na.omit</code> and <code>na.fail</code> . The default is set by the <code>na.action</code> setting in <code>options()</code> .
<code>EMmaxit</code>	maximum number of EM iterations.
<code>EMdev.change</code>	stops EM algorithm when deviance change falls below this value.
<code>lambda</code>	only applicable for Gaussian and Gamma mixtures. If set, standard deviations/ shape parameters are calculated smoothly across components via a Aitchison-Aitken kernel (<code>dkern</code>) with parameter <code>lambda</code> . The setting <code>lambda= 0</code> is automatically mapped to <code>lambda =1/k</code> and corresponds to the case 'maximal smoothing' (i.e. equal component dispersion parameters), while <code>lambda=1</code> means 'no smoothing' (unequal disp. param.)
<code>damp</code>	switches EM damping on or off.
<code>damp.power</code>	steers degree of damping applied on dispersion parameter according to formula $1-(1-tol)^{(damp.power*iter+1)}$, see Einbeck & Hinde (2005).
<code>spike.protect</code>	protects algorithm to converge into likelihood spikes for Gaussian and Gamma mixtures with unequal or smooth component standard deviations, by stopping the EM algorithm if one of the component standard deviations (shape parameters, resp.), divided by the fitted mass points, falls below (exceeds, resp.) a certain threshold, which is $0.000001*spike.protect$ ($10^6*spike.protect$, resp.) Setting <code>spike.protect=0</code> means disabling the spike protection. If set, then <code>spike.protect=1</code> is recommended. Note that the displayed disparity may not be correct when convergence is not achieved. This can be checked with <code>EMconverged</code> .
<code>sdev</code>	optional; specifies standard deviation for normally distributed response. If unspecified, it will be estimated from the data.
<code>shape</code>	optional; specifies shape parameter for gamma-distributed response. Setting <code>shape=1</code> gives an exponential distribution. If unspecified, it will be estimated from the data.
<code>plot.opt</code>	if equal to zero, then no graphical output is given. For <code>plot.opt=1</code> the development of the disparity $-2 \log L$ over iteration number is plotted, for <code>plot.opt=2</code> the EM trajectories are plotted, and for <code>plot.opt=3</code> both plots are shown.
<code>verbose</code>	if set to <code>FALSE</code> , no printed output is given during function execution. Useful for <code>tolfind</code> .
<code>...</code>	generic options for the <code>glm</code> function. Not all options may be supported under any circumstances.

Details

The nonparametric maximum likelihood (NPML) approach was introduced in Aitkin (1996) as a tool to fit overdispersed generalized linear models. The idea is to approximate the unknown and unspecified distribution of the random effect by a discrete mixture of exponential

family densities, leading to a simple expression of the marginal likelihood which can then be maximized using a standard EM algorithm.

Aitkin (1999) extended this method to generalized linear models with shared random effects arising through variance component or repeated measures structure. Applications are two-stage sample designs, when firstly the primary sampling units (the upper-level units, e.g. classes) and then the secondary sampling units (lower-level units, e.g. students) are selected, or longitudinal data. Models of this type have also been referred to as multi-level models (Goldstein, 2003). `allvc` is restricted to 2-level models.

The number of components k of the finite mixture has to be specified beforehand. When option `'gq'` is set, then Gauss-Hermite masses and mass points are used, assuming implicitly a normally distributed random effect. When option `'np'` is chosen, the EM algorithm uses the Gauss-Hermite masses and mass points as starting points. The position of the starting points can be concentrated or extended by setting `tol` smaller or larger than one, respectively.

Fitting random coefficient models (Aitkin, Francis & Hinde, 2005, pp. 474, p. 491) is possible by specifying the random term explicitly. Note that the setting `random= ~ x` gives a model with a random slope and a random intercept, that only one random coefficient can be specified, and that the option `random.distribution` is restricted to `np` in this case.

The weights have to be understood as frequency weights, i.e. setting all weights in `alldist` equal to 2 will duplicate each data point and hence double the disparity and deviance.

Value

The function `alldist` produces an object of class `glmmNPML` (if `random.distribution` is set to `np`) or `glmmGQ` (`gq`). Both objects contain the following 29 components:

<code>coefficients</code>	a named vector of coefficients (including the mass points). In case of Gaussian quadrature, the coefficient given at \mathbf{z} corresponds to the standard deviation of the mixing distribution.
<code>residuals</code>	the difference between the true response and the empirical Bayes predictions.
<code>fitted.values</code>	the empirical Bayes predictions (Aitkin, 1996b) on the scale of the responses.
<code>family</code>	the 'family' object used.
<code>linear.predictors</code>	the extended linear predictors $\hat{\eta}_{ik}$.
<code>disparity</code>	the disparity ($-2\log L$) of the fitted mixture regression model.
<code>deviance</code>	the deviance of the fitted mixture regression model.
<code>null.deviance</code>	The deviance for the null model (just containing an intercept), comparable with 'deviance'.
<code>df.residual</code>	the residual degrees of freedom of the fitted model (including the random part).
<code>df.null</code>	the residual degrees of freedom for the null model.
<code>y</code>	the (extended) response vector.
<code>call</code>	the matched call.

<code>formula</code>	the formula supplied.
<code>random</code>	the random term of the model formula.
<code>data</code>	the data argument.
<code>model</code>	the (extended) design matrix.
<code>weights</code>	the case weights initially supplied.
<code>offset</code>	the offset initially supplied.
<code>mass.points</code>	the fitted mass points.
<code>masses</code>	the mixture probabilities corresponding to the mass points.
<code>sdev</code>	a list of the two elements <code>sdev\$sdev</code> and <code>sdev\$sdevk</code> . The former is the (overall) standard deviation of a Gaussian mixture (identical to the value MLE of <code>sigma</code> provided in the summary), and the latter gives the unequal or smooth component-specific standard deviations. All values are equal if <code>lambda=0</code> .
<code>shape</code>	a list of the two elements <code>shape\$shape</code> and <code>shape\$shapek</code> , to be interpreted in analogy to <code>sdev</code> .
<code>post.prob</code>	a matrix of posteriori probabilities.
<code>post.int</code>	a vector of ‘posteriori intercepts’ (as in Sofroniou et al. (2006)).
<code>ebp</code>	the empirical Bayes Predictions on the scale of the linear predictor. For compatibility with older versions.
<code>EMiter</code>	gives the number of iterations of the EM algorithm.
<code>EMconverged</code>	logical value indicating if the EM algorithm converged.
<code>lastglm</code>	the fitted <code>glm</code> object from the last EM iteration.
<code>Misc</code>	contains additional information relevant for the summary and plot functions, in particular the disparity trend and the EM trajectories.

If a binomial model is specified by giving a two-column response, the weights returned by `weights` are the total numbers of cases (factored by the supplied case weights) and the component `y` of the result is the proportion of successes.

As a by-product, `alldist` produces a plot showing the disparity in dependence of the iteration number. Further, a plot with the EM trajectories is given. The x-axis corresponds to the iteration number, and the y-axis to the value of the mass points at a particular iteration. This plot is not produced for GQ.

Note

In contrast to the GLIM 4 version, this R implementation uses for Gaussian and Gamma mixtures by default a damping procedure in the first cycles of the EM algorithm (Einbeck & Hinde, 2006), which stabilizes the algorithm and makes it less sensitive to the optimal choice of `tol`. If `tol` is very small (i.e. less than 0.1), it can be useful to set `damp.power` to values larger than 1 in order to accelerate convergence. Do not use `damp.power=0`, as this would mean permanent damping during EM. Using the option `pluginz`, one can to some extent circumvent the necessity to specify `tol` by giving the starting points explicitly. However, when using `pluginz` for normal or gamma-distributed response, damping will be strictly necessary to ensure that the imposed starting points don’t get blurred immediately due to initial fluctuations, implying that `tol` still plays a role in this case.

Author(s)

Originally translated from the GLIM 4 functions `alldist` and `allvc` (Aitkin & Francis, 1995) to R by Ross Darnell (2002). Modified, extended, and prepared for publication by Jochen Einbeck & John Hinde (2006).

References

- Aitkin, M. and Francis, B. (1995). Fitting overdispersed generalized linear models by nonparametric maximum likelihood. *GLIM Newsletter* 25, 37-45.
- Aitkin, M. (1996a). A general maximum likelihood analysis of overdispersion in generalized linear models. *Statistics and Computing* 6, 251-262.
- Aitkin, M. (1996b). Empirical Bayes shrinkage using posterior random effect means from nonparametric maximum likelihood estimation in general random effect models. *Statistical Modelling: Proceedings of the 11th IWSM 1996*, 87-94.
- Aitkin, M. (1999). A general maximum likelihood analysis of variance components in generalized linear models. *Biometrics* 55, 117-128.
- Aitkin, M., Francis, B. and Hinde, J. (2005). *Statistical Modelling in GLIM 4*. Second Edition, Oxford Statistical Science Series, Oxford, UK.
- Einbeck, J. & Hinde, J. (2006). A note on NPML estimation for exponential family regression models with unspecified dispersion parameter. *Austrian Journal of Statistics* 35, 233-243.
- Goldstein, H. (2003). *Multilevel Statistical Models* (3rd edition). Arnold, London, UK.
- Hinde, J. (1982). Compound Poisson regression models. *Lecture Notes in Statistics* 14, 109-121.
- Sofroniou, N., Einbeck, J., and Hinde, J. (2006). Analyzing Irish suicide rates with mixture models. *Proceedings of the 21st International Workshop on Statistical Modelling in Galway, Ireland, 2006*.

See Also

`glm`, `summary.glmmNPML`, `predict.glmmNPML`, `family.glmmNPML`, `plot.glmmNPML`.

Examples

```
# The first three examples (galaxy data, toxoplasmosis data , fabric faults)
# are based on GLIM examples in Aitkin et al. (2005), and the forth example using
# the Hospital-Stay-Data (Rosner, 2000) is taken from Einbeck & Hinde (2006).
# The fifth data example using the Oxford boys is again inspired by Aitkin et al. (2005).
# The sixth example on Irish suicide rates is taken from Sofroniou et al. (2006).

# The galaxy data
data(galaxies, package="MASS")
gal<-as.data.frame(galaxies)
galaxy.np6 <- alldist(galaxies/1000~1, random=~1, random.distribution="np",
  data=gal, k=6)
```

```

galaxy.np8u <- alldist(galaxies/1000~1, random=~1, random.distribution="np",
  data=gal, k=8, lambda=0.99)
round(galaxy.np8u$sdev$sdevk, digits=3)
#[1] 0.906 0.435 0.218 0.676 1.205 0.216 0.412 0.295

# The toxoplasmosis data
data(rainfall, package="forward")
rainfall$x<-rainfall$Rain/1000
rainfall$x2<- rainfall$x^2; rainfall$x3<- rainfall$x^3
toxو.np3<- alldist(cbind(Cases>Total-Cases) ~ x+x2+x3, random=~1,
  random.distribution="np", family=binomial(link=logit), data=rainfall, k=3)
toxو.np3x<- alldist(cbind(Cases>Total-Cases) ~ x, random=~x,
  random.distribution="np", family=binomial(link=logit), data=rainfall, k=3)
#is the same as
toxو.np3x<- alldist(Cases/Total ~ x, random = ~x, weights=Total,
  family=binomial(link=logit), data=rainfall, k=3)
#or
toxو.np3x<-update(toxo.np3, .~-x2-x3, random = ~x)

# The fabric faults data
data(fabric, package="gamlss")
coefficients(alldist(y ~ x, random=~1, family=poisson(link=log),
  random.distribution="gq", data= fabric, k=3, verbose=FALSE))
#(Intercept)      x      z
# -3.3088663   0.8488060   0.3574909

# The Pennsylvanian hospital stay data
data(hosp)
fitnp3<- alldist(duration~age+temp1, data=hosp, k=3, family=Gamma(link=log),
  tol=0.5)
fitnp3$shape$shape
#[1] 50.75232
fitnp3<- alldist(duration~age+temp1, data=hosp, k=3, family=Gamma(link=log),
  tol=0.5, lambda=0.9)
fitnp3$shape$shapek
#[1] 49.03108 42.79532 126.64046

# The Oxford boys data
data(Oxboys, package="nlme")
Oxboys$boy <- gl(26,9)
allvc(height~age, random=~1|boy, data=Oxboys, random.distribution='gq', k=20)
allvc(height~age, random=~1|boy, data=Oxboys,random.distribution='np',k=8)
#with random coefficients:
allvc(height~age,random=~age|boy, data=Oxboys, random.distribution='np', k=8)

# Irish suicide data
data(irlsuicide)
# Crude rate model:
crude<- allvc(death~sex* age, random=~1|ID, offset=log(pop),
  k=3, data=irlsuicide, family=poisson)
crude$disparity
# [1] 654.021
# Relative risk model:

```

```
relrisk<- allvc(death~1, random=~1|ID, offset=log(expected),
  k=3, data=irlsuicide, family=poisson)
relrisk$disparity
# [1] 656.4955
```

dkern

Aitchison-Aitken kernel

Description

Discrete kernel for categorical data with k unordered categories.

Usage

```
dkern(x, y, k, lambda)
```

Arguments

<code>x</code>	categorical data vector
<code>y</code>	postive integer defining a fixed category
<code>k</code>	positive integer giving the number of categories
<code>lambda</code>	smoothing parameter

Details

This kernel was introduced in Aitkinson & Aitken (1976); see also Titterington (1980).

The setting `lambda = 1/k` corresponds to the extreme case 'maximal smoothing', while `lambda = 1` means 'no smoothing'. Statistically sensible settings are only $1/k \leq \text{lambda} \leq 1$.

Author(s)

Jochen Einbeck (2006)

References

Aitchison, J. and Aitken, C.G.G. (1976). Multivariate binary discrimination by kernel method. *Biometrika* 63, 413-420.

Titterington, D. M. (1980). A comparative study of kernel-based density estimates for categorical data. *Technometrics*, 22, 259-268.

Examples

```
k<-6;
dkern(1:k,4,k,0.99)
# Kernel centered at the 4th component with a very small amount of smoothing.

## The function is currently defined as
function(x,y,k,lambda){
  ifelse(y==x, lambda, (1-lambda)/(k-1))
}
```

family.glmmNPML	<i>Generic functions for objects of class glmmNPML or glmmGQ</i>
-----------------	--

Description

Methods for the generic family and model.matrix functions

Usage

```
family.glmmNPML(object, ...)
family.glmmGQ(object, ...)
model.matrix.glmmNPML(object, ...)
model.matrix.glmmGQ(object, ...)
```

Arguments

object	object of class glmmNPML or glmmGQ.
...	further arguments, ensuring compability with generic functions.

Note

The generic R functions `update()`, `coefficients()`, `coef()`, `fitted()`, `fitted.values()`, and `df.residual()` can also be applied straightforwardly on all objects of class `glmmNPML` or `glmmGQ`. They are not listed above as they use the generic default functions and are not separately implemented.

Explicit implementations exist for `predict`, `summary`, `print`, and `plot`, and these functions are explained in the corresponding help files.

Author(s)

Jochen Einbeck and John Hinde (2006)

See Also

`summary.glmmNPML`, `predict.glmmNPML`, `family`, `model.matrix`, `update`, `coefficients`, `alldist`.

Description

Calculate Gaussian Quadrature points for the Normal distribution using the abscissas and weights for Hermite integration.

Usage

```
gqz(numnodes=20, minweight=0.000001)
```

Arguments

numnodes	theoretical number of quadrature points.
minweight	locations with weights that are less than this value will be omitted.

Details

The conversion of the locations and weights is given in Lindsey (1992, page 169:3) and Skrondal & Rabe-Hesketh (2004, page 165:1). The argument `numnodes` is the theoretical number of quadrature points, locations with weights that are less than the argument `minweight` will be omitted. The default value of `minweight=0.000001` returns 14 masspoints for the default `numnodes=20` as in Aitkin, Francis & Hinde (2005).

Value

A list with two vectors:

location	locations of mass points
weight	masses

Author(s)

Nick Sofroniou (2005)

References

- Aitkin, M., Francis, B. and Hinde, J. (2005). *Statistical Modelling in GLIM 4*. Second Edition, Oxford Statistical Science Series, Oxford, UK.
- Lindsey, J. K. (1992). *The Analysis of Stochastic Processes using GLIM*. Berlin: Springer-Verlag.
- Skrondal, A. and Rabe-Hesketh, S. (2004). *Generalized latent variable modelling*. Boca Raton: Chapman and Hall/CRC.

See Also

`alldist`, `allvc`

Examples

```
gqz(20, minweight=1e-14)
# gives 20 GH mass points, as used as EM starting points for k=20
# in alldist and allvc
```

hosp

The Pennsylvanian Hospital Stay Data

Description

The data, 25 observations, are a subset from a larger data set collected on persons discharged from a selected Pennsylvania hospital as part of a retrospective chart review of antibiotic use in hospitals (Townsend et al., 1979, Rosner, 2000).

Usage

```
data(hosp)
```

Format

A data frame with 25 observations on the following 9 variables. All variables are given as numerical vectors.

`id` patient ID.

`duration` the total number of days patients spent in hospital.

`age` age of patient in whole years.

`sex` gender: 1=M, 2=F.

`temp1` first temperature following admission.

`wbc1` first WBC count ($\times 10^3$) following admission. [WBC= white blood cells].

`antib` received antibiotic: 1=yes, 2=no.

`bact` received bacterial culture: 1=yes, 2=no.

`serv` service: 1 =med., 2=surg.

Warnings

Don't confuse with the Barcelona 'Hospital stay data' `aep` in package `gamlss`.

Source

B. Rosner, Harvard University.

References

Rosner, B. (2000). *Fundamentals of Biostatistics*. Thomson Learning, Duxbury, CA, USA.
Townsend, T.R., Shapiro, M., Rosner, B., & Kass, E. H. (1979). Use of antimicrobial drugs in general hospitals. I. Description of population and definition of methods. *Journal of Infectious Diseases* 139 , 688-697.

Examples

```
data(hosp)
glm(duration~age+temp1+wbc1, data=hosp)
```

irlsuicide

Irish Suicide Data

Description

Suicide Rates in the Republic of Ireland 1989-1998.

Usage

```
data(irlsuicide)
```

Format

A data frame with 104 observations on the following 8 variables.

Region a factor with levels Cork , Dublin , EHB - Dub., Galway, Lim., Mid HB, MWHB-Lim., NEHB, NWHB, SEHB-Wat., SHB-Cork, Waterf., WHB-Gal..

ID a factor with levels 1 2 3 4 5 6 7 8 9 10 11 12 13 correspondng to Regions.

pop a numeric vector giving the population sizes (estimated for 1994).

death a numeric vector giving the total number of deaths.

sex a factor for gender with levels 0 (female) and 1 (male).

age a factor for age with levels 1 (0-29), 2 (30-39), 3 (40-59), 4 (60+ years).

smr a numeric vector with standardized mortality ratios (SMRs)

expected a numeric vector with 'expected' number of cases obtained from a reference population (Ahlbom, 1993).

Details

The data set is examined in Sofroniou et al. (2006), using a variance component model with regions as upper level.

Source

Institute of Public Health in Ireland (2005). All Ireland Mortality Database. Retrieved August 8, 2005, from <http://mapserver1.cdc-ni.com/iph/index.htm>.

References

Ahlbom, A., (1993). Biostatistics for Epidemiologists. Boca Raton: Lewis Publishers.

Sofroniou, N., Einbeck, J., and Hinde, J. (2006). Analyzing Irish Suicide Rates with Mixture Models. Proceedings of the 21st Workshop on Statistical Modelling in Galway, Ireland, 2006.

Examples

```
data(irlsuicide)
library(lattice)
trellis.device(color=FALSE)
plot2age<-rep(gl(4,2),13)
xyplot(irlsuicide$death/irlsuicide$pop~plot2age|irlsuicide$Region,
       pch=(1+(irlsuicide$sex==1)),xlab="age",ylab="Crude rates")
```

missouri

Missouri lung cancer data

Description

Lung cancer mortality in the 84 largest Missouri cities, for males aged 45-54, 1972-1981. Data presented in Tsutakawa (1985).

Usage

```
data(missouri)
```

Format

A data frame with 84 observations on the following 2 variables.

Size population of the city.

Deaths number of lung cancer deaths.

Details

The data set was analyzed using a Poisson model with normal random effect in Tsutakawa (1985), and using a binomial logit model with unspecified random effect distribution in Aitkin (1996b). Aitkin fitted this model with GLIM4.

Source

Tsutakawa, R. (1985).

References

Aitkin, M. (1996b). Empirical Bayes shrinkage using posterior random effect means from nonparametric maximum likelihood estimation in general random effect models. *Statistical Modelling: Proceedings of the 11th IWSM 1996*, 87-94.

Tsutakawa, R. (1985). Estimation of Cancer Mortality Rates: A Bayesian Analysis of Small Frequencies. *Biometrics* 41, 69-79.

Examples

```
data(missouri)
alldist(Deaths~1, offset=log(Size), random=~1, k=2,
        family=poisson(link='log'), data=missouri)
```

`weightslogl.calc.w` *Internal npmlreg functions*

Description

These are not to be called by the user.

Usage

```
weightslogl.calc.w(p, fjk, weights)
expand(x, k)
expand.vc(x, ni)
binomial.expand(Y, k, w)
```

Arguments

<code>p</code>	...
<code>fjk</code>	...
<code>weights</code>	...
<code>x</code>	...
<code>k</code>	...
<code>ni</code>	...
<code>Y</code>	...
<code>w</code>	...

Author(s)

Ross Darnell and Jochen Einbeck.

`npmlreg-package` *Nonparametric maximum likelihood estimation for random effect models*

Description

Nonparametric maximum likelihood estimation or Gaussian quadrature for overdispersed generalized linear models and variance component models. The main functions are `alldist` and `allvc`.

Details

Package: npmlreg
Type: Package
Version: 0.37
Date: 2006-08-14
License: GPL version 2 or newer

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

For details on the GNU General Public License see <http://www.gnu.org/copyleft/gpl.html> or write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

Acknowledgments

This R package is based on several GLIM4 macros originally written by Murray Aitkin and Brian Francis. The authors are also grateful to Nick Sofroniou for retrieving the suicide data and providing the function `gqz`.

The work on this R package was supported by Science Foundation Ireland Basic Research Grant 04/BR/M0051.

Author(s)

Jochen Einbeck, Ross Darnell and John Hinde (2006).

Maintainer: Jochen Einbeck <jochen.einbeck@nuigalway.ie>

References

Aitkin, M., Francis, B. and Hinde, J. (2005). Statistical Modelling in GLIM 4. Second Edition, Oxford Statistical Science Series, Oxford, UK.

Einbeck, J., and Hinde, J. (2006). Nonparametric maximum likelihood estimation for random effect models in R. Vignette to R package `npmlreg`. Type `vignette("npmlreg-v")` to open it.

See Also

`glm`

Description

The functions `alldist` and `allvc` produce objects of type `glmmGQ`, if Gaussian quadrature (Hinde, 1982, `random.distribution="gq"`) was applied for computation, and objects of class `glmmNPML`, if parameter estimation was carried out by nonparametric maximum likelihood (Aitkin, 1996a, `random.distribution="np"`). The functions presented here give some useful diagnostic plotting functionalities to analyze these objects.

Usage

```
plot.glmmNPML(x, plot.opt = 15, noformat=FALSE, ...)  
plot.glmmGQ(x, plot.opt = 3, noformat=FALSE, ...)
```

Arguments

<code>x</code>	a fitted object of class <code>glmmNPML</code> or <code>glmmGQ</code> .
<code>plot.opt</code>	an integer with values $0 \leq \text{plot.opt} \leq 15$.
<code>noformat</code>	if <code>TRUE</code> , then any formatting of the plots is omitted (useful if the user wants to include the plots into a panel of several other plots, possibly generated by other functions).
<code>...</code>	further arguments which will mostly not have any effect (and are included only to ensure compatibility with the generic <code>plot()</code> -function.)

Details

See the help pages to `alldist` and the vignette (Einbeck & Hinde, 2006). It is sufficient to write `plot` instead of `plot.glmmNPML` or `plot.glmmGQ`, since the generic `plot` function provided in R automatically selects the right model class.

Value

For class `glmmNPML`: Depending on the choice of `plot.opt`, a subset of the following four plots:

- | | |
|---|--|
| 1 | Disparity trend. |
| 2 | EM Trajectories. |
| 3 | Empirical Bayes Predictions against observed response. |
| 4 | Individual posterior probabilities. |

The number given in `plot.opt` is transformed into a binary number indicating which plots are to be selected. The first digit (from the right!) refers to plot 1, the second one to plot 2, and so on. For example, `plot.opt=4` gives the binary number 0100 and hence selects just plot 3.

For class `g1mmGQ`: Depending on the choice of `plot.opt`, a subset of plots 1 and 3. Again, the number is transformed into binary coding, yielding only the disparity trend for `plot.opt=1`, only the EBP's for `plot.opt=2`, and both plots for `plot.opt=3`.

Author(s)

Jochen Einbeck and John Hinde (2006)

References

Aitkin, M. (1996a). A general maximum likelihood analysis of overdispersion in generalized linear models. *Statistics and Computing* 6, 251-262.

Einbeck, J., and Hinde, J. (2006). Nonparametric maximum likelihood estimation for random effect models in R. Vignette to R package `npmlreg`. Type `vignette("npmlreg-v")` to open it.

Hinde, J. (1982). Compound Poisson regression models. *Lecture Notes in Statistics* 14, 109-121.

See Also

`alldist`, `allvc`

Examples

```
data(galaxies, package="MASS")
gal<-as.data.frame(galaxies)
galaxy.np4u <- alldist(galaxies/1000~1,random=~1,k=4,tol=0.5,data=gal,lambda=1)
predict(galaxy.np4u, type="response") # EBP on scale of responses

plot(galaxy.np4u, plot.opt=4) # plots only EBP vs. response
plot(galaxy.np4u, plot.opt=3) # gives same output as given by default when executing alldist
plot(galaxy.np4u)             # gives all four plots.
```

post

Posterior probabilities/intercepts, and mass point classifications

Description

Takes an object of class `g1mmNPML` or `g1mmGQ` and displays the posterior probabilities w_{ik} as well as the posterior intercepts (Sofroniou et. al, 2006). Further it classifies the observations to mass points according to their posterior probability. The level on which the information in all three cases is displayed can be chosen by the user via the `level` argument ("`upper`" or "`lower`"). The actual information in both cases is identical, the latter is just an expanded version of the former. In case of simple overdispersion models, the `level` argument is not relevant.

Usage

```
post(object, level="upper")
```

Arguments

<code>object</code>	an object of class <code>glmmNPML</code> or <code>glmmGQ</code> .
<code>level</code>	"upper" or "lower".

Value

A list of the following four items:

<code>prob</code>	posterior probabilities (identical to <code>object\$post.prob</code> in case of "lower" and for one-level models).
<code>int</code>	posterior intercepts (identical to <code>object\$post.int</code> in case of "lower" and for one-level models).
<code>classif</code>	a numerical vector containing the class numbers (the order of the classes corresponds to the order of the mass points given in the output of <code>alldist</code> or <code>allvc</code>).
<code>level</code>	either "lower", "upper", or "none" (for one-level models).

Author(s)

Jochen Einbeck and John Hinde (2006)

References

Sofroniou, N., Einbeck, J., and Hinde, J. (2006). Analyzing Irish suicide rates with mixture models. Proceedings of the 21st International Workshop on Statistical Modelling in Galway, Ireland, 2006.

See Also

`alldist`, `allvc`

Examples

```
data(galaxies, package="MASS")
gal <- as.data.frame(galaxies)
post(alldist(galaxies/1000~1, random=~1, data=gal, k=5))$classif
# classifies the 82 galaxies to one of the five mass points
```

Description

The functions `alldist` and `allvc` produce objects of type `glmmGQ`, if Gaussian quadrature (Hinde, 1982, `random.distribution="gq"`) was applied for computation, and objects of class `glmmNPML`, if parameter estimation was carried out by nonparametric maximum likelihood (Aitkin, 1996a, `random.distribution="np"`). The functions presented here give predictions from those objects.

Usage

```
predict.glmmNPML(object, newdata, type = "link", ...)
predict.glmmGQ(object, newdata, type = "link", ...)
```

Arguments

<code>object</code>	a fitted object of class <code>glmmNPML</code> or <code>glmmGQ</code> .
<code>newdata</code>	a data frame with covariates from which prediction is desired. If omitted, empirical Bayes predictions for the original data will be given.
<code>type</code>	if set to <code>link</code> , the prediction is given on the linear predictor scale. If set to <code>response</code> , prediction is given on the scale of the responses.
<code>...</code>	further arguments which will mostly not have any effect (and are included only to ensure compatibility with the generic <code>predict()</code> - function.)

Details

The predicted values are obtained by

- Empirical Bayes (Aitkin, 1996b), if `newdata` has not been specified. That is, the prediction on the linear predictor scale is given by $\sum \eta_{ik} w_{ik}$, whereby η_{ik} are the fitted linear predictors, w_{ik} are the weights in the final iteration of the EM algorithm (corresponding to the posterior probability for observation i to come from component k), and the sum is taken over the number of components k for fixed i .
- the marginal model, if `object` is of class `glmmNPML` and `newdata` has been specified. That is, computation is identical as above, but with w_{ik} replaced by the masses π_k of the fitted model.
- the analytical expression for the marginal mean of the responses, if `object` is of class `glmmGQ` and `newdata` has been specified. See Aitkin et al. (2005), p. 459, for the formula. This method is only supported for the logarithmic link function, as otherwise no analytical expression for the marginal mean of the responses exists.

It is sufficient to write `predict` instead of `predict.glmmNPML` or `predict.glmmGQ`, since the generic `predict` function provided in R automatically selects the right model class.

Value

A vector of predicted values.

Note

The results of the generic `fitted()` method correspond to `predict(object, type="response")`. Note that, as we are working with random effects, fitted values are never really ‘fitted’ but rather ‘predicted’.

Author(s)

Jochen Einbeck and John Hinde (2006).

References

Aitkin, M. (1996a). A general maximum likelihood analysis of overdispersion in generalized linear models. *Statistics and Computing* 6, 251-262.

Aitkin, M. (1996b). Empirical Bayes shrinkage using posterior random effect means from nonparametric maximum likelihood estimation in general random effect models. *Statistical Modelling: Proceedings of the 11th IWSM 1996*, 87-94.

Aitkin, M., Francis, B. and Hinde, J. (2005). *Statistical Modelling in GLIM 4*. Second Edition, Oxford Statistical Science Series, Oxford, UK.

Hinde, J. (1982). Compound Poisson regression models. *Lecture Notes in Statistics* 14, 109-121.

See Also

`alldist`, `allvc`, `predict`

Examples

```
# Toxoplasmosis data:
data(rainfall, package="forward")
rainfall$x<-rainfall$Rain/1000
tox0.0.3x<- alldist(cbind(Cases>Total-Cases)~1, random=~x,
  data=rainfall, k=3, family=binomial(link=logit))
tox0.1.3x<- alldist(cbind(Cases>Total-Cases)~x, random=~x,
  data=rainfall, k=3, family=binomial(link=logit))
predict(tox0.0.3x, type="response", newdata=data.frame(x=2))
# [1] 0.4608
predict(tox0.1.3x, type="response", newdata=data.frame(x=2))
# [1] 0.4608
# gives the same result, as both models are equivalent and only differ
# by a parameter transformation.

# Fabric faults data:
data(fabric, package="gamlss")
names(fabric)
# [1] "leng" "y" "x"
faults.g2<- alldist(y ~ x, family=poisson(link=log), random=~1,
```

```

      data= fabric,k=2, random.distribution="gq")
predict(faults.g2, type="response",newdata=fabric[1:6,])
# [1]  8.715805 10.354556 13.341242  5.856821 11.407828 13.938013
# is not the same as
predict(faults.g2, type="response")[1:6]
# [1]  6.557786  7.046213 17.020242  7.288989 13.992591  9.533823
# since in the first case prediction is done using the analytical
# mean of the marginal distribution, and in the second case using the
# individual posterior probabilities in an empirical Bayes approach.

```

summary.glmmNPML

Summarizing finite mixture regression fits

Description

These functions are the `summary` and `print` methods for objects of type `glmmNPML` and `glmmGQ`.

Usage

```

summary.glmmNPML(object, digits = max(3, getOption("digits") - 3), ...)
summary.glmmGQ(object, digits = max(3, getOption("digits") - 3), ...)

```

```

print.glmmNPML(x, digits=max(3,getOption('digits')-3), ...)
print.glmmGQ(x, digits=max(3,getOption('digits')-3), ...)

```

Arguments

<code>object</code>	a fitted object of class <code>glmmNPML</code> or <code>glmmGQ</code> .
<code>x</code>	a fitted object of class <code>glmmNPML</code> or <code>glmmGQ</code> .
<code>digits</code>	number of digits; applied on various displayed quantities.
<code>...</code>	further arguments, which will mostly be ignored.

Details

The `summary...-` and `print...-` functions invoke the generic `UseMethod(...)` function and pick the summary for the right model class automatically.

A summary of the `glm` fitted in the last EM iteration is available via `summary(object)$lastglmsumm`.

Value

Print or Summary.

Objects returned by `summary.glmmNPML` or `summary.glmmGQ` are identical to objects of class `glmmNPML` or `glmmGQ`, but have two additional components `$dispersion` and `$lastglmsumm` providing the estimated dispersion parameter and a summary of the `glm` fitted in the last EM iteration.

Author(s)

originally from Ross Darnell (2002), modified and prepared for publication by Jochen Einbeck and John Hinde (2006).

See Also

[alldist](#), [allvc](#), [summary](#), [print](#), [family.glmNPML](#)

<code>tolfind</code>	<i>Grid search over tol for NPML estimation of (generalized) random effect models</i>
----------------------	---

Description

Performs a grid search to select the parameter `tol`, which is a tuning parameter for starting point selection of the EM algorithm for NPML estimation (see e.g. Aitkin, Hinde & Francis, 2005, p. 418)

Usage

```
tolfind(formula,
        random = ~1,
        family = gaussian(),
        data,
        k = 4,
        random.distribution="np",
        offset,
        weights,
        na.action,
        EMmaxit = 500,
        EMdev.change = 0.001,
        lambda = 0,
        damp = TRUE,
        damp.power = 1,
        spike.protect = 1,
        sdev,
        shape,
        plot.opt = 1,
        steps = 15,
        find.in.range = c(0.05, 0.8),
        verbose = FALSE,
        noformat = FALSE,
        ...)
```

Arguments

<code>formula</code>	a formula defining the response and the fixed effects (e.g. $y \sim x$).
<code>random</code>	a formula defining the random model. Set <code>random=~1</code> to model overdispersion.
<code>family</code>	conditional distribution of responses. "gaussian", "poisson", "binomial", or "Gamma" can be set.
<code>data</code>	the data frame (mandatory, even if it is attached to the workspace!).
<code>k</code>	the number of mass points/integration points (supported are up to 30 mass points).
<code>random.distribution</code>	the mixing distribution, Gaussian Quadrature (<code>gq</code>) or NPML (<code>np</code>) can be set.
<code>offset</code>	an optional offset to be included in the model.
<code>weights</code>	optional prior weights for the data.
<code>na.action</code>	a function indicating what should happen when NA's occur, with possible arguments <code>na.omit</code> and <code>na.fail</code> . The default is set by the <code>na.action</code> setting in <code>options()</code> .
<code>EMmaxit</code>	maximum number of EM iterations.
<code>EMdev.change</code>	stops EM algorithm when deviance change falls below this value.
<code>lambda</code>	see the help file for <code>alldist</code> .
<code>damp</code>	switches EM damping on or off.
<code>damp.power</code>	steers degree of damping.
<code>spike.protect</code>	see the help file for <code>alldist</code> . For unequal or smooth component dispersion parameters, the setting <code>spike.protect=1</code> is strongly recommended.
<code>sdev</code>	optional fixed standard deviation for normal mixture.
<code>shape</code>	optional fixed shape parameter for Gamma mixture.
<code>plot.opt</code>	For <code>plot.opt=1</code> the EM trajectories are plotted, for <code>plot.opt=2</code> the development of the disparity $-2 \log L$ over iteration number is plotted, for <code>plot.opt=3</code> both plots are shown, and for <code>plot.opt=0</code> none of them.
<code>steps</code>	number of grid points for the search of <code>tol</code> .
<code>find.in.range</code>	range for the search of <code>tol</code> .
<code>verbose</code>	If set to <code>FALSE</code> , no printed output is given during execution of <code>alldist</code> or <code>allvc</code> .
<code>noformat</code>	If <code>TRUE</code> , then any formatting of the plots is omitted.
<code>...</code>	further arguments which will be ignored.

Details

The EM algorithm for NPML estimation (Aitkin, 1996) uses the Gauss-Hermite masses and mass points as starting points. The position of the starting points can be concentrated or extended by setting `tol` smaller or larger than 1, respectively. The tuning parameter `tol` is, as in GLIM4, responsible for this scaling. A careful selection of `tol` may be necessary

for some data sets. The reason is that NPML has a tendency to get stuck in local maxima, as the log-likelihood function is not concave for fixed k (Boehning, 1999).

For Gaussian and Gamma mixtures this R implementation uses by default a damping procedure in the first cycles of the EM algorithm (Einbeck & Hinde, 2006), which stabilizes the algorithm and makes it less sensitive to the optimal choice of `tol`. Application of `tolfind` to check that the optimal solution has not been overlooked may nevertheless be advisable.

`tolfind` works for `alldist` and `allvc`. The `tolfind` function is mainly designed for NPML (`random.distribution="np"`). It can also be applied to Gaussian Quadrature (`random.distribution="gq"`), though `tol` is of little importance for this and primarily influences the speed of convergence.

Value

A list of 5 items:

<code>MinDisparity</code>	the minimal disparity achieved (for which EM converged).
<code>Mintol</code>	the <code>tol</code> value at which this disparity is achieved.
<code>AllDisparities</code>	a vector containing all disparities calculated on the grid.
<code>Alltol</code>	all corresponding <code>tol</code> values making up the grid.
<code>AllEMconverged</code>	a vector of Booleans indicating if EM converged for the particular <code>tol</code> values.

Author(s)

Jochen Einbeck & John Hinde (2006).

References

- Aitkin, M. (1996). A general maximum likelihood analysis of overdispersion in generalized linear models. *Statistics and Computing* 6 , 251-262.
- Aitkin, M., Francis, B. and Hinde, J. (2005). *Statistical Modelling in GLIM 4*. Second Edition, Oxford Statistical Science Series, Oxford, UK.
- Böhning, D. (1999). *Computer-Assisted Analysis of Mixtures and Applications*. Meta-Analysis, Disease Mapping and others. Chapman & Hall / CRC, Boca Raton, FL, USA.
- Einbeck, J. & Hinde, J. (2006). A note on NPML estimation for exponential family regression models with unspecified dispersion parameter. *Austrian Journal of Statistics* 35, 233-243.

See Also

`alldist`, `allvc`

Examples

```
data(galaxies, package="MASS")
gal<-as.data.frame(galaxies)
tolfind(galaxies/1000~1, random=~1, k=5, data=gal, lambda=1, damp=TRUE,
        find.in.range=c(0,1), steps=10)
# Minimal Disparity: 380.1444 at tol= 0.5
```