

Package ‘curve’

April 6, 2006

Title Dynamic Systems Estimation - Curvature extensions

Description Multivariate Time Series - extensions

Depends R (>= 2.0.0), numDeriv (>= 2006.4-1), setRNG (>= 2004.4-1), tframe (>= 2006.4-1), dse1 (>= 2006.4-1)

Version 2006.4-1

LazyLoad yes

License Free. See the LICENCE file for details.

Author Paul Gilbert <pgilbert@bank-banque-canada.ca>

Maintainer Paul Gilbert <pgilbert@bank-banque-canada.ca>

URL <http://www.bank-banque-canada.ca/pgilbert>

R topics documented:

curvature	2
curvature.TSestModel	3
curvatureStats	4
effectiveCurvature	5
genD.TSestModel	6
hessian.TSestModel	7
print.curvature	8
project	8
relCurvature	9
span	10
span.TSestModel	11

Index

13

curvature

Curvature

Description

Curvature calculations and summary statistics as in Bates and Watts.

Usage

```
curvature(func, ...)
## Default S3 method:
curvature(func, x,
          method="Richardson", method.args=list(d=0.01, eps=1e-4, r=6, v=2),
          signif=0.05, show.details=FALSE, warn=TRUE, ...)
## S3 method for class 'Darray':
curvature(func, signif = 0.05,
          show.extra.details=FALSE, show.details=show.extra.details, warn=TRUE, ...)
```

Arguments

<code>func</code>	a function for the default method, a Darray object, or a object for which a specific method is defined (e.g. a TStestModel).
<code>x</code>	parameters to the function.
<code>signif</code>	The significance level for F test (passed to <code>qf</code>).
<code>show.details</code>	logical indicating if intermediate calculations should be printed.
<code>show.extra.details</code>	logical indicating if extra intermediate calculations should be printed.
<code>warn</code>	see <code>effectiveCurvature</code> .
<code>method</code>	string indicating the numerical approximation method.
<code>method.args</code>	list with arguments to <code>method</code> (see <code>grad</code>).
<code>...</code>	additional arguments passed to <code>func</code> .

Details

This function is generic. It can be called with a function and parameter `x`, in which case the Bates and Watts D matrix is calculated, or with a previously calculated D matrix. A function `func` should return a sample space vector at the parameter value `x`. The method for a Darray object works on the result from `genD` which has already done most of the calculations. The Darray has an element `Dlist` with the 3 elements as follows: `D` is a matrix of first(gradients) and second order partial derivatives organized in the same manner as Bates and Watts. (first `p` columns are the gradients and the next $p(p-1)/2$ columns are the lower triangle of the Hessian). `p` is the dimension of the parameter space=`dim` of the tangent space. `f0` is the function value at the point where the matrix `D` was calculated. (The calculation should not/does not? depend on this value - but it should be the right dimension and 0's do not work).

Value

A list is returned (with invisible). Curvature summary statistics as in Bates and Watts are in the element `stat`. A representation of the Bates and Watts D matrix is in the element `Dlist`. The curvature array `C` as in Bates and Watts defn. (7.16) p242 and examples p244 & p245 is in the elements `C.parameter` and `C.intrinsic`.

Side Effects

Curvature summary statistics as in Bates and Watts are printed.

References

Bates and Watts(1983), 'Nonlinear Regression Analysis and Its Applications.'

See Also

[genD curvature.TSestModel effectiveCurvature](#)

Examples

```
func <- function(x){c(x[1], x[1], x[2]^2)}
#   curvature(func, c(2,2))
```

`curvature.TSestModel`

Curvature for a TSestModel

Description

Calculate curvature for a TSestModel.

Usage

```
## S3 method for class 'TSestModel':
curvature(func, x=coef(func),
           method="Richardson", method.args=list(d=0.01, eps=1e-4, r=6, v=2),
           compiled=TRUE, warn=TRUE,
           Shape=TSmodel(func), data=TSdata(func), ...)
```

Arguments

<code>func</code>	a TSestModel object which is used as a function mapping coefficients (parameters) to residuals.
<code>x</code>	parameter vector first argument to function func indicating the point with respect to which the derivative is calculated.
<code>method</code>	string indicating the numerical approximation method.
<code>method.args</code>	list with arguments to method (see grad).
<code>warn</code>	logical. see <code>effectiveCurvature</code> .
<code>compiled</code>	logical, set FALSE to use curvature.default (for debugging).
<code>Shape</code>	a TSmodel in which the parameters should be used.
<code>data</code>	TSdata to use in teh evaluation.
<code>...</code>	additional arguments passed to func.

Details

See the generic version of the function.

See Also

[curvature](#) [genD](#) [grad](#) [effectiveCurvature](#)

Examples

```
data("eg1.DSE.data.diff", package="dse1")
model <- estVARXls(TSdata( output=outputData(eg1.DSE.data.diff, series=1:2)),
                     max.lag=2)
curvature(genD(model))
```

curvatureStats

Curvature Statistics Utility Used by Curvature and Project

Description

XXX

Usage

```
curvatureStats(cur, n, signif=0.05)
```

Arguments

cur	the relative curvature array. See relCurvature .
n	$n-p$ is denominator degrees of freedom for F statistic, where p is <code>ncol(cur)</code> .
signif	The significance level for F test (passed as <code>1 - signif</code> to <code>qf</code>).

Details

...

Value

x

References

Bates and Watts(1983), 'Nonlinear Regression Analysis and Its Applications.'

See Also

[curvature](#) [project](#) [effectiveCurvature](#) [curvature.Darray](#) [relCurvature](#)

effectiveCurvature *Effective Curvature Utility Used by Curvature and Project*

Description

XXX

Usage

```
effectiveCurvature(cur, QRofD, residual, s.sqr, show.details=FALSE,  
warn=TRUE)
```

Arguments

<code>cur</code>	the relative curvature array. See <code>relCurvature</code> .
<code>QRofD</code>	QR decomposition of D array from Bates and Watts.
<code>residual</code>	point in sample space where the curvature should be calculated (possibly shifted by subtracting actual data to give a residual).
<code>s.sqr</code>	sample estimate of the residual variance.
<code>show.details</code>	logical indicating if intermediate calculations should be printed.
<code>warn</code>	see details.

Details

Effective residual curvature from Bates and Watts p260 Calculate the scaled RMS curvatures relative to a confidence disk radius and extreme axis ratios. ref. Bates and Watts (1983) p254 eqn (7.23). and Bates and Watts J.R. Statist.Soc. B (1980).

Transform the residual vector by multiply Q-transpose and $\sqrt{s.sqr * p}$. Calculate the p by p effective residual curvature matrix B and its eigenvalues. Bates and Watts p260

... If $I - B$ is not positive definite, where B is the effective residual curvature matrix, and `warn` is TRUE, then a warning will indicate that the calculation does not seem to correspond to a local minimum.

Value

`x`

References

Bates and Watts (1980), J.R. Statist.Soc. B. Bates and Watts(1983), 'Nonlinear Regression Analysis and Its Applications.'

See Also

[curvature](#) [project](#) [curvatureStats](#) [relCurvature](#)

genD.TSestModel *Generate Bates and Watts D Matrix*

Description

Generate a matrix of function derivative information.

Usage

```
## S3 method for class 'TSestModel':
genD(func, x=coef(func),
      method="Richardson", method.args=list(d=0.01, eps=1e-4, r=6, v=2),
      Shape=TSmodel(func), data=TSdata(func), ...)
## S3 method for class 'ARMA':
genD(func, x=coef(func),
      method="Richardson", method.args=list(d=0.01, eps=1e-4, r=6, v=2),
      Shape=TSmodel(func), data=TSdata(func), ...)
## S3 method for class 'innov':
genD(func, x=coef(func),
      method="Richardson", method.args=list(d=0.01, eps=1e-4, r=6, v=2),
      Shape=TSmodel(func), data=TSdata(func), ...)
```

Arguments

- func** a TSestModel or TSmodel object which is used as a function mapping coefficients (parameters) to residuals.
- x** parameter vector first argument to function func indicating the point with respect to which the derivative is calculated.
- method** string indicating the numerical approximation method.
- method.args** list with arguments to method (see grad).
- Shape** a TSmodel in which the parameters should be used.
- data** TSdata to use in teh evaluation.
- ...** additional arguments passed to func.

Details

The derivatives are calculated numerically using Richardson improvement.

Value

A list with three elements as follows: D is a matrix of first(gradients) and second order partial derivatives organized in the same manner as Bates and Watts. (The first p columns are the gradients and the next $p(p-1)/2$ columns are the lower triangle of the Hessian). p is the dimension of the parameter space=dim of the tangent space. f0 is the function value at the point where the matrix D was calculated.

See Also

[genD](#) [grad](#) [curvature](#)

Examples

```
data("eg1.DSE.data.diff", package="dse1")
model <- estVARXls(TSdata( output=outputData(eg1.DSE.data.diff, series=1:2)),
                    max.lag=2)
z <- genD(model)
```

hessian.TSestModel *Calculate Hessian Matrix*

Description

Calculatate the hessian matrix of a TSmodel at a parameter value.

Usage

```
## S3 method for class 'TSestModel':
hessian(func, x=coef(func),
        method="Richardson", method.args=list(d=0.01, eps=1e-4, r=6, v=2),
        Shape=TSmodel(func), data=TSdata(func), ...)
```

Arguments

- | | |
|-------------|--|
| func | a TSestModel object which is used as a function mapping coefficients (parameters) to likelihood. |
| x | The parameter point at which the hessian is calculated. |
| method | string indicating the numerical approximation method. |
| method.args | list with arguments to method (see grad). |
| Shape | a TSmodel in which the parameters should be used. |
| data | TSdata to use in teh evaluation. |
| ... | additional arguments passed to func. |

Details

This function calculates the second derivative of the likelihood for the model at its specified parameter value using given data.

Value

a matrix of second derivative of the likelihood (Fisher Information).

See Also

[hessian](#) [genD](#) [grad](#) [span](#)

`print.curvature` *Specific Methods for Print*

Description

See the generic function description.

Usage

```
## S3 method for class 'curvature':
print(x, ...)
## S3 method for class 'curvatureArray':
print(x, ...)
```

Arguments

- `x` a curvature object to be printed.
- `...` arguments to be passed to other methods.

See Also

[print](#)

`project` *Project*

Description

`project`

Usage

```
project(c1, c2, signif = 0.05, eps=1e-5, fuzz=1e-14,
       show.details=FALSE, warn=TRUE)
```

Arguments

- `c1` curvature summary. See details.
- `c2` curvature summary. See details.
- `signif` passed to `curvatureStats`.
- `eps` significance tolerance for singular values. See details.
- `fuzz` tolerance for comparing parameter points. See details.
- `show.details` logical indicating if detailed calculations should be shown.
- `warn` see `effectiveCurvature`.

Details

Under Development

c1 and c2 should be curvature summary statistics as returned by curvature. It is assumed that c1 is a submodel of c2. The tangent space (parameter effects curvature) of the sub-model c1 is a subspace of the tangent space of the larger model. The acceleration space (first normal space, intrinsic curvature effects) of the sub-model is a subspace of the direct sum of the tangent and acceleration spaces of the larger model, so the intrinsic Tangent and acceleration vectors of the submodel c1 can be projected onto the tangent and acceleration spaces of the larger model c2. These are called T1inT2, N1inT2, and N1inN2 (T for tangent, N for normal). A second projection (restriction) of c2 onto the tangent and acceleration spaces of c1 is less interesting but may be a useful check. The intrinsic curvature of the larger model should also be intrinsic on the sub-model and the parameter effects of the larger model may be partly intrinsic on the sub-model. These two projected onto the intrinsic curvature space of the submodel (N2andT2inN1) should compare with the intrinsic curvature of the submodel.

Singular values smaller than eps times the largest singular value are considered to be zero when calculating the dimension of the tangent space.

If the parameter points for the two models are not within fuzz then a warning is issued to indicate that they do not represent the same point in parameter space.

Value

xxx

See Also

[curvature](#) [effectiveCurvature](#)

relCurvature

Relative Curvature Utility Used by Curvature and Project

Description

xxx

Usage

```
relCurvature(s.sqr, R11, R2, show.extra.details=FALSE,
            eps=sqrt(.Machine$double.eps))
```

Arguments

s.sqr	sample estimate of the residual variance.
R11	submatrix of R. See details.
R2	submatrix of R. See details.
show.extra.details	logical indicating if extra intermediate calculations should be printed.
eps	singular values smaller than eps times the largest singular value are considered to be zero.

Details

The result is the relative curvature array Bates & Watts p242-244 eqn. (7.16) and examples p244-245.

R11 is a p by p sub matrix of R. See Bates & Watts p236 and R2 is the m by pp sub matrix R12 R22 ... If I-B is not positive definite, where B is the effective residual curvature matrix, and warn is TRUE, then a warning will indicate that the calculation does not seem to correspond to a local minimum.

Value

relative curvature array

See Also

[curvature](#) [project](#) [effectiveCurvature](#) [curvatureStats](#)

span

Calculate Span of Tangent Plane

Description

Calculate the dimension of the tangent space

Usage

```
span(func, x,
      method="Richardson", method.args=list(d=0.01, eps=1e-4, r=6, v=2),
      show.details=FALSE, ...)
## Default S3 method:
span(func, x,
      method="Richardson", method.args=list(d=0.01, eps=1e-4, r=6, v=2),
      show.details=FALSE, ...)
```

Arguments

- func a function which returns the residual vector for a given parameter vector.
- x parameter vector first argument to function func indicating the point with respect to which the derivative is calculated.
- show.details logical indicating if detailed calculations should be shown.
- method string indicating the numerical approximation method.
- method.args list with arguments to method (see grad).
- ... additional arguments passed to func.

Details

The first argument of a function must be a vector. span performs a svd of the tangent vectors at the point x. This can be used to calculate the dimension of the tangent space (ie. by over specifying the model and counting the number of significant singular values). This function uses Richardson extrapolation (for more details see the functions gradRichardson and genD) to get a numerical approximation of the tangent vectors to the parameter manifold. SVD is then used to calculate their span.

Value

The singular values of the matrix of tangent vectors are returned.

Side Effects

If show.details is T then intermediate calculations are printed.

See Also

[span.TSestModel](#), [gradRichardson](#), [genD](#)

Examples

```
func <- function(x){c(x[1], x[1], x[2]^2)}
span(func, c(2,2))
span(func, c(2,5))
span(func, c(2,2,5))
```

span.TSestModel *Calculate Span of Tangent Plane*

Description

Calculate the dimension of the tangent space

Usage

```
## S3 method for class 'TSestModel':
span(func, x=coef(func),
      method="Richardson", method.args=list(d=0.01, eps=1e-4, r=6, v=2),
      show.details=FALSE, compiled=.DSEflags()$COMPILED,
      Shape=TSmodel(func), data=TSdata(func), ...)
```

Arguments

- | | |
|--------------|---|
| func | a TSestModel object which is used as a function mapping coefficients (parameters) to residuals. |
| x | parameter vector first argument to function func indicating the point with respect to which the derivative is calculated. |
| show.details | logical indicating if detailed calculations should be shown. |
| compiled | use the compiled version of the code. (FALSE only for debugging.) |
| method | string indicating the numerical approximation method. |
| method.args | list with arguments to method (see grad). |
| Shape | a TSmodel in which the parameters should be used. |
| data | TSdata to use in teh evaluation. |
| ... | additional arguments passed to func. |

Details

See the generic function.

Value

The singular values of the matrix of tangent vectors are returned.

Side Effects

If show.details is TRUE then intermediate calculations are printed.

See Also

[span](#), [grad](#), [genD](#)

Index

*Topic **internal**

 curvatureStats, 4
 effectiveCurvature, 4
 relCurvature, 9

*Topic **ts**

 curvature, 1
 curvature.TSestModel, 3
 genD.TSestModel, 5
 hessian.TSestModel, 6
 print.curvature, 7
 project, 8
 span, 10
 span.TSestModel, 11

 curvature, 1, 3–6, 8, 9
 curvature.Darray, 4
 curvature.TSestModel, 2, 3
 curvatureStats, 4, 5, 9

 effectiveCurvature, 2, 3, 4, 4, 8, 9

 genD, 2, 3, 6, 7, 10, 11
 genD.ARMA (*genD.TSestModel*), 5
 genD.innov (*genD.TSestModel*), 5
 genD.TSestModel, 5
 grad, 3, 6, 7, 11
 gradRichardson, 10

 hessian, 7
 hessian.TSestModel, 6

 print, 7
 print.curvature, 7
 print.curvatureArray
 (*print.curvature*), 7
 project, 4, 5, 8, 9

 relCurvature, 4, 5, 9

 span, 7, 10, 11
 span.TSestModel, 10, 11