

# Package ‘fauxnaif’

August 2, 2020

**Title** Convert Values to NA

**Version** 0.6.0

**Description** Provides a replacement for dplyr::na\_if(). Allows you to specify multiple values to be replaced with NA using a single function.

**License** MIT + file LICENSE

**URL** <https://github.com/rossellhayes/fauxnaif>

**BugReports** <https://github.com/rossellhayes/fauxnaif/issues>

**Depends** R (>= 3.5)

**Imports** dplyr,  
glue,  
lifecycle,  
magrittr,  
rlang

**Suggests** covr,  
intrval,  
knitr,  
rmarkdown,  
roxygen2,  
testthat,  
tibble,  
tidyR,  
vctrs

**VignetteBuilder** knitr

**RdMacros** lifecycle

**Encoding** UTF-8

**Language** en-US

**LazyData** true

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.1.1

## R topics documented:

faux_census . . . . .	2
na_if_in . . . . .	2
scoped_na_if . . . . .	4

<b>Index</b>	<b>6</b>
--------------	----------

---

faux_census	<i>A small sample of a fabricated census-like dataset</i>
-------------	---

---

## Description

A dataset containing fake demographic data, used in the `fauxnaif` vignette.

## Usage

```
faux_census
```

## Format

A tibble with 20 rows and 6 variables.

## Source

Fabricated

## Examples

```
faux_census
```

---

na_if_in	<i>Convert values to NA</i>
----------	-----------------------------

---

## Description

This is a replacement for `dplyr::na_if()`. It is useful if you want to convert annoying values to NA. Unlike `dplyr::na_if()`, this function allows you to specify multiple values to be replaced with NA at the same time.

- `na_if_in()` replaces values that match its arguments with NA.
- `na_if_not()` replaces values that *do not* match its arguments with NA.

## Usage

```
na_if_in(input, ...)
na_if(input, ...)
na_if_not(input, ...)
```

## Arguments

<code>input</code>	Vector to modify
<code>...</code>	Values to replace with NA, specified as either:
	<ul style="list-style-type: none"> <li>• An object, vector of objects, or list of objects</li> <li>• A one-sided formula (see section "Formulas")</li> </ul>

## Value

A modified version of `input` with selected values replaced with NA.

## Formulas

These functions accept one-sided formulas that can evaluate to logical vectors. The input is represented in these conditional statements as "...". Valid formulas take the form  $\sim . < 0$ . Additional examples are included in section "Examples".

## See Also

[Scoped variants](#) can be used in pipelines and modify multiple variables at once  
`dplyr::na_if()` to replace a single value with NA.  
`dplyr::coalesce()` to replace missing values with a specified value.  
`tidyverse::replace_na()` to replace NA with a value.  
`dplyr::recode()` and `dplyr::case_when()` to more generally replace values.

## Examples

```
-1:10
# We can replace -1...
# ... explicitly
na_if_in(-1:10, -1)
# ... by specifying values to keep
na_if_not(-1:10, 0:10)
# ... using a formula
na_if_in(-1:10, ~ . < 0)
# ... or using a function
na_if_in(-1:10, min)

messy_string <- c("abc", "", "def", "NA", "ghi", 42, "jkl", "NULL", "mno")
# We can replace unwanted values...
# ... one at a time
na_if_in(messy_string, "")
# ... or all at once
na_if_in(messy_string, "", "NA", "NULL", 1:100)
na_if_in(messy_string, c("", "NA", "NULL", 1:100))
na_if_in(messy_string, list("", "NA", "NULL", 1:100))
# ... or using a clever formula
grepl("[a-z]{3,}", messy_string)
na_if_not(messy_string, ~ grepl("[a-z]{3,}", .))

# na_if_in() is particularly useful inside dplyr::mutate
faux_census %>%
  dplyr::mutate(
    state = na_if_in(state, "Canada"),
    age   = na_if_in(age, ~ . < 18, ~ . > 120)
  )

# We get a message if our values to replace don't exist
na_if_in(-1:10, 11)
# And a warning if we use an invalid input...
# ... like a two-sided formula
na_if_in(-1:10, x ~ . < 0)
```

```
# ... NULL
na_if_in(-1:10, NULL)
# ... or nothing at all
na_if_in(-1:10)

# This function handles vector values differently than dplyr,
# and returns a different result with vector replacement values:
na_if_in(1:5, 5:1)
dplyr::na_if(1:5, 5:1)
```

**scoped\_na\_if***Convert values to NA in multiple columns***Description****Deprecated****Usage**

```
na_if_all(.tbl, ...)
na_if_not_all(.tbl, ...)
na_if_at(.tbl, .vars, ...)
na_if_not_at(.tbl, .vars, ...)
na_if_if(.tbl, .predicate, ...)
na_if_not_if(.tbl, .predicate, ...)
```

**Arguments**

.tbl	A <code>tbl</code> object
...	Values to replace with NA, specified as either: <ul style="list-style-type: none"> <li>An object, vector of objects, or list of objects</li> <li>A one-sided formula (see section "Formulas" in <a href="#">na_if()</a>)</li> </ul>
.vars	A list of columns generated by <a href="#">dplyr::vars()</a> , a character vector of column names, a numeric vector of column positions, or <code>NULL</code> .
.predicate	A predicate function to be applied to the columns or a logical vector. The variables for which <code>.predicate</code> is <code>TRUE</code> are selected. This argument is passed to <a href="#">rlang::as_function()</a> and thus supports quosure-style lambda functions and strings representing function names.

**Details**

The `dplyr::scoped` variants of [na\\_if\(\)](#) and [na\\_if\\_not\(\)](#) can be used directly within pipelines and can modify multiple variables at once.

- `*_all()` affects every variable
- `*_at()` affects variables selected with a character vector or [dplyr::vars\(\)](#)
- `*_if()` affects variables selected with a predicate function

**Value**

A modified data frame. Matched values in selected columns are replaced with NA.

**See Also**

[na\\_if\\_in\(\)](#) and [na\\_if\\_not\(\)](#) operate directly on vectors  
[dplyr::mutate\\_all\(\)](#), [dplyr::mutate\\_at\(\)](#) and [dplyr::mutate\\_if\(\)](#) can apply any function to variables selected in the same way

**Examples**

```
## Not run:  
df <- data.frame(a = 0:5, b = 5:0, c = as.numeric(0:5), d = letters[1:6])  
  
na_if_all(df, 0)  
na_if_not_all(df, 0:3, "c")  
  
na_if_at(df, c("a", "c"), 0)  
na_if_not_at(df, c("a", "c"), 0:3)  
  
na_if_if(df, is.integer, 0)  
na_if_not_if(df, is.integer, 0:3)  
  
## End(Not run)
```

# Index

## \* datasets

faux\_census, [2](#)  
dplyr::case\_when(), [3](#)  
dplyr::coalesce(), [3](#)  
dplyr::mutate\_all(), [5](#)  
dplyr::mutate\_at(), [5](#)  
dplyr::mutate\_if(), [5](#)  
dplyr::na\_if(), [2](#), [3](#)  
dplyr::recode(), [3](#)  
dplyr::scoped, [4](#)  
dplyr::vars(), [4](#)  
  
faux\_census, [2](#)  
  
na\_if(na\_if\_in), [2](#)  
na\_if(), [4](#)  
na\_if\_all(scoped\_na\_if), [4](#)  
na\_if\_at(scoped\_na\_if), [4](#)  
na\_if\_if(scoped\_na\_if), [4](#)  
na\_if\_in, [2](#)  
na\_if\_in(), [5](#)  
na\_if\_not(na\_if\_in), [2](#)  
na\_if\_not(), [4](#), [5](#)  
na\_if\_not\_all(scoped\_na\_if), [4](#)  
na\_if\_not\_at(scoped\_na\_if), [4](#)  
na\_if\_not\_if(scoped\_na\_if), [4](#)  
  
rlang::as\_function(), [4](#)  
  
Scoped variants, [3](#)  
scoped\_na\_if, [4](#)  
  
tidyr::replace\_na(), [3](#)