

# On the usage of the `geepack`

Søren Højsgaard

November 16, 2011

## 1 Introduction

The `geepack` package for generalized estimating equations is described in Halekoh, U., Højsgaard, S., Yan, J. (2006). The package geepack for generalized estimating equations. Journal of Statistical Software. 15, 2. If you use `geepack` in your own work, please do cite the above reference.

This note contains a few extra examples. We illustrate the usage of a the `waves` argument and the `zcor` argument together with a fixed working correlation matrix for the `geeglm()` function. To illustrate these features we simulate some data suitable for a regression model.

```
> library(geepack)
> timeorder <- rep(1:5, 6)
> tvar      <- timeorder + rnorm(length(timeorder))
> idvar <- rep(1:6, each=5)
> uuu     <- rep(rnorm(6), each=5)
> yvar    <- 1 + 2*tvar + uuu + rnorm(length(tvar))
> simdat <- data.frame(idvar, timeorder, tvar, yvar)
> head(simdat,12)

  idvar timeorder      tvar      yvar
1     1          1 1.8449631 4.432342
2     1          2 3.1749567 7.629293
3     1          3 3.1925733 6.679165
4     1          4 4.3811518 9.440102
5     1          5 2.9371403 8.162482
6     2          1 2.0575328 3.968900
7     2          2 1.8507987 2.721638
8     2          3 2.1536808 4.897881
9     2          4 3.1341779 4.894287
10    2          5 5.6353729 9.910881
11    3          1 0.9225695 3.907438
12    3          2 2.2135960 5.588491
```

Notice that clusters of data appear together in `simdat` and that observations are ordered (according to `timeorder`) within clusters.

We can fit a model with an AR(1) error structure as

```

> mod1 <- geeglm(yvar~tvar, id=idvar, data=simdat, corstr="ar1")
> mod1

Call:
geeglm(formula = yvar ~ tvar, data = simdat, id = idvar, corstr = "ar1")

Coefficients:
(Intercept)      tvar
    1.084046     1.981558

Degrees of Freedom: 30 Total (i.e. Null);  28 Residual

Scale Link:           identity
Estimated Scale Parameters: [1] 1.390683

Correlation: Structure = ar1   Link = identity
Estimated Correlation Parameters:
    alpha
0.5638696

Number of clusters:  6   Maximum cluster size: 5

```

This works because observations are ordered according to time within each subject in the dataset.

## 2 Using the waves argument

If observations were not ordered according to cluster and time within cluster we would get the wrong result:

```

> set.seed(123)
> ## library(doBy)
> simdatPerm <- simdat[sample(nrow(simdat)),]
> ## simdatPerm <- orderBy(~idvar, simdatPerm)
> simdatPerm <- simdatPerm[order(simdatPerm$idvar),]
> head(simdatPerm)

  idvar timeorder      tvar      yvar
2      1          2 3.174957 7.629293
4      1          4 4.381152 9.440102
1      1          1 1.844963 4.432342
3      1          3 3.192573 6.679165
5      1          5 2.937140 8.162482
9      2          4 3.134178 4.894287

```

Notice that in `simdatPerm` data is ordered according to subject but the time ordering within subject is random.

Fitting the model as before gives

```

> mod2 <- geeglm(yvar~tvar, id=idvar, data=simdatPerm, corstr="ar1")
> mod2

Call:
geeglm(formula = yvar ~ tvar, data = simdatPerm, id = idvar,
       corstr = "ar1")

Coefficients:
(Intercept)      tvar
    0.9366466   2.0317212

Degrees of Freedom: 30 Total (i.e. Null);  28 Residual

Scale Link:           identity
Estimated Scale Parameters: [1] 1.359835

Correlation: Structure = ar1   Link = identity
Estimated Correlation Parameters:
    alpha
0.5719275

Number of clusters:  6   Maximum cluster size: 5

```

Likewise if clusters do not appear contiguously in data we also get the wrong result (the clusters are not recognized):

```
> ## simdatPerm2 <- orderBy(~timeorder, data=simdat)
> simdatPerm2 <- simdat[order(simdat$timeorder),]
> geeglm(yvar~tvar, id=idvar, data=simdatPerm2, corstr="ar1")

Call:
geeglm(formula = yvar ~ tvar, data = simdatPerm2, id = idvar,
       corstr = "ar1")

Coefficients:
(Intercept)      tvar
  0.650570    2.112266

Degrees of Freedom: 30 Total (i.e. Null); 28 Residual

Scale Link:           identity
Estimated Scale Parameters: [1] 1.339184

Correlation: Structure = ar1   Link = identity
Estimated Correlation Parameters:
alpha
  0

Number of clusters: 30  Maximum cluster size: 1
```

To obtain the right result we must give the `waves` argument:

```
> wav <- simdatPerm$timeorder
> wav
[1] 2 4 1 3 5 4 5 2 1 3 2 3 4 5 1 5 4 2 1 3 3 4 5 1 2 2 5 4 1 3

> mod3 <- geeglm(yvar~tvar, id=idvar, data=simdatPerm, corstr="ar1", waves=wav)
> mod3

Call:
geeglm(formula = yvar ~ tvar, data = simdatPerm, id = idvar,
       waves = wav, corstr = "ar1")

Coefficients:
(Intercept)      tvar
  1.084046    1.981558

Degrees of Freedom: 30 Total (i.e. Null); 28 Residual

Scale Link:           identity
Estimated Scale Parameters: [1] 1.390683

Correlation: Structure = ar1   Link = identity
Estimated Correlation Parameters:
alpha
  0.5638696

Number of clusters: 6  Maximum cluster size: 5
```

### 3 Using a fixed correlation matrix and the `zcor` argument

Suppose we want to use a fixed working correlation matrix:

```

> cor.fixed <- matrix(c(1      , 0.5   , 0.25,  0.125, 0.125,
+                      0.5   , 1     , 0.25,  0.125, 0.125,
+                      0.25  , 0.25 , 1     , 0.5   , 0.125,
+                      0.125, 0.125, 0.5   , 1     , 0.125,
+                      0.125, 0.125, 0.125, 0.125, 1      ), 5, 5)
> cor.fixed

 [,1] [,2] [,3] [,4] [,5]
[1,] 1.000 0.500 0.250 0.125 0.125
[2,] 0.500 1.000 0.250 0.125 0.125
[3,] 0.250 0.250 1.000 0.500 0.125
[4,] 0.125 0.125 0.500 1.000 0.125
[5,] 0.125 0.125 0.125 0.125 1.000

```

Such a working correlation matrix has to be passed to `geeglm()` as a vector in the `zcor` argument. This vector can be created using the `fixed2Zcor()` function:

```

> zcor <- fixed2Zcor(cor.fixed, id=simdatPerm$idvar, waves=simdatPerm$timeorder)
> zcor

[1] 0.125 0.500 0.250 0.125 0.125 0.500 0.125 0.250 0.125 0.125 0.125 0.125
[13] 0.125 0.500 0.125 0.125 0.125 0.500 0.250 0.250 0.250 0.125 0.125 0.500
[25] 0.500 0.125 0.250 0.125 0.125 0.125 0.125 0.125 0.125 0.125 0.125 0.125
[37] 0.500 0.500 0.250 0.250 0.500 0.125 0.250 0.250 0.125 0.125 0.125 0.125
[49] 0.125 0.500 0.125 0.125 0.500 0.250 0.125 0.125 0.125 0.125 0.500 0.250

```

Notice that `zcor` contains correlations between measurements within the same cluster. Hence if a cluster contains only one observation, then there will be generated no entry in `zcor` for that cluster. Now we can fit the model with:

```

> mod4 <- geeglm(yvar~tvar, id=idvar, data=simdatPerm, corstr="fixed", zcor=zcor)
> mod4

Call:
geeglm(formula = yvar ~ tvar, data = simdatPerm, id = idvar,
       zcor = zcor, corstr = "fixed")

Coefficients:
(Intercept)      tvar
0.9196243    2.0271640

Degrees of Freedom: 30 Total (i.e. Null);  28 Residual

Scale Link:           identity
Estimated Scale Parameters: [1] 1.360649

Correlation: Structure = fixed    Link = identity
Estimated Correlation Parameters:
alpha:1
1

Number of clusters: 6  Maximum cluster size: 5

```