

Package ‘ggstatsplot’

January 19, 2021

Type Package

Title 'ggplot2' Based Plots with Statistical Details

Version 0.6.8

Maintainer Indrajeet Patil <patilindrajeet.science@gmail.com>

Description Extension of 'ggplot2', 'ggstatsplot' creates graphics with details from statistical tests included in the plots themselves. It provides an easier API to generate information-rich plots for statistical analysis of continuous (violin plots, scatterplots, histograms, dot plots, dot-and-whisker plots) or categorical (pie and bar charts) data. Currently, it supports the most common types of statistical tests: parametric, nonparametric, robust, and Bayesian versions of t-test/ANOVA, correlation analyses, contingency table analysis, meta-analysis, and regression analyses.

License GPL-3 | file LICENSE

URL <https://indrajeetpatil.github.io/ggstatsplot/>,
<https://github.com/IndrajeetPatil/ggstatsplot>

BugReports <https://github.com/IndrajeetPatil/ggstatsplot/issues>

Depends R (>= 3.6.0)

Imports cowplot,
dplyr,
ggcorrplot,
ggExtra,
ggplot2,
ggrepel (>= 0.9.0),
ggsignif,
insight (>= 0.12.0),
ipmisc (>= 5.0.2),
pairwiseComparisons (>= 3.1.2),
paletteer,
parameters (>= 0.11.0),
performance,
purrr,
rlang,
stats,
statsExpressions (>= 0.7.0),
tidyr,
utils

Suggests forcats,
knitr,
MASS,
rmarkdown,
spelling,
testthat,
tibble,
WRS2

VignetteBuilder knitr

Encoding UTF-8

Language en-US

LazyData true

Roxygen list(markdown = TRUE, roclets = c("`rd", ``namespace",
``collate", ``pkgapi::api_roclet"))

RoxygenNote 7.1.1

Config/testthat/edition 3

Config/testthat/parallel true

R topics documented:

ggstatsplot-package	3
bugs_long	4
bugs_wide	5
combine_plots	6
combine_plots2	9
ggbarsstats	11
ggbetweenstats	14
ggcoefstats	18
ggcorrmat	22
ggdotplotstats	25
gghistostats	28
ggpiestats	31
ggscatterstats	34
ggwithinstats	37
grouped_ggbarsstats	42
grouped_ggbetweenstats	45
grouped_ggcorrmat	49
grouped_ggdotplotstats	52
grouped_gghistostats	55
grouped_ggpiestats	58
grouped_ggscatterstats	60
grouped_ggwithinstats	64
iris_long	68
movies_long	69
movies_wide	70
theme_ggstatsplot	71
Titanic_full	71
VR_dilemma	72

Index **74**

ggstatsplot-package *ggstatsplot: 'ggplot2' Based Plots with Statistical Details*

Description

ggstatsplot is an extension of 'ggplot2', 'ggstatsplot' creates graphics with details from statistical tests included in the plots themselves. It provides an easier API to generate information-rich plots for statistical analysis of continuous (violin plots, scatterplots, histograms, dot plots, dot-and-whisker plots) or categorical (pie and bar charts) data. Currently, it supports the most common types of statistical tests: parametric, nonparametric, robust, and Bayesian versions of t-test/ANOVA, correlation analyses, contingency table analysis, meta-analysis, and regression analyses.

Details

ggstatsplot

The main functions are-

- [ggbetweenstats](#) function to produce information-rich comparison plot *between* different groups or conditions with ggplot2 and details from the statistical tests in the subtitle.
- [ggwithinstats](#) function to produce information-rich comparison plot *within* different groups or conditions with ggplot2 and details from the statistical tests in the subtitle.
- [ggscatterstats](#) function to produce ggplot2 scatterplots along with a marginal histograms/boxplots/density plots from ggExtra and details from the statistical tests in the subtitle.
- [ggpiestats](#) function to produce pie chart with details from the statistical tests in the subtitle.
- [ggbarstats](#) function to produce stacked bar chart with details from the statistical tests in the subtitle.
- [gghistostats](#) function to produce histogram for a single variable with results from one sample test displayed in the subtitle.
- [ggdotplotstats](#) function to produce Cleveland-style dot plots/charts for a single variable with labels and results from one sample test displayed in the subtitle.
- [ggcorrmatrix](#) function to visualize the correlation matrix.
- [ggcoefstats](#) function to visualize results from regression analyses.
- [combine_plots2](#) helper function to combine multiple ggstatsplot plots using `cowplot::plot_grid()` with a combination of title, caption, and annotation label.

For more documentation, see the dedicated [Website](#).

Author(s)

Maintainer: Indrajeet Patil <patilindrajeet.science@gmail.com> ([ORCID](#)) (@patilindrajeets)
[copyright holder]

See Also

Useful links:

- <https://indrajeetpatil.github.io/ggstatsplot/>
- <https://github.com/IndrajeetPatil/ggstatsplot>
- Report bugs at <https://github.com/IndrajeetPatil/ggstatsplot/issues>

bugs_long

Tidy version of the "Bugs" dataset.

Description

Tidy version of the "Bugs" dataset.

Usage

```
bugs_long
```

Format

A data frame with 372 rows and 6 variables

- subject. Dummy identity number for each participant.
- gender. Participant's gender (Female, Male).
- region. Region of the world the participant was from.
- education. Level of education.
- condition. Condition of the experiment the participant gave rating for (**LDLF**: low frighteningness and low disgustingness; **LFHD**: low frighteningness and high disgustingness; **HFHD**: high frighteningness and low disgustingness; **HFHD**: high frighteningness and high disgustingness).
- desire. The desire to kill an arthropod was indicated on a scale from 0 to 10.

Details

This data set, "Bugs", provides the extent to which men and women want to kill arthropods that vary in frighteningness (low, high) and disgustingness (low, high). Each participant rates their attitudes towards all anthropods. Subset of the data reported by Ryan et al. (2013).

Source

<https://www.sciencedirect.com/science/article/pii/S0747563213000277>

Examples

```
dim(bugs_long)
head(bugs_long)
dplyr::glimpse(bugs_long)
```

bugs_wide	<i>Wide-format version of the "Bugs" dataset.</i>
-----------	---

Description

Wide-format version of the "Bugs" dataset.

Usage

```
bugs_wide
```

Format

A data frame with 93 rows and 6 variables

- `subject`. Dummy identity number for each participant.
- `gender`. Participant's gender (Female, Male).
- `region`. Region of the world the participant was from.
- `education`. Level of education.
- `ldlf,ldhf,hdlf,hdhf`. The desire to kill an arthropod was indicated on a scale from 0 to 10 in each condition of the experiment (**LDLF**: low frighteningness and low disgustingness; **LFHD**: low frighteningness and high disgustingness; **HFHD**: high frighteningness and low disgustingness; **HFHD**: high frighteningness and high disgustingness).

Details

This data set, "Bugs", provides the extent to which men and women want to kill arthropods that vary in frighteningness (low, high) and disgustingness (low, high). Each participant rates their attitudes towards all arthropods. Subset of the data reported by Ryan et al. (2013).

Source

<https://www.sciencedirect.com/science/article/pii/S0747563213000277>

Examples

```
dim(bugs_wide)
head(bugs_wide)
dplyr::glimpse(bugs_wide)
```

 combine_plots

Combining and arranging multiple plots in a grid

Description

Stable

Wrapper around `plot_grid` that will return a plotgrid along with a combination of title, caption, and annotation label

Usage

```
combine_plots(
  ...,
  title.text = NULL,
  title.color = "black",
  title.size = 16,
  title.vjust = 0.5,
  title.hjust = 0.5,
  title.fontface = "bold",
  caption.text = NULL,
  caption.color = "black",
  caption.size = 10,
  caption.vjust = 0.5,
  caption.hjust = 0.5,
  caption.fontface = "plain",
  sub.text = NULL,
  sub.color = "black",
  sub.size = 12,
  sub.vjust = 0.5,
  sub.hjust = 0.5,
  sub.fontface = "plain",
  sub.x = 0.5,
  sub.y = 0.5,
  sub.vpadding = ggplot2::unit(1, "lines"),
  sub.angle = 0,
  sub.lineheight = 0.9,
  title.rel.heights = c(0.1, 1.2),
  caption.rel.heights = c(1.2, 0.1),
  title.caption.rel.heights = c(0.1, 1.2, 0.1)
)
```

Arguments

- ... Arguments passed on to `cowplot::plot_grid`
- plotlist (optional) List of plots to display. Alternatively, the plots can be provided individually as the first n arguments of the function `plot_grid` (see examples).
- align (optional) Specifies whether graphs in the grid should be horizontally ("h") or vertically ("v") aligned. Options are "none" (default), "hv" (align in both directions), "h", and "v".

<code>axis</code> (optional)	Specifies whether graphs should be aligned by the left ("l"), right ("r"), top ("t"), or bottom ("b") margins. Options are "none" (default), or a string of any combination of l, r, t, and b in any order (e.g. "tblr" or "rlbt" for aligning all margins). Must be specified if any of the graphs are complex (e.g. faceted) and alignment is specified and desired. See align_plots() for details.
<code>nrow</code> (optional)	Number of rows in the plot grid.
<code>ncol</code> (optional)	Number of columns in the plot grid.
<code>rel_widths</code> (optional)	Numerical vector of relative columns widths. For example, in a two-column grid, <code>rel_widths = c(2, 1)</code> would make the first column twice as wide as the second column.
<code>rel_heights</code> (optional)	Numerical vector of relative rows heights. Works just as <code>rel_widths</code> does, but for rows rather than columns.
<code>labels</code> (optional)	List of labels to be added to the plots. You can also set <code>labels="AUTO"</code> to auto-generate upper-case labels or <code>labels="auto"</code> to auto-generate lower-case labels.
<code>label_size</code> (optional)	Numerical value indicating the label size. Default is 14.
<code>label_fontfamily</code> (optional)	Font family of the plot labels. If not provided, is taken from the current theme.
<code>label_fontface</code> (optional)	Font face of the plot labels. Default is "bold".
<code>label_colour</code> (optional)	Color of the plot labels. If not provided, is taken from the current theme.
<code>label_x</code> (optional)	Single value or vector of x positions for plot labels, relative to each subplot. Defaults to 0 for all labels. (Each label is placed all the way to the left of each plot.)
<code>label_y</code> (optional)	Single value or vector of y positions for plot labels, relative to each subplot. Defaults to 1 for all labels. (Each label is placed all the way to the top of each plot.)
<code>hjust</code>	Adjusts the horizontal position of each label. More negative values move the label further to the right on the plot canvas. Can be a single value (applied to all labels) or a vector of values (one for each label). Default is -0.5.
<code>vjust</code>	Adjusts the vertical position of each label. More positive values move the label further down on the plot canvas. Can be a single value (applied to all labels) or a vector of values (one for each label). Default is 1.5.
<code>scale</code>	Individual number or vector of numbers greater than 0. Enables you to scale the size of all or select plots. Usually it's preferable to set margins instead of using <code>scale</code> , but <code>scale</code> can sometimes be more powerful.
<code>greedy</code> (optional)	How should margins be adjusted during alignment. See align_plots() for details.
<code>byrow</code>	Logical value indicating if the plots should be arranged by row (default) or by column.
<code>cols</code>	Deprecated. Use <code>ncol</code> .
<code>rows</code>	Deprecated. Use <code>nrow</code> .
<code>title.text</code>	String or plotmath expression to be drawn as title for the <i>combined plot</i> .
<code>title.color</code>	Text color for title.
<code>title.size</code>	Point size of title text.
<code>title.vjust</code>	Vertical justification for title. Default = 0.5 (centered on y). 0 = baseline at y, 1 = ascender at y.

title.hjust	Horizontal justification for title. Default = 0.5 (centered on x). 0 = flush-left at x, 1 = flush-right.
title.fontface	The font face ("plain", "bold" (default), "italic", "bold.italic") for title.
caption.text	String or plotmath expression to be drawn as the caption for the <i>combined plot</i> .
caption.color	Text color for caption.
caption.size	Point size of title text.
caption.vjust	Vertical justification for caption. Default = 0.5 (centered on y). 0 = baseline at y, 1 = ascender at y.
caption.hjust	Horizontal justification for caption. Default = 0.5 (centered on x). 0 = flush-left at x, 1 = flush-right.
caption.fontface	The font face ("plain" (default), "bold", "italic", "bold.italic") for caption.
sub.text	The label with which the <i>combined plot</i> should be annotated. Can be a plotmath expression.
sub.color	Text color for annotation label (Default: "black").
sub.size	Point size of annotation text (Default: 12).
sub.vjust	Vertical justification for annotation label (Default: 0.5).
sub.hjust	Horizontal justification for annotation label (Default: 0.5).
sub.fontface	The font face ("plain" (default), "bold", "italic", "bold.italic") for the annotation label.
sub.x	The x position of annotation label (Default: 0.5).
sub.y	The y position of annotation label (Default: 0.5).
sub.vpadding	Vertical padding. The total vertical space added to the label, given in grid units. By default, this is added equally above and below the label. However, by changing the y and vjust parameters, this can be changed (Default: <code>ggplot2::unit(1, "lines")</code>).
sub.angle	Angle at which annotation label is to be drawn (Default: 0).
sub.lineheight	Line height of annotation label.
title.rel.heights	Numerical vector of relative columns heights while combining (title, plot).
caption.rel.heights	Numerical vector of relative columns heights while combining (plot, caption).
title.caption.rel.heights	Numerical vector of relative columns heights while combining (title, plot, caption).

Value

Combined plot with title and/or caption and/or annotation label

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/combine_plots.html

Examples

```
# loading the necessary libraries
library(ggplot2)

# preparing the first plot
p1 <-
  ggplot2::ggplot(
    data = subset(iris, iris$Species == "setosa"),
    aes(x = Sepal.Length, y = Sepal.Width)
  ) +
  geom_point() +
  labs(title = "setosa")

# preparing the second plot
p2 <-
  ggplot2::ggplot(
    data = subset(iris, iris$Species == "versicolor"),
    aes(x = Sepal.Length, y = Sepal.Width)
  ) +
  geom_point() +
  labs(title = "versicolor")

# combining the plot with a title and a caption
combine_plots(
  p1, p2,
  labels = c("(a)", "(b)"),
  title.text = "Dataset: Iris Flower dataset",
  caption.text = "Note: Only two species of flower are displayed",
  title.color = "red",
  caption.color = "blue"
)
```

combine_plots2

Simpler way to combine and arrange multiple plots in a grid

Description

Stable

Wrapper around `cowplot::plot_grid` that will return a plotgrid along with a combination of title, caption, and annotation label. This is a simpler version of the `combine_plots` function in this package.

Usage

```
combine_plots2(
  plotlist,
  plotgrid.args = list(),
  title.text = NULL,
  title.args = list(size = 16, fontface = "bold"),
  caption.text = NULL,
  caption.args = list(size = 10),
  sub.text = NULL,
  sub.args = list(size = 12),
```

```

title.rel.heights = c(0.1, 1.2),
caption.rel.heights = c(1.2, 0.1),
title.caption.rel.heights = c(0.1, 1.2, 0.1),
...
)

```

Arguments

`plotlist` A list of plots to display.

`plotgrid.args` A list of additional arguments to `cowplot::plot_grid`.

`title.text` String or plotmath expression to be drawn as title for the *combined plot*.

`title.args`, `caption.args`, `sub.args`
A list of additional arguments provided to `title`, `caption` and `sub`, resp.

`caption.text` String or plotmath expression to be drawn as the caption for the *combined plot*.

`sub.text` The label with which the *combined plot* should be annotated. Can be a plotmath expression.

`title.rel.heights`
Numerical vector of relative columns heights while combining (title, plot).

`caption.rel.heights`
Numerical vector of relative columns heights while combining (plot, caption).

`title.caption.rel.heights`
Numerical vector of relative columns heights while combining (title, plot, caption).

... Currently ignored.

Value

Combined plot with title and/or caption and/or annotation label

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/combine_plots.html

Examples

```

# loading the necessary libraries
library(ggplot2)

# preparing the first plot
p1 <-
  ggplot2::ggplot(
    data = subset(iris, iris$Species == "setosa"),
    aes(x = Sepal.Length, y = Sepal.Width)
  ) +
  geom_point() +
  labs(title = "setosa")

# preparing the second plot
p2 <-
  ggplot2::ggplot(
    data = subset(iris, iris$Species == "versicolor"),
    aes(x = Sepal.Length, y = Sepal.Width)
  )

```

```

) +
  geom_point() +
  labs(title = "versicolor")

# combining the plot with a title and a caption
combine_plots2(
  plotlist = list(p1, p2),
  plotlist.args = list(labels = c("(a)", "(b)")),
  title.text = "Dataset: Iris Flower dataset",
  caption.text = "Note: Only two species of flower are displayed",
  title.args = list(color = "red"),
  caption.args = list(color = "blue")
)

```

ggbarstats

Bar (column) charts with statistical tests

Description

Maturing

Bar charts for categorical data with statistical details included in the plot as a subtitle.

Usage

```

ggbarstats(
  data,
  x,
  y,
  counts = NULL,
  ratio = NULL,
  paired = FALSE,
  results.subtitle = TRUE,
  sample.size.label = TRUE,
  label = "percentage",
  label.args = list(alpha = 1, fill = "white"),
  conf.level = 0.95,
  k = 2L,
  proportion.test = TRUE,
  perc.k = 0,
  bf.message = TRUE,
  sampling.plan = "indepMulti",
  fixed.margin = "rows",
  prior.concentration = 1,
  title = NULL,
  subtitle = NULL,
  caption = NULL,
  legend.title = NULL,
  xlab = NULL,
  ylab = NULL,
  ggtheme = ggplot2::theme_bw(),
  ggstatsplot.layer = TRUE,
  package = "RColorBrewer",

```

```

palette = "Dark2",
ggplot.component = NULL,
output = "plot",
...
)

```

Arguments

<code>data</code>	A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will not be accepted.
<code>x</code>	The variable to use as the rows in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped.
<code>y</code>	The variable to use as the columns in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped. Default is NULL. If NULL, one-sample proportion test (a goodness of fit test) will be run for the x variable. Otherwise an appropriate association test will be run. This argument can not be NULL for ggbarstats function.
<code>counts</code>	A string naming a variable in data containing counts, or NULL if each row represents a single observation.
<code>ratio</code>	A vector of proportions: the expected proportions for the proportion test (should sum to 1). Default is NULL, which means the null is equal theoretical proportions across the levels of the nominal variable. This means if there are two levels this will be <code>ratio = c(0.5, 0.5)</code> or if there are four levels this will be <code>ratio = c(0.25, 0.25, 0.25, 0.25)</code> , etc.
<code>paired</code>	Logical indicating whether data came from a within-subjects or repeated measures design study (Default: FALSE). If TRUE, McNemar's test expression will be returned. If FALSE, Pearson's chi-square test will be returned.
<code>results.subtitle</code>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
<code>sample.size.label</code>	Logical that decides whether sample size information should be displayed for each level of the grouping variable y (Default: TRUE).
<code>label</code>	Character decides what information needs to be displayed on the label in each pie slice. Possible options are "percentage" (default), "counts", "both".
<code>label.args</code>	Additional aesthetic arguments that will be passed to <code>geom_label</code> .
<code>conf.level</code>	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code>).
<code>proportion.test</code>	Decides whether proportion test for x variable is to be carried out for each level of y (Default: TRUE). In ggbarstats, only <i>p</i> -values from this test will be displayed.
<code>perc.k</code>	Numeric that decides number of decimal places for percentage labels (Default: 0).
<code>bf.message</code>	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).

<code>sampling.plan</code>	Character describing the sampling plan. Possible options are "indepMulti" (independent multinomial; default), "poisson", "jointMulti" (joint multinomial), "hypergeom" (hypergeometric). For more, see <code>?BayesFactor::contingencyTableBF()</code> .
<code>fixed.margin</code>	For the independent multinomial sampling plan, which margin is fixed ("rows" or "cols"). Defaults to "rows".
<code>prior.concentration</code>	Specifies the prior concentration parameter, set to 1 by default. It indexes the expected deviation from the null hypothesis under the alternative, and corresponds to Gunel and Dickey's (1974) "a" parameter.
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>caption</code>	The text for the plot caption.
<code>legend.title</code>	Title text for the legend.
<code>xlab</code>	Custom text for the x axis label (Default: NULL, which will cause the x axis label to be the x variable).
<code>ylab</code>	Custom text for the y axis label (Default: NULL).
<code>ggtheme</code>	A function, ggplot2 theme name. Default value is <code>ggplot2::theme_bw()</code> . Any of the ggplot2 themes, or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> , etc.).
<code>ggstatsplot.layer</code>	Logical that decides whether <code>theme_ggstatsplot</code> theme elements are to be displayed along with the selected <code>ggtheme</code> (Default: TRUE). <code>theme_ggstatsplot</code> is an opinionated theme layer that override some aspects of the selected <code>ggtheme</code> .
<code>package</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletter::palettes_d_names)</code> .
<code>palette</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletter::palettes_d_names)</code> .
<code>ggplot.component</code>	A ggplot component to be added to the plot prepared by <code>ggstatsplot</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is NULL. The argument should be entered as a ggplot2 function or a list of ggplot2 functions.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
<code>...</code>	Currently ignored.

See Also

[grouped_ggbarstats](#), [ggpiestats](#), [grouped_ggpiestats](#)

Examples

```
# for reproducibility
set.seed(123)

# association test (or contingency table analysis)
ggstatsplot::ggbarstats(
  data = mtcars,
  x = vs,
  y = cyl
)
```

ggbetweenstats

Box/Violin plots for group or condition comparisons in between-subjects designs.

Description

Maturing

A combination of box and violin plots along with jittered data points for between-subjects designs with statistical details included in the plot as a subtitle.

Usage

```
ggbetweenstats(
  data,
  x,
  y,
  plot.type = "boxviolin",
  type = "parametric",
  pairwise.comparisons = TRUE,
  pairwise.display = "significant",
  p.adjust.method = "holm",
  effsize.type = "unbiased",
  bf.prior = 0.707,
  bf.message = TRUE,
  results.subtitle = TRUE,
  xlab = NULL,
  ylab = NULL,
  caption = NULL,
  title = NULL,
  subtitle = NULL,
  sample.size.label = TRUE,
  k = 2L,
  var.equal = FALSE,
  conf.level = 0.95,
  nboot = 100L,
  tr = 0.1,
  centrality.plotting = TRUE,
  centrality.point.args = list(size = 5, color = "darkred"),
```

```

centrality.label.args = list(size = 3, nudge_x = 0.4, segment.linetype = 4),
notch = FALSE,
notchwidth = 0.5,
outlier.tagging = FALSE,
outlier.label = NULL,
outlier.coef = 1.5,
outlier.shape = 19,
outlier.color = "black",
outlier.label.args = list(size = 3),
point.args = list(position = ggplot2::position_jitterdodge(dodge.width = 0.6), alpha
  = 0.4, size = 3, stroke = 0),
violin.args = list(width = 0.5, alpha = 0.2),
ggsignif.args = list(textsize = 3, tip_length = 0.01),
ggtheme = ggplot2::theme_bw(),
ggstatsplot.layer = TRUE,
package = "RColorBrewer",
palette = "Dark2",
ggplot.component = NULL,
output = "plot",
...
)

```

Arguments

<code>data</code>	A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will not be accepted.
<code>x</code>	The grouping variable from the dataframe data.
<code>y</code>	The response (a.k.a. outcome or dependent) variable from the dataframe data.
<code>plot.type</code>	Character describing the <i>type</i> of plot. Currently supported plots are "box" (for pure boxplots), "violin" (for pure violin plots), and "boxviolin" (for a combination of box and violin plots; default).
<code>type</code>	Type of statistic expected ("parametric" or "nonparametric" or "robust" or "bayes").Corresponding abbreviations are also accepted: "p" (for parametric), "np" (nonparametric), "r" (robust), or "bf" resp.
<code>pairwise.comparisons</code>	Logical that decides whether pairwise comparisons are to be displayed (default: TRUE). Please note that only significant comparisons will be shown by default. To change this behavior, select appropriate option with <code>pairwise.display</code> argument. The pairwise comparison dataframes are prepared using the <code>pairwiseComparisons::pairwiseComparisons</code> function. For more details about pairwise comparisons, see the documentation for that function.
<code>pairwise.display</code>	Decides which pairwise comparisons to display. Available options are "significant" (abbreviation accepted: "s") or "non-significant" (abbreviation accepted: "ns") or "everything"/"all". The default is "significant". You can use this argument to make sure that your plot is not uber-cluttered when you have multiple groups being compared and scores of pairwise comparisons being displayed.
<code>p.adjust.method</code>	Adjustment method for <i>p</i> -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".

<code>effsize.type</code>	Type of effect size needed for <i>parametric</i> tests. The argument can be "eta" (partial eta-squared) or "omega" (partial omega-squared).
<code>bf.prior</code>	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors.
<code>bf.message</code>	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
<code>results.subtitle</code>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
<code>xlab, ylab</code>	Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
<code>caption</code>	The text for the plot caption.
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>sample.size.label</code>	Logical that decides whether sample size information should be displayed for each level of the grouping variable x (Default: TRUE).
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: k = 2L).
<code>var.equal</code>	a logical variable indicating whether to treat the two variances as being equal. If TRUE then the pooled variance is used to estimate the variance otherwise the Welch (or Satterthwaite) approximation to the degrees of freedom is used.
<code>conf.level</code>	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
<code>nboot</code>	Number of bootstrap samples for computing confidence interval for the effect size (Default: 100).
<code>tr</code>	Trim level for the mean when carrying out robust tests. If you get error stating "Standard error cannot be computed because of Winsorized variance of 0 (e.g., due to ties). Try to decrease the trimming level.", try to play around with the value of <code>tr</code> , which is by default set to 0.1. Lowering the value might help.
<code>centrality.plotting</code>	Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the <code>type</code> argument (mean for parametric, median for non-parametric, trimmed mean for robust, and MAP estimator for Bayes).
<code>centrality.point.args, centrality.label.args</code>	A list of additional aesthetic arguments to be passed to <code>ggplot2::geom_point</code> and <code>ggrepel::geom_label_repel</code> geoms, which are involved in mean plotting.
<code>notch</code>	A logical. If FALSE (default), a standard box plot will be displayed. If TRUE, a notched box plot will be used. Notches are used to compare groups; if the notches of two boxes do not overlap, this suggests that the medians are significantly different. In a notched box plot, the notches extend $1.58 * IQR / \sqrt{n}$, where IQR: Inter-Quartile Range. This gives a roughly 95% confidence interval for comparing medians.
<code>notchwidth</code>	For a notched box plot, width of the notch relative to the body (default 0.5).
<code>outlier.tagging</code>	Decides whether outliers should be tagged (Default: FALSE).

<code>outlier.label</code>	Label to put on the outliers that have been tagged. This can't be the same as <code>x</code> argument.
<code>outlier.coef</code>	Coefficient for outlier detection using Tukey's method. With Tukey's method, outliers are below (1st Quartile) or above (3rd Quartile) <code>outlier.coef</code> times the Inter-Quartile Range (IQR) (Default: 1.5).
<code>outlier.shape</code>	Hiding the outliers can be achieved by setting <code>outlier.shape = NA</code> . Importantly, this does not remove the outliers, it only hides them, so the range calculated for the y-axis will be the same with outliers shown and outliers hidden.
<code>outlier.color</code>	Default aesthetics for outliers (Default: "black").
<code>outlier.label.args</code>	A list of additional aesthetic arguments to be passed to <code>ggrepel::geom_label_repel</code> for outlier label plotting.
<code>point.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_point</code> displaying the raw data.
<code>violin.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_violin</code> .
<code>ggsignif.args</code>	A list of additional aesthetic arguments to be passed to <code>ggsignif::geom_signif</code> .
<code>ggtheme</code>	A function, ggplot2 theme name. Default value is <code>ggplot2::theme_bw()</code> . Any of the ggplot2 themes, or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> , etc.).
<code>ggstatsplot.layer</code>	Logical that decides whether <code>theme_ggstatsplot</code> theme elements are to be displayed along with the selected <code>ggtheme</code> (Default: TRUE). <code>theme_ggstatsplot</code> is an opinionated theme layer that override some aspects of the selected <code>ggtheme</code> .
<code>package, palette</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d_names)</code> .
<code>ggplot.component</code>	A ggplot component to be added to the plot prepared by <code>ggstatsplot</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is NULL. The argument should be entered as a ggplot2 function or a list of ggplot2 functions.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
<code>...</code>	Currently ignored.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggbetweenstats.html

See Also

[grouped_ggbetweenstats](#), [ggwithinstats](#), [grouped_ggwithinstats](#)

Examples

```
# to get reproducible results from bootstrapping
set.seed(123)
library(ggstatsplot)

# simple function call with the defaults
ggstatsplot::ggbetweenstats(
  data = mtcars,
  x = am,
  y = mpg,
  title = "Fuel efficiency by type of car transmission",
  caption = "Transmission (0 = automatic, 1 = manual)"
)

# more detailed function call
ggstatsplot::ggbetweenstats(
  data = datasets::morley,
  x = Expt,
  y = Speed,
  type = "nonparametric",
  plot.type = "box",
  xlab = "The experiment number",
  ylab = "Speed-of-light measurement",
  pairwise.comparisons = TRUE,
  p.adjust.method = "fdr",
  outlier.tagging = TRUE,
  outlier.label = Run,
  ggtheme = ggplot2::theme_grey(),
  ggstatsplot.layer = FALSE
)
```

ggcoefstats

Dot-and-whisker plots for regression analyses

Description**Maturing**

Plot with the regression coefficients' point estimates as dots with confidence interval whiskers and other statistical details included as labels.

Usage

```
ggcoefstats(
  x,
  output = "plot",
  statistic = NULL,
  conf.int = TRUE,
  conf.level = 0.95,
  k = 2L,
  exclude.intercept = FALSE,
  effsize = "eta",
```

```

meta.analytic.effect = FALSE,
meta.type = "parametric",
bf.message = TRUE,
sort = "none",
xlab = "regression coefficient",
ylab = "term",
title = NULL,
subtitle = NULL,
caption = NULL,
only.significant = FALSE,
point.args = list(size = 3, color = "blue"),
errorbar.args = list(height = 0),
vline = TRUE,
vline.args = list(size = 1, linetype = "dashed"),
stats.labels = TRUE,
stats.label.color = NULL,
stats.label.args = list(size = 3, direction = "y"),
package = "RColorBrewer",
palette = "Dark2",
ggtheme = ggplot2::theme_bw(),
ggstatsplot.layer = TRUE,
...
)

```

Arguments

<code>x</code>	A model object to be tidied, or a tidy data frame containing results from a regression model. Function internally uses <code>parameters::model_parameters</code> to get a tidy dataframe. If a data frame is used, it <i>must</i> contain columns named <code>term</code> (names of predictors) and <code>estimate</code> (corresponding estimates of coefficients or other quantities of interest).
<code>output</code>	Character describing the expected output from this function: <code>"plot"</code> (visualization of regression coefficients) or <code>"tidy"</code> (tidy dataframe of results <code>parameters::model_parameters</code>) or <code>"glance"</code> (object from <code>performance::model_performance</code>).
<code>statistic</code>	Which statistic is to be displayed (either <code>"t"</code> or <code>"f"</code> or <code>"z"</code> or <code>"chi"</code>) in the label. This is relevant if the <code>x</code> argument is a <i>dataframe</i> .
<code>conf.int</code>	Logical. Decides whether to display confidence intervals as error bars (Default: TRUE).
<code>conf.level</code>	Numeric deciding level of confidence or credible intervals (Default: 0.95).
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code>).
<code>exclude.intercept</code>	Logical that decides whether the intercept should be excluded from the plot (Default: FALSE).
<code>effsize</code>	Character describing the effect size to be displayed: <code>"eta"</code> (default) or <code>"omega"</code> . This argument is relevant only for models objects of class <code>aov</code> , <code>anova</code> , <code>aovlist</code> , <code>"Gam"</code> , and <code>"manova"</code> .
<code>meta.analytic.effect</code>	Logical that decides whether subtitle for meta-analysis via linear (mixed-effects) models (default: FALSE). If TRUE, input to argument <code>subtitle</code> will be ignored. This will be mostly relevant if a data frame with estimates and their standard errors is entered.

<code>meta.type</code>	Type of statistics used to carry out random-effects meta-analysis. If "parametric" (default), <code>metafor::rma</code> function will be used. If "robust", <code>metaplus::metaplus</code> function will be used. If "bayes", <code>metaBMA::meta_random</code> function will be used.
<code>bf.message</code>	Logical that decides whether results from running a Bayesian meta-analysis assuming that the effect size d varies across studies with standard deviation t (i.e., a random-effects analysis) should be displayed in caption. Defaults to TRUE.
<code>sort</code>	If "none" (default) do not sort, "ascending" sort by increasing coefficient value, or "descending" sort by decreasing coefficient value.
<code>xlab, ylab</code>	Labels for x- and y- axis variables, respectively (Defaults: "regression coefficient" and "term").
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. The input to this argument will be ignored if <code>meta.analytic.effect</code> is set to TRUE.
<code>caption</code>	Text to display as caption. This argument is relevant only when <code>output = "caption"</code> .
<code>only.significant</code>	If TRUE, only stats labels for significant effects is shown (Default: FALSE). This can be helpful when a large number of regression coefficients are to be displayed in a single plot. Relevant only when the output is a plot.
<code>point.args</code>	Additional arguments that will be passed to <code>ggplot2::geom_point</code> geom. Please see documentation for that function to know more about these arguments.
<code>errorbar.args</code>	Additional arguments that will be passed to <code>ggplot2::geom_errorbarh</code> geom. Please see documentation for that function to know more about these arguments.
<code>vline</code>	Decides whether to display a vertical line (Default: "TRUE").
<code>vline.args</code>	Additional arguments that will be passed to <code>ggplot2::geom_vline</code> geom. Please see documentation for that function to know more about these arguments.
<code>stats.labels</code>	Logical. Decides whether the statistic and p -values for each coefficient are to be attached to each dot as a text label using <code>ggrepel</code> (Default: TRUE).
<code>stats.label.color</code>	Color for the labels. If set to NULL, colors will be chosen from the specified package (Default: "RColorBrewer") and palette (Default: "Dark2").
<code>stats.label.args</code>	Additional arguments that will be passed to <code>ggrepel::geom_label_repel</code> geom. Please see documentation for that function to know more about these arguments.
<code>package</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d_names)</code> .
<code>palette</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d_names)</code> .
<code>ggtheme</code>	A function, ggplot2 theme name. Default value is <code>ggplot2::theme_bw()</code> . Any of the ggplot2 themes, or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> , etc.).
<code>ggstatsplot.layer</code>	Logical that decides whether <code>theme_ggstatsplot</code> theme elements are to be displayed along with the selected <code>ggtheme</code> (Default: TRUE). <code>theme_ggstatsplot</code> is an opinionated theme layer that override some aspects of the selected <code>ggtheme</code> .
<code>...</code>	Additional arguments to tidying method. For more, see <code>parameters::model_parameters</code> .

Note

1. All rows of regression estimates where either of the following quantities is NA will be removed if labels are requested: estimate, statistic, p.value.
2. Given the rapid pace at which new methods are added to these packages, it is recommended that you install the GitHub versions of parameters and performance in order to make most of this function.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggcoefstats.html

Examples

```
# for reproducibility
set.seed(123)

# ----- with model object -----

# model object
mod <- lm(formula = mpg ~ cyl * am, data = mtcars)

# to get a plot
ggstatsplot::ggcoefstats(x = mod, output = "plot")

# to get a tidy dataframe
ggstatsplot::ggcoefstats(x = mod, output = "tidy")

# to get a glance summary
ggstatsplot::ggcoefstats(x = mod, output = "glance")

# ----- with custom dataframe -----

# creating a dataframe
df <-
  structure(
    list(
      term = structure(
        c(3L, 4L, 1L, 2L, 5L),
        .Label = c(
          "Africa",
          "Americas", "Asia", "Europe", "Oceania"
        ),
        class = "factor"
      ),
      estimate = c(
        0.382047603321706,
        0.780783111514665,
        0.425607573765058,
        0.558365541235078,
        0.956473848429961
      ),
      std.error = c(
        0.0465576338644502,
        0.0330218199731529,
        0.0362834986178494,
```

```

      0.0480571500648261,
      0.062215818388157
    ),
    statistic = c(
      8.20590677855356,
      23.6444603038067,
      11.7300588415607,
      11.6187818146078,
      15.3734833553524
    ),
    conf.low = c(
      0.290515146096969,
      0.715841986960399,
      0.354354575031406,
      0.46379116008131,
      0.827446138277154
    ),
    conf.high = c(
      0.473580060546444,
      0.845724236068931,
      0.496860572498711,
      0.652939922388847,
      1.08550155858277
    ),
    p.value = c(
      3.28679518728519e-15,
      4.04778497135963e-75,
      7.59757330804449e-29,
      5.45155840151592e-26,
      2.99171217913312e-13
    ),
    df.error = c(
      394L, 358L, 622L,
      298L, 22L
    )
  ),
  row.names = c(NA, -5L),
  class = c(
    "tbl_df",
    "tbl", "data.frame"
  )
)

# plotting the dataframe
ggstatsplot::ggcoefstats(
  x = df,
  statistic = "t",
  meta.analytic.effect = TRUE,
  k = 3
)

```

Description

Maturing

Correlation matrix plot or a dataframe containing results from pairwise correlation tests. The package internally uses `ggcorrplot::ggcorrplot` for creating the visualization matrix, while the correlation analysis is carried out using the `correlation::correlation` function.

Usage

```
ggcorrmat(
  data,
  cor.vars = NULL,
  cor.vars.names = NULL,
  output = "plot",
  matrix.type = "upper",
  type = "parametric",
  beta = 0.1,
  partial = FALSE,
  k = 2L,
  sig.level = 0.05,
  conf.level = 0.95,
  bf.prior = 0.707,
  p.adjust.method = "holm",
  pch = "cross",
  ggcorrplot.args = list(method = "square", outline.color = "black"),
  package = "RColorBrewer",
  palette = "Dark2",
  colors = c("#E69F00", "white", "#009E73"),
  ggtheme = ggplot2::theme_bw(),
  ggstatsplot.layer = TRUE,
  ggplot.component = NULL,
  title = NULL,
  subtitle = NULL,
  caption = NULL,
  ...
)
```

Arguments

<code>data</code>	Dataframe from which variables specified are preferentially to be taken.
<code>cor.vars</code>	List of variables for which the correlation matrix is to be computed and visualized. If <code>NULL</code> (default), all numeric variables from <code>data</code> will be used.
<code>cor.vars.names</code>	Optional list of names to be used for <code>cor.vars</code> . The names should be entered in the same order.
<code>output</code>	Character that decides expected output from this function. If <code>"plot"</code> , the visualization matrix will be returned. If <code>"dataframe"</code> (or literally anything other than <code>"plot"</code>), a dataframe containing all details from statistical analyses (e.g., correlation coefficients, statistic values, <i>p</i> -values, no. of observations, etc.) will be returned.
<code>matrix.type</code>	Character, <code>"upper"</code> (default), <code>"lower"</code> , or <code>"full"</code> , display full matrix, lower triangular or upper triangular matrix.

type	Type of association between paired samples required ("parametric": Pearson's product moment correlation coefficient" or "nonparametric": Spearman's rho" or "robust": percentage bend correlation coefficient" or "bayes": Bayes Factor for Pearson's r "). Corresponding abbreviations are also accepted: "p" (for parametric/pearson), "np" (nonparametric/spearman), "r" (robust), "bf" (for bayes factor), resp.
beta	bending constant (Default: 0.1). For more, see <code>WRS2::pbcor()</code> .
partial	Can be TRUE for partial correlations. For Bayesian partial correlations, "full" instead of pseudo-Bayesian partial correlations (i.e., Bayesian correlation based on frequentist partialization) are returned.
k	Number of digits after decimal point (should be an integer) (Default: $k = 2L$).
sig.level	Significance level (Default: 0.05). If the p -value in p -value matrix is bigger than sig.level, then the corresponding correlation coefficient is regarded as insignificant and flagged as such in the plot. Relevant only when output = "plot".
conf.level	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
bf.prior	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors.
p.adjust.method	Adjustment method for p -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
pch	Decides the point shape to be used for insignificant correlation coefficients (only valid when insig = "pch"). Default: pch = "cross".
ggcorrplot.args	A list of additional (mostly aesthetic) arguments that will be passed to <code>ggcorrplot::ggcorrplot</code> function. The list should avoid any of the following arguments since they are already internally being used: corr, method, p.mat, sig.level, ggtheme, colors, lab, pch, legend.title, digits.
package	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletter::palettes_d_names)</code> .
palette	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletter::palettes_d_names)</code> .
colors	A vector of 3 colors for low, mid, and high correlation values. If set to NULL, manual specification of colors will be turned off and 3 colors from the specified palette from package will be selected.
ggtheme	A function, ggplot2 theme name. Default value is <code>ggplot2::theme_bw()</code> . Any of the ggplot2 themes, or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> , etc.).
ggstatsplot.layer	Logical that decides whether theme_ggstatsplot theme elements are to be displayed along with the selected ggtheme (Default: TRUE). theme_ggstatsplot is an opinionated theme layer that override some aspects of the selected ggtheme.
ggplot.component	A ggplot component to be added to the plot prepared by ggstatsplot. This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a ggplot2 function or a list of ggplot2 functions.

title	The text for the plot title.
subtitle	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
caption	The text for the plot caption.
...	Currently ignored.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggcorrmat.html

See Also

[grouped_ggcorrmat](#) [ggscatterstats](#) [grouped_ggscatterstats](#)

Examples

```
# for reproducibility
set.seed(123)

# if `cor.vars` not specified, all numeric variables used
ggstatsplot::ggcorrmat(iris)

# to get the correlalogram
# note that the function will run even if the vector with variable names is
# not of same length as the number of variables
ggstatsplot::ggcorrmat(
  data = ggplot2::msleep,
  type = "robust",
  cor.vars = sleep_total:bodywt,
  cor.vars.names = c("total sleep", "REM sleep"),
  matrix.type = "lower"
)

# to get the correlation analyses results in a dataframe
ggstatsplot::ggcorrmat(
  data = ggplot2::msleep,
  cor.vars = sleep_total:bodywt,
  partial = TRUE,
  output = "dataframe"
)
```

ggdotplotstats

Dot plot/chart for labeled numeric data.

Description

Maturing

A dot chart (as described by William S. Cleveland) with statistical details from one-sample test included in the plot as a subtitle.

Usage

```

ggdotplotstats(
  data,
  x,
  y,
  xlab = NULL,
  ylab = NULL,
  title = NULL,
  subtitle = NULL,
  caption = NULL,
  type = "parametric",
  test.value = 0,
  bf.prior = 0.707,
  bf.message = TRUE,
  effsize.type = "g",
  conf.level = 0.95,
  nboot = 100,
  tr = 0.1,
  k = 2,
  results.subtitle = TRUE,
  point.args = list(color = "black", size = 3, shape = 16),
  centrality.plotting = TRUE,
  centrality.k = 2,
  centrality.line.args = list(color = "blue", size = 1),
  centrality.label.args = list(color = "blue", size = 3),
  ggplot.component = NULL,
  ggtheme = ggplot2::theme_bw(),
  ggstatsplot.layer = TRUE,
  output = "plot",
  ...
)

```

Arguments

<code>data</code>	A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will not be accepted.
<code>x</code>	A numeric variable from the dataframe <code>data</code> .
<code>y</code>	Label or grouping variable.
<code>xlab</code>	Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
<code>ylab</code>	Labels for x- and y- axis variables, respectively (Defaults: "regression coefficient" and "term").
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>caption</code>	The text for the plot caption.
<code>type</code>	Type of statistic expected ("parametric" or "nonparametric" or "robust" or "bayes"). Corresponding abbreviations are also accepted: "p" (for parametric), "np" (nonparametric), "r" (robust), or "bf" resp.
<code>test.value</code>	A number specifying the value of the null hypothesis (Default: 0).

<code>bf.prior</code>	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors.
<code>bf.message</code>	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
<code>effsize.type</code>	Type of effect size needed for <i>parametric</i> tests. The argument can be "d" (for Cohen's <i>d</i>) or "g" (for Hedge's <i>g</i>).
<code>conf.level</code>	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
<code>nboot</code>	Number of bootstrap samples for computing confidence interval for the effect size (Default: 100).
<code>tr</code>	Trim level for the mean when carrying out robust tests. If you get error stating "Standard error cannot be computed because of Winsorized variance of 0 (e.g., due to ties). Try to decrease the trimming level.", try to play around with the value of <code>tr</code> , which is by default set to 0.1. Lowering the value might help.
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code>).
<code>results.subtitle</code>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
<code>point.args</code>	A list of additional aesthetic arguments passed to <code>geom_point</code> .
<code>centrality.plotting</code>	Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the <code>type</code> argument (mean for parametric, median for non-parametric, trimmed mean for robust, and MAP estimator for Bayes).
<code>centrality.k</code>	Integer denoting the number of decimal places expected for centrality parameter label. (Default: 2L).
<code>centrality.line.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_line</code> used to display the lines corresponding to the centrality parameter and test value.
<code>centrality.label.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_label</code> used to display the label corresponding to the centrality parameter and test value.
<code>ggplot.component</code>	A <code>ggplot</code> component to be added to the plot prepared by <code>ggstatsplot</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is NULL. The argument should be entered as a <code>ggplot2</code> function or a list of <code>ggplot2</code> functions.
<code>ggtheme</code>	A function, <code>ggplot2</code> theme name. Default value is <code>ggplot2::theme_bw()</code> . Any of the <code>ggplot2</code> themes, or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> , etc.).
<code>ggstatsplot.layer</code>	Logical that decides whether <code>theme_ggstatsplot</code> theme elements are to be displayed along with the selected <code>ggtheme</code> (Default: TRUE). <code>theme_ggstatsplot</code> is an opinionated theme layer that override some aspects of the selected <code>ggtheme</code> .
<code>output</code>	If "expression", will return expression with statistical details, while "dataframe" will return a dataframe containing the results.
...	Currently ignored.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggdotplotstats.html

See Also

[grouped_gghistostats](#), [gghistostats](#), [grouped_ggdotplotstats](#)

Examples

```
# for reproducibility
set.seed(123)

# plot
ggdotplotstats(
  data = ggplot2::mpg,
  x = cty,
  y = manufacturer,
  test.value = 15,
  test.value.line = TRUE,
  test.line.labeller = TRUE,
  centrality.parameter = "median",
  centrality.k = 0,
  title = "Fuel economy data",
  xlab = "city miles per gallon",
  caption = substitute(
    paste(italic("Source"), ": EPA dataset on http://fueleconomy.gov")
  )
)
```

gghistostats

Histogram for distribution of a numeric variable

Description**Maturing**

Histogram with statistical details from one-sample test included in the plot as a subtitle.

Usage

```
gghistostats(
  data,
  x,
  binwidth = NULL,
  xlab = NULL,
  title = NULL,
  subtitle = NULL,
  caption = NULL,
  type = "parametric",
  test.value = 0,
  bf.prior = 0.707,
```

```

    bf.message = TRUE,
    effsize.type = "g",
    conf.level = 0.95,
    nboot = 100,
    tr = 0.1,
    k = 2L,
    ggtheme = ggplot2::theme_bw(),
    ggstatsplot.layer = TRUE,
    bar.fill = "grey50",
    results.subtitle = TRUE,
    centrality.plotting = TRUE,
    centrality.k = 2,
    centrality.line.args = list(size = 1, color = "blue"),
    centrality.label.args = list(color = "blue", size = 3),
    normal.curve = FALSE,
    normal.curve.args = list(size = 2),
    ggplot.component = NULL,
    output = "plot",
    ...
  )

```

Arguments

data	A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will not be accepted.
x	A numeric variable from the dataframe data.
binwidth	The width of the histogram bins. Can be specified as a numeric value, or a function that calculates width from x. The default is to use the $\max(x) - \min(x) / \sqrt{N}$. You should always check this value and explore multiple widths to find the best to illustrate the stories in your data.
xlab	Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
title	The text for the plot title.
subtitle	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
caption	The text for the plot caption.
type	Type of statistic expected ("parametric" or "nonparametric" or "robust" or "bayes"). Corresponding abbreviations are also accepted: "p" (for parametric), "np" (nonparametric), "r" (robust), or "bf" resp.
test.value	A number specifying the value of the null hypothesis (Default: 0).
bf.prior	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors.
bf.message	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
effsize.type	Type of effect size needed for <i>parametric</i> tests. The argument can be "d" (for Cohen's <i>d</i>) or "g" (for Hedge's <i>g</i>).
conf.level	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
nboot	Number of bootstrap samples for computing confidence interval for the effect size (Default: 100).

<code>tr</code>	Trim level for the mean when carrying out robust tests. If you get error stating "Standard error cannot be computed because of Winsorized variance of 0 (e.g., due to ties). Try to decrease the trimming level.", try to play around with the value of <code>tr</code> , which is by default set to 0.1. Lowering the value might help.
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code>).
<code>ggtheme</code>	A function, ggplot2 theme name. Default value is <code>ggplot2::theme_bw()</code> . Any of the ggplot2 themes, or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> , etc.).
<code>ggstatsplot.layer</code>	Logical that decides whether <code>theme_ggstatsplot</code> theme elements are to be displayed along with the selected <code>ggtheme</code> (Default: <code>TRUE</code>). <code>theme_ggstatsplot</code> is an opinionated theme layer that override some aspects of the selected <code>ggtheme</code> .
<code>bar.fill</code>	Character input that decides which color will uniformly fill all the bars in the histogram (Default: "grey50").
<code>results.subtitle</code>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: <code>TRUE</code>). If set to <code>FALSE</code> , only the plot will be returned.
<code>centrality.plotting</code>	Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: <code>TRUE</code>). Function decides which central tendency measure to show depending on the type argument (mean for parametric, median for non-parametric, trimmed mean for robust, and MAP estimator for Bayes).
<code>centrality.k</code>	Integer denoting the number of decimal places expected for centrality parameter label. (Default: <code>2L</code>).
<code>centrality.line.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_line</code> used to display the lines corresponding to the centrality parameter and test value.
<code>centrality.label.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_label</code> used to display the label corresponding to the centrality parameter and test value.
<code>normal.curve</code>	A logical value that decides whether to super-impose a normal curve using <code>stats::dnorm(mean(x), sd(x))</code> . Default is <code>FALSE</code> .
<code>normal.curve.args</code>	A list of additional aesthetic arguments to be passed to the normal curve.
<code>ggplot.component</code>	A ggplot component to be added to the plot prepared by <code>ggstatsplot</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is <code>NULL</code> . The argument should be entered as a ggplot2 function or a list of ggplot2 functions.
<code>output</code>	If "expression", will return expression with statistical details, while "dataframe" will return a dataframe containing the results.
<code>...</code>	Currently ignored.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/gghistostats.html

See Also

[grouped_gghistostats](#), [ggdotplotstats](#), [grouped_ggdotplotstats](#)

Examples

```
# most basic function
ggstatsplot::gghistostats(
  data = ToothGrowth,
  x = len,
  xlab = "Tooth length",
  centrality.parameter = "median"
)

# a detailed function call
ggstatsplot::gghistostats(
  data = iris,
  x = Sepal.Length,
  type = "p",
  caption = substitute(paste(italic("Note"), ": Iris dataset by Anderson")),
  bf.prior = 0.8,
  test.value = 3,
  test.value.line = TRUE,
  binwidth = 0.10,
  bar.fill = "grey50"
)
```

ggpiestats

Pie charts with statistical tests

Description**Maturing**

Pie charts for categorical data with statistical details included in the plot as a subtitle.

Usage

```
ggpiestats(
  data,
  x,
  y = NULL,
  counts = NULL,
  ratio = NULL,
  paired = FALSE,
  results.subtitle = TRUE,
  label = "percentage",
  label.args = list(direction = "both"),
  label.repel = FALSE,
  conf.level = 0.95,
  k = 2L,
  proportion.test = TRUE,
```

```

perc.k = 0,
bf.message = TRUE,
sampling.plan = "indepMulti",
fixed.margin = "rows",
prior.concentration = 1,
title = NULL,
subtitle = NULL,
caption = NULL,
legend.title = NULL,
ggtheme = ggplot2::theme_bw(),
ggstatsplot.layer = TRUE,
package = "RColorBrewer",
palette = "Dark2",
ggplot.component = NULL,
output = "plot",
...
)

```

Arguments

data	A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will not be accepted.
x	The variable to use as the rows in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped.
y	The variable to use as the columns in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped. Default is NULL. If NULL, one-sample proportion test (a goodness of fit test) will be run for the x variable. Otherwise an appropriate association test will be run. This argument can not be NULL for ggbarstats function.
counts	A string naming a variable in data containing counts, or NULL if each row represents a single observation.
ratio	A vector of proportions: the expected proportions for the proportion test (should sum to 1). Default is NULL, which means the null is equal theoretical proportions across the levels of the nominal variable. This means if there are two levels this will be <code>ratio = c(0.5, 0.5)</code> or if there are four levels this will be <code>ratio = c(0.25, 0.25, 0.25, 0.25)</code> , etc.
paired	Logical indicating whether data came from a within-subjects or repeated measures design study (Default: FALSE). If TRUE, McNemar's test expression will be returned. If FALSE, Pearson's chi-square test will be returned.
results.subtitle	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
label	Character decides what information needs to be displayed on the label in each pie slice. Possible options are "percentage" (default), "counts", "both".
label.args	Additional aesthetic arguments that will be passed to <code>geom_label</code> .
label.repel	Whether labels should be repelled using <code>ggrepel</code> package. This can be helpful in case the labels are overlapping.
conf.level	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
k	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code>).

proportion.test	Decides whether proportion test for x variable is to be carried out for each level of y (Default: TRUE). In ggbarstats, only p -values from this test will be displayed.
perc.k	Numeric that decides number of decimal places for percentage labels (Default: 0).
bf.message	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
sampling.plan	Character describing the sampling plan. Possible options are "indepMulti" (independent multinomial; default), "poisson", "jointMulti" (joint multinomial), "hypergeom" (hypergeometric). For more, see ?BayesFactor::contingencyTableBF().
fixed.margin	For the independent multinomial sampling plan, which margin is fixed ("rows" or "cols"). Defaults to "rows".
prior.concentration	Specifies the prior concentration parameter, set to 1 by default. It indexes the expected deviation from the null hypothesis under the alternative, and corresponds to Gunel and Dickey's (1974) "a" parameter.
title	The text for the plot title.
subtitle	The text for the plot subtitle. Will work only if results.subtitle = FALSE.
caption	The text for the plot caption.
legend.title	Title text for the legend.
ggtheme	A function, ggplot2 theme name. Default value is ggplot2::theme_bw(). Any of the ggplot2 themes, or themes from extension packages are allowed (e.g., ggthemes::theme_fivethirtyeight(), hrbrthemes::theme_ipsum_ps(), etc.).
ggstatsplot.layer	Logical that decides whether theme_ggstatsplot theme elements are to be displayed along with the selected ggtheme (Default: TRUE). theme_ggstatsplot is an opinionated theme layer that override some aspects of the selected ggtheme.
package	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running View(paletter::palettes_d_names).
palette	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running View(paletter::palettes_d_names).
ggplot.component	A ggplot component to be added to the plot prepared by ggstatsplot. This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a ggplot2 function or a list of ggplot2 functions.
output	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set results.subtitle = FALSE, then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when type = "parametric" and bf.message = TRUE, otherwise this will return a NULL.
...	Currently ignored.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggpiestats.html

See Also

[grouped_ggpiestats](#), [ggbarstats](#), [grouped_ggbarstats](#)

Examples

```
# for reproducibility
set.seed(123)

# one sample goodness of fit proportion test
ggstatsplot::ggpiestats(ggplot2::msleep, vore)

# association test (or contingency table analysis)
ggstatsplot::ggpiestats(
  data = mtcars,
  x = vs,
  y = cyl
)
```

ggscatterstats

Scatterplot with marginal distributions and statistical results

Description**Maturing**

Scatterplots from ggplot2 combined with marginal histograms/boxplots/density plots with statistical details added as a subtitle.

Usage

```
ggscatterstats(
  data,
  x,
  y,
  type = "parametric",
  conf.level = 0.95,
  bf.prior = 0.707,
  bf.message = TRUE,
  beta = 0.1,
  k = 2L,
  results.subtitle = TRUE,
  label.var = NULL,
  label.expression = NULL,
  point.label.args = list(size = 3),
  smooth.line.args = list(size = 1.5, color = "blue"),
  point.args = list(size = 3, alpha = 0.4),
  point.width.jitter = 0,
  point.height.jitter = 0,
  marginal = TRUE,
  marginal.type = "densigram",
```

```

    marginal.size = 5,
    xfill = "#009E73",
    yfill = "#D55E00",
    xlab = NULL,
    ylab = NULL,
    title = NULL,
    subtitle = NULL,
    caption = NULL,
    ggtheme = ggplot2::theme_bw(),
    ggstatsplot.layer = TRUE,
    ggplot.component = NULL,
    output = "plot",
    ...
  )

```

Arguments

<code>data</code>	A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will not be accepted.
<code>x</code>	The column in data containing the explanatory variable to be plotted on the x-axis. Can be entered either as a character string (e.g., "x") or as a bare expression (e.g, x).
<code>y</code>	The column in data containing the response (outcome) variable to be plotted on the y-axis. Can be entered either as a character string (e.g., "y") or as a bare expression (e.g, y).
<code>type</code>	Type of association between paired samples required ("parametric": Pearson's product moment correlation coefficient" or "nonparametric": Spearman's rho" or "robust": percentage bend correlation coefficient" or "bayes": Bayes Factor for Pearson's r "). Corresponding abbreviations are also accepted: "p" (for parametric/pearson), "np" (nonparametric/spearman), "r" (robust), "bf" (for bayes factor), resp.
<code>conf.level</code>	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
<code>bf.prior</code>	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors.
<code>bf.message</code>	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
<code>beta</code>	bending constant (Default: 0.1). For more, see WRS2::pbcor() .
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: k = 2L).
<code>results.subtitle</code>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
<code>label.var</code>	Variable to use for points labels. Can be entered either as a character string (e.g., "var1") or as a bare expression (e.g, var1).
<code>label.expression</code>	An expression evaluating to a logical vector that determines the subset of data points to label. This argument can be entered either as a character string (e.g., "y < 4 & z < 20") or as a bare expression (e.g., y < 4 & z < 20).

<code>point.label.args</code>	A list of additional aesthetic arguments to be passed to <code>ggrepel::geom_label_repel</code> geom used to display the labels.
<code>smooth.line.args</code>	A list of additional aesthetic arguments to be passed to <code>ggplot2::geom_smooth</code> geom used to display the regression line.
<code>point.args</code>	A list of additional aesthetic arguments to be passed to <code>ggplot2::geom_point</code> geom used to display the raw data points.
<code>point.width.jitter, point.height.jitter</code>	Degree of jitter in x and y direction, respectively. Defaults to 0 (0%) of the resolution of the data. Note that the jitter should not be specified in the <code>point.args</code> because this information will be passed to two different geoms: one displaying the points and the other displaying the labels for these points.
<code>marginal</code>	Decides whether <code>ggExtra::ggMarginal()</code> plots will be displayed; the default is TRUE.
<code>marginal.type</code>	Type of marginal distribution to be plotted on the axes ("histogram", "boxplot", "density", "violin", "densigram").
<code>marginal.size</code>	Integer describing the relative size of the marginal plots compared to the main plot. A size of 5 means that the main plot is 5x wider and 5x taller than the marginal plots.
<code>xfill, yfill</code>	Character describing color fill for x and y axes marginal distributions (default: "#009E73" (for x) and "#D55E00" (for y)). Note that the defaults are colorblind-friendly.
<code>xlab</code>	Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
<code>ylab</code>	Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>caption</code>	The text for the plot caption.
<code>ggtheme</code>	A function, ggplot2 theme name. Default value is <code>ggplot2::theme_bw()</code> . Any of the ggplot2 themes, or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> , etc.).
<code>ggstatsplot.layer</code>	Logical that decides whether <code>theme_ggstatsplot</code> theme elements are to be displayed along with the selected <code>ggtheme</code> (Default: TRUE). <code>theme_ggstatsplot</code> is an opinionated theme layer that override some aspects of the selected <code>ggtheme</code> .
<code>ggplot.component</code>	A ggplot component to be added to the plot prepared by <code>ggstatsplot</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is NULL. The argument should be entered as a ggplot2 function or a list of ggplot2 functions.
<code>output</code>	If "expression", will return expression with statistical details, while "dataframe" will return a dataframe containing the results.
<code>...</code>	Currently ignored.

Note

- If you set `marginal = TRUE`, the resulting plot can't be further modified with `ggplot2` functions since it is no longer a `ggplot` object. In case you want a `ggplot` object, set `marginal = FALSE`. Also have a look at the `ggplot.component` argument.
- The plot uses `ggrepel::geom_label_repel` to attempt to keep labels from over-lapping to the largest degree possible. As a consequence plot times will slow down massively (and the plot file will grow in size) if you have a lot of labels that overlap.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggscatterstats.html

See Also

[grouped_ggscatterstats](#), [ggcorrmat](#), [grouped_ggcorrmat](#)

Examples

```
# to get reproducible results from bootstrapping
set.seed(123)
library(ggstatsplot)

# creating dataframe with rownames converted to a new column
mtcars_new <- as_tibble(mtcars, rownames = "car")

# simple function call with the defaults
ggstatsplot::ggscatterstats(
  data = mtcars_new,
  x = wt,
  y = mpg,
  label.var = car,
  label.expression = wt < 4 & mpg < 20,
  # making further customizations with `ggplot2` functions
  ggplot.component = list(ggplot2::scale_y_continuous(
    limits = c(5, 35),
    breaks = seq(5, 35, 5)
  ))
)
```

ggwithinstats

*Box/Violin plots for group or condition comparisons in within-subjects
(or repeated measures) designs.*

Description**Maturing**

A combination of box and violin plots along with raw (unjittered) data points for within-subjects designs with statistical details included in the plot as a subtitle.

Usage

```
ggwithinstats(
  data,
  x,
  y,
  type = "parametric",
  pairwise.comparisons = TRUE,
  pairwise.display = "significant",
  p.adjust.method = "holm",
  effsize.type = "unbiased",
  bf.prior = 0.707,
  bf.message = TRUE,
  results.subtitle = TRUE,
  xlab = NULL,
  ylab = NULL,
  caption = NULL,
  title = NULL,
  subtitle = NULL,
  sample.size.label = TRUE,
  k = 2L,
  conf.level = 0.95,
  nboot = 100L,
  tr = 0.1,
  centrality.plotting = TRUE,
  centrality.point.args = list(size = 5, color = "darkred"),
  centrality.label.args = list(size = 3, nudge_x = 0.4, segment.linetype = 4),
  point.path = TRUE,
  point.path.args = list(alpha = 0.5, linetype = "dashed"),
  centrality.path = TRUE,
  centrality.path.args = list(color = "red", size = 1, alpha = 0.5),
  notch = FALSE,
  notchwidth = 0.5,
  outlier.tagging = FALSE,
  outlier.label = NULL,
  outlier.coef = 1.5,
  outlier.label.args = list(size = 3),
  violin.args = list(width = 0.5, alpha = 0.2),
  ggsignif.args = list(textsize = 3, tip_length = 0.01),
  ggtheme = ggplot2::theme_bw(),
  ggstatsplot.layer = TRUE,
  package = "RColorBrewer",
  palette = "Dark2",
  ggplot.component = NULL,
  output = "plot",
  ...
)
```

Arguments

<code>data</code>	A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will not be accepted.
<code>x</code>	The grouping variable from the dataframe data.

<code>y</code>	The response (a.k.a. outcome or dependent) variable from the dataframe <code>data</code> .
<code>type</code>	Type of statistic expected ("parametric" or "nonparametric" or "robust" or "bayes"). Corresponding abbreviations are also accepted: "p" (for parametric), "np" (nonparametric), "r" (robust), or "bf" resp.
<code>pairwise.comparisons</code>	Logical that decides whether pairwise comparisons are to be displayed (default: TRUE). Please note that only significant comparisons will be shown by default. To change this behavior, select appropriate option with <code>pairwise.display</code> argument. The pairwise comparison dataframes are prepared using the <code>pairwiseComparisons::pairwise</code> function. For more details about pairwise comparisons, see the documentation for that function.
<code>pairwise.display</code>	Decides which pairwise comparisons to display. Available options are "significant" (abbreviation accepted: "s") or "non-significant" (abbreviation accepted: "ns") or "everything"/"all". The default is "significant". You can use this argument to make sure that your plot is not uber-cluttered when you have multiple groups being compared and scores of pairwise comparisons being displayed.
<code>p.adjust.method</code>	Adjustment method for <i>p</i> -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
<code>effsize.type</code>	Type of effect size needed for <i>parametric</i> tests. The argument can be "eta" (partial eta-squared) or "omega" (partial omega-squared).
<code>bf.prior</code>	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors.
<code>bf.message</code>	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
<code>results.subtitle</code>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
<code>xlab</code>	Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
<code>ylab</code>	Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
<code>caption</code>	The text for the plot caption.
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>sample.size.label</code>	Logical that decides whether sample size information should be displayed for each level of the grouping variable <i>x</i> (Default: TRUE).
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: $k = 2L$).
<code>conf.level</code>	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
<code>nboot</code>	Number of bootstrap samples for computing confidence interval for the effect size (Default: 100).

<code>tr</code>	Trim level for the mean when carrying out robust tests. If you get error stating "Standard error cannot be computed because of Winsorized variance of 0 (e.g., due to ties). Try to decrease the trimming level.", try to play around with the value of <code>tr</code> , which is by default set to 0.1. Lowering the value might help.
<code>centrality.plotting</code>	Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the <code>type</code> argument (mean for parametric, median for non-parametric, trimmed mean for robust, and MAP estimator for Bayes).
<code>centrality.point.args</code>	A list of additional aesthetic arguments to be passed to <code>ggplot2::geom_point</code> and <code>ggrepel::geom_label_repel</code> geoms, which are involved in mean plotting.
<code>centrality.label.args</code>	A list of additional aesthetic arguments to be passed to <code>ggplot2::geom_point</code> and <code>ggrepel::geom_label_repel</code> geoms, which are involved in mean plotting.
<code>point.path, centrality.path</code>	Logical that decides whether individual data points and means, respectively, should be connected using <code>geom_path</code> . Both default to TRUE. Note that <code>point.path</code> argument is relevant only when there are two groups (i.e., in case of a <i>t</i> -test). In case of large number of data points, it is advisable to set <code>point.path = FALSE</code> as these lines can overwhelm the plot.
<code>centrality.path.args, point.path.args</code>	A list of additional aesthetic arguments passed on to <code>geom_path</code> connecting raw data points and mean points.
<code>notch</code>	A logical. If FALSE (default), a standard box plot will be displayed. If TRUE, a notched box plot will be used. Notches are used to compare groups; if the notches of two boxes do not overlap, this suggests that the medians are significantly different. In a notched box plot, the notches extend $1.58 * IQR / \sqrt{n}$, where IQR: Inter-Quartile Range. This gives a roughly 95% confidence interval for comparing medians.
<code>notchwidth</code>	For a notched box plot, width of the notch relative to the body (default 0.5).
<code>outlier.tagging</code>	Decides whether outliers should be tagged (Default: FALSE).
<code>outlier.label</code>	Label to put on the outliers that have been tagged. This can't be the same as <code>x</code> argument.
<code>outlier.coef</code>	Coefficient for outlier detection using Tukey's method. With Tukey's method, outliers are below (1st Quartile) or above (3rd Quartile) <code>outlier.coef</code> times the Inter-Quartile Range (IQR) (Default: 1.5).
<code>outlier.label.args</code>	A list of additional aesthetic arguments to be passed to <code>ggrepel::geom_label_repel</code> for outlier label plotting.
<code>violin.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_violin</code> .
<code>ggsignif.args</code>	A list of additional aesthetic arguments to be passed to <code>ggsignif::geom_signif</code> .
<code>ggtheme</code>	A function, <code>ggplot2</code> theme name. Default value is <code>ggplot2::theme_bw()</code> . Any of the <code>ggplot2</code> themes, or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> , etc.).

<code>ggstatsplot.layer</code>	Logical that decides whether <code>theme_ggstatsplot</code> theme elements are to be displayed along with the selected <code>ggtheme</code> (Default: TRUE). <code>theme_ggstatsplot</code> is an opinionated theme layer that override some aspects of the selected <code>ggtheme</code> .
<code>package</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletter::palettes_d_names)</code> .
<code>palette</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletter::palettes_d_names)</code> .
<code>ggplot.component</code>	A <code>ggplot</code> component to be added to the plot prepared by <code>ggstatsplot</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is NULL. The argument should be entered as a <code>ggplot2</code> function or a list of <code>ggplot2</code> functions.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
<code>...</code>	Currently ignored.

Note

1. Please note that the function expects that the data is already sorted by subject/repeated measures ID.
2. To get the Bayes Factor message, you are going to need to install the development version of `BayesFactor` (0.9.12-4.3). You can download it by running: `remotes::install_github("richarddmorey/BayesFactor")`.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggwithinstats.html

See Also

[grouped_ggbetweenstats](#), [ggbetweenstats](#), [grouped_ggwithinstats](#)

Examples

```
# setup
set.seed(123)
library(ggstatsplot)

# two groups (*t*-test)
ggstatsplot::ggwithinstats(
  data = VR_dilemma,
  x = modality,
  y = score,
  xlab = "Presentation modality",
  ylab = "Proportion of utilitarian decisions"
)

# more than two groups (anova)
```

```
library(WRS2)

ggstatsplot::ggwithinstats(
  data = WineTasting,
  x = Wine,
  y = Taste,
  type = "np",
  pairwise.comparisons = TRUE,
  outlier.tagging = TRUE,
  outlier.label = Taster
)
```

grouped_ggbarstats *Grouped bar (column) charts with statistical tests*

Description

Maturing

Helper function for `ggstatsplot::ggbarstats` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots2`.

Usage

```
grouped_ggbarstats(
  data,
  x,
  y,
  counts = NULL,
  grouping.var,
  title.prefix = NULL,
  output = "plot",
  ...,
  plotgrid.args = list(),
  title.text = NULL,
  title.args = list(size = 16, fontface = "bold"),
  caption.text = NULL,
  caption.args = list(size = 10),
  sub.text = NULL,
  sub.args = list(size = 12)
)
```

Arguments

<code>data</code>	A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will not be accepted.
<code>x</code>	The variable to use as the rows in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped.
<code>y</code>	The variable to use as the columns in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped. Default is NULL. If NULL, one-sample proportion test (a goodness of fit test) will be run

	for the x variable. Otherwise an appropriate association test will be run. This argument can not be NULL for ggbarstats function.
counts	A string naming a variable in data containing counts, or NULL if each row represents a single observation.
grouping.var	A single grouping variable (can be entered either as a bare name x or as a string "x").
title.prefix	Character string specifying the prefix text for the fixed plot title (name of each factor level) (Default: NULL). If NULL, the variable name entered for grouping.var will be used.
output	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set results.subtitle = FALSE, then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when type = "parametric" and bf.message = TRUE, otherwise this will return a NULL.
...	Arguments passed on to ggbarstats
xlab	Custom text for the x axis label (Default: NULL, which will cause the x axis label to be the x variable).
ylab	Custom text for the y axis label (Default: NULL).
sample.size.label	Logical that decides whether sample size information should be displayed for each level of the grouping variable y (Default: TRUE).
ratio	A vector of proportions: the expected proportions for the proportion test (should sum to 1). Default is NULL, which means the null is equal theoretical proportions across the levels of the nominal variable. This means if there are two levels this will be ratio = c(0.5, 0.5) or if there are four levels this will be ratio = c(0.25, 0.25, 0.25, 0.25), etc.
paired	Logical indicating whether data came from a within-subjects or repeated measures design study (Default: FALSE). If TRUE, McNemar's test expression will be returned. If FALSE, Pearson's chi-square test will be returned.
results.subtitle	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
label	Character decides what information needs to be displayed on the label in each pie slice. Possible options are "percentage" (default), "counts", "both".
label.args	Additional aesthetic arguments that will be passed to geom_label.
conf.level	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
k	Number of digits after decimal point (should be an integer) (Default: k = 2L).
proportion.test	Decides whether proportion test for x variable is to be carried out for each level of y (Default: TRUE). In ggbarstats, only p-values from this test will be displayed.
perc.k	Numeric that decides number of decimal places for percentage labels (Default: 0).
bf.message	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).

<code>sampling.plan</code>	Character describing the sampling plan. Possible options are "indepMulti" (independent multinomial; default), "poisson", "jointMulti" (joint multinomial), "hypergeom" (hypergeometric). For more, see <code>?BayesFactor::contingen</code>
<code>fixed.margin</code>	For the independent multinomial sampling plan, which margin is fixed ("rows" or "cols"). Defaults to "rows".
<code>prior.concentration</code>	Specifies the prior concentration parameter, set to 1 by default. It indexes the expected deviation from the null hypothesis under the alternative, and corresponds to Gunel and Dickey's (1974) "a" parameter.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>caption</code>	The text for the plot caption.
<code>legend.title</code>	Title text for the legend.
<code>ggtheme</code>	A function, ggplot2 theme name. Default value is <code>ggplot2::theme_bw()</code> . Any of the ggplot2 themes, or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> , etc.).
<code>ggstatsplot.layer</code>	Logical that decides whether <code>theme_ggstatsplot</code> theme elements are to be displayed along with the selected <code>ggtheme</code> (Default: TRUE). <code>theme_ggstatsplot</code> is an opinionated theme layer that override some aspects of the selected <code>ggtheme</code> .
<code>package</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d</code>
<code>palette</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d</code>
<code>ggplot.component</code>	A ggplot component to be added to the plot prepared by <code>ggstatsplot</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is NULL. The argument should be entered as a ggplot2 function or a list of ggplot2 functions.
<code>plotgrid.args</code>	A list of additional arguments to <code>cowplot::plot_grid</code> .
<code>title.text</code>	String or plotmath expression to be drawn as title for the <i>combined plot</i> .
<code>title.args</code>	A list of additional arguments provided to title, caption and sub, resp.
<code>caption.text</code>	String or plotmath expression to be drawn as the caption for the <i>combined plot</i> .
<code>caption.args</code>	A list of additional arguments provided to title, caption and sub, resp.
<code>sub.text</code>	The label with which the <i>combined plot</i> should be annotated. Can be a plotmath expression.
<code>sub.args</code>	A list of additional arguments provided to title, caption and sub, resp.

See Also

[ggbarstats](#), [ggpiestats](#), [grouped_ggpiestats](#)

Examples

```
# for reproducibility
set.seed(123)

# let's create a smaller dataframe
diamonds_short <- ggplot2::diamonds %>%
  dplyr::filter(.data = ., cut %in% c("Very Good", "Ideal")) %>%
```

```

dplyr::filter(.data = ., clarity %in% c("SI1", "SI2", "VS1", "VS2")) %>%
dplyr::sample_frac(tbl = ., size = 0.05)

# plot
# let's skip statistical analysis
ggstatsplot::grouped_ggbarstats(
  data = diamonds_short,
  x = color,
  y = clarity,
  grouping.var = cut,
  title.prefix = "Quality",
  plotgrid.args = list(nrow = 2)
)

```

grouped_ggbetweenstats

Violin plots for group or condition comparisons in between-subjects designs repeated across all levels of a grouping variable.

Description

Maturing

Helper function for `ggstatsplot::ggbetweenstats` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots2`.

Usage

```

grouped_ggbetweenstats(
  data,
  x,
  y,
  grouping.var,
  outlier.label = NULL,
  title.prefix = NULL,
  output = "plot",
  ...,
  plotgrid.args = list(),
  title.text = NULL,
  title.args = list(size = 16, fontface = "bold"),
  caption.text = NULL,
  caption.args = list(size = 10),
  sub.text = NULL,
  sub.args = list(size = 12)
)

```

Arguments

<code>data</code>	A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will not be accepted.
<code>x</code>	The grouping variable from the dataframe data.

<code>y</code>	The response (a.k.a. outcome or dependent) variable from the dataframe data.
<code>grouping.var</code>	A single grouping variable (can be entered either as a bare name <code>x</code> or as a string " <code>x</code> ").
<code>outlier.label</code>	Label to put on the outliers that have been tagged. This can't be the same as <code>x</code> argument.
<code>title.prefix</code>	Character string specifying the prefix text for the fixed plot title (name of each factor level) (Default: NULL). If NULL, the variable name entered for <code>grouping.var</code> will be used.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
<code>...</code>	Arguments passed on to ggbetweenstats
<code>plot.type</code>	Character describing the <i>type</i> of plot. Currently supported plots are "box" (for pure boxplots), "violin" (for pure violin plots), and "boxviolin" (for a combination of box and violin plots; default).
<code>xlab</code>	Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
<code>ylab</code>	Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
<code>pairwise.comparisons</code>	Logical that decides whether pairwise comparisons are to be displayed (default: TRUE). Please note that only significant comparisons will be shown by default. To change this behavior, select appropriate option with <code>pairwise.display</code> argument. The pairwise comparison dataframes are prepared using the <code>pairwiseComparisons::pairwise_comparisons</code> function. For more details about pairwise comparisons, see the documentation for that function.
<code>p.adjust.method</code>	Adjustment method for <i>p</i> -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
<code>pairwise.display</code>	Decides which pairwise comparisons to display. Available options are "significant" (abbreviation accepted: "s") or "non-significant" (abbreviation accepted: "ns") or "everything"/"all". The default is "significant". You can use this argument to make sure that your plot is not uber-cluttered when you have multiple groups being compared and scores of pairwise comparisons being displayed.
<code>bf.prior</code>	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors.
<code>bf.message</code>	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
<code>results.subtitle</code>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>caption</code>	The text for the plot caption.

- `sample.size.label` Logical that decides whether sample size information should be displayed for each level of the grouping variable `x` (Default: TRUE).
- `notch` A logical. If FALSE (default), a standard box plot will be displayed. If TRUE, a notched box plot will be used. Notches are used to compare groups; if the notches of two boxes do not overlap, this suggests that the medians are significantly different. In a notched box plot, the notches extend $1.58 * IQR / \sqrt{n}$, where IQR: Inter-Quartile Range. This gives a roughly 95% confidence interval for comparing medians.
- `notchwidth` For a notched box plot, width of the notch relative to the body (default 0.5).
- `outlier.color` Default aesthetics for outliers (Default: "black").
- `outlier.tagging` Decides whether outliers should be tagged (Default: FALSE).
- `outlier.shape` Hiding the outliers can be achieved by setting `outlier.shape = NA`. Importantly, this does not remove the outliers, it only hides them, so the range calculated for the y-axis will be the same with outliers shown and outliers hidden.
- `outlier.label.args` A list of additional aesthetic arguments to be passed to `ggrepel::geom_label_repel` for outlier label plotting.
- `outlier.coef` Coefficient for outlier detection using Tukey's method. With Tukey's method, outliers are below (1st Quartile) or above (3rd Quartile) `outlier.coef` times the Inter-Quartile Range (IQR) (Default: 1.5).
- `centrality.plotting` Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the type argument (**mean** for parametric, **median** for non-parametric, **trimmed mean** for robust, and **MAP estimator** for Bayes).
- `point.args` A list of additional aesthetic arguments to be passed to the `geom_point` displaying the raw data.
- `violin.args` A list of additional aesthetic arguments to be passed to the `geom_violin`.
- `ggplot.component` A ggplot component to be added to the plot prepared by `ggstatsplot`. This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a `ggplot2` function or a list of `ggplot2` functions.
- `package` Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d`
- `palette` Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d`
- `centrality.point.args` A list of additional aesthetic arguments to be passed to `ggplot2::geom_point` and `ggrepel::geom_label_repel` geoms, which are involved in mean plotting.
- `centrality.label.args` A list of additional aesthetic arguments to be passed to `ggplot2::geom_point` and `ggrepel::geom_label_repel` geoms, which are involved in mean plotting.
- `ggsignif.args` A list of additional aesthetic arguments to be passed to `ggsignif::geom_signif`.
- `ggtheme` A function, `ggplot2` theme name. Default value is `ggplot2::theme_bw()`. Any of the `ggplot2` themes, or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.).
- `ggstatsplot.layer` Logical that decides whether `theme_ggstatsplot` theme elements are to be displayed along with the selected `ggtheme` (Default:

TRUE). `theme_ggstatsplot` is an opinionated theme layer that override some aspects of the selected `ggtheme`.

`type` Type of statistic expected ("parametric" or "nonparametric" or "robust" or "bayes"). Corresponding abbreviations are also accepted: "p" (for parametric), "np" (nonparametric), "r" (robust), or "bf" resp.

`effsize.type` Type of effect size needed for *parametric* tests. The argument can be "eta" (partial eta-squared) or "omega" (partial omega-squared).

`k` Number of digits after decimal point (should be an integer) (Default: $k = 2L$).

`var.equal` a logical variable indicating whether to treat the two variances as being equal. If TRUE then the pooled variance is used to estimate the variance otherwise the Welch (or Satterthwaite) approximation to the degrees of freedom is used.

`conf.level` Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).

`nboot` Number of bootstrap samples for computing confidence interval for the effect size (Default: 100).

`tr` Trim level for the mean when carrying out robust tests. If you get error stating "Standard error cannot be computed because of Winsorized variance of 0 (e.g., due to ties). Try to decrease the trimming level.", try to play around with the value of `tr`, which is by default set to 0.1. Lowering the value might help.

`plotgrid.args` A list of additional arguments to `cowplot::plot_grid`.

`title.text` String or plotmath expression to be drawn as title for the *combined plot*.

`title.args` A list of additional arguments provided to `title`, `caption` and `sub`, resp.

`caption.text` String or plotmath expression to be drawn as the caption for the *combined plot*.

`caption.args` A list of additional arguments provided to `title`, `caption` and `sub`, resp.

`sub.text` The label with which the *combined plot* should be annotated. Can be a plotmath expression.

`sub.args` A list of additional arguments provided to `title`, `caption` and `sub`, resp.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggbetweenstats.html

See Also

[ggbetweenstats](#), [ggwithinstats](#), [grouped_ggwithinstats](#)

Examples

```
# to get reproducible results from bootstrapping
set.seed(123)

# the most basic function call
ggstatsplot::grouped_ggbetweenstats(
  data = dplyr::filter(ggplot2::mpg, drv != "4"),
  x = year,
  y = hwy,
  grouping.var = drv,
  conf.level = 0.99
```

```

)

# modifying individual plots using `ggplot.component` argument
ggstatsplot::grouped_ggbetweenstats(
  data = dplyr::filter(
    ggstatsplot::movies_long,
    genre %in% c("Action", "Comedy"),
    mpaa %in% c("R", "PG")
  ),
  x = genre,
  y = rating,
  grouping.var = mpaa,
  results.subtitle = FALSE,
  ggplot.component = ggplot2::scale_y_continuous(
    breaks = seq(1, 9, 1),
    limits = (c(1, 9))
  )
)
)

```

grouped_ggcorrmat	<i>Visualization of a correlalogram (or correlation matrix) for all levels of a grouping variable</i>
-------------------	---

Description

Maturing

Helper function for `ggstatsplot::ggcorrmat` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots2`.

Usage

```

grouped_ggcorrmat(
  data,
  cor.vars = NULL,
  cor.vars.names = NULL,
  grouping.var,
  title.prefix = NULL,
  output = "plot",
  ...,
  plotgrid.args = list(),
  title.text = NULL,
  title.args = list(size = 16, fontface = "bold"),
  caption.text = NULL,
  caption.args = list(size = 10),
  sub.text = NULL,
  sub.args = list(size = 12)
)

```

Arguments

`data` Dataframe from which variables specified are preferentially to be taken.

<code>cor.vars</code>	List of variables for which the correlation matrix is to be computed and visualized. If NULL (default), all numeric variables from data will be used.
<code>cor.vars.names</code>	Optional list of names to be used for <code>cor.vars</code> . The names should be entered in the same order.
<code>grouping.var</code>	A single grouping variable (can be entered either as a bare name <code>x</code> or as a string " <code>x</code> ").
<code>title.prefix</code>	Character string specifying the prefix text for the fixed plot title (name of each factor level) (Default: NULL). If NULL, the variable name entered for <code>grouping.var</code> will be used.
<code>output</code>	Character that decides expected output from this function. If "plot", the visualization matrix will be returned. If "dataframe" (or literally anything other than "plot"), a dataframe containing all details from statistical analyses (e.g., correlation coefficients, statistic values, <i>p</i> -values, no. of observations, etc.) will be returned.
...	Arguments passed on to <code>ggcorrmat</code>
<code>partial</code>	Can be TRUE for partial correlations. For Bayesian partial correlations, "full" instead of pseudo-Bayesian partial correlations (i.e., Bayesian correlation based on frequentist partialization) are returned.
<code>matrix.type</code>	Character, "upper" (default), "lower", or "full", display full matrix, lower triangular or upper triangular matrix.
<code>sig.level</code>	Significance level (Default: 0.05). If the <i>p</i> -value in <i>p</i> -value matrix is bigger than <code>sig.level</code> , then the corresponding correlation coefficient is regarded as insignificant and flagged as such in the plot. Relevant only when <code>output = "plot"</code> .
<code>colors</code>	A vector of 3 colors for low, mid, and high correlation values. If set to NULL, manual specification of colors will be turned off and 3 colors from the specified palette from package will be selected.
<code>pch</code>	Decides the point shape to be used for insignificant correlation coefficients (only valid when <code>insig = "pch"</code>). Default: <code>pch = "cross"</code> .
<code>ggcorrplot.args</code>	A list of additional (mostly aesthetic) arguments that will be passed to <code>ggcorrplot::ggcorrplot</code> function. The list should avoid any of the following arguments since they are already internally being used: <code>corr</code> , <code>method</code> , <code>p.mat</code> , <code>sig.level</code> , <code>ggtheme</code> , <code>colors</code> , <code>lab</code> , <code>pch</code> , <code>legend.title</code> , <code>digits</code> .
<code>type</code>	Type of association between paired samples required ("parametric": Pearson's product moment correlation coefficient" or "nonparametric": Spearman's rho" or "robust": percentage bend correlation coefficient" or "bayes": Bayes Factor for Pearson's <i>r</i> "). Corresponding abbreviations are also accepted: "p" (for parametric/pearson), "np" (nonparametric/spearman), "r" (robust), "bf" (for bayes factor), resp.
<code>beta</code>	bending constant (Default: 0.1). For more, see <code>WRS2::pbcor()</code> .
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code>).
<code>conf.level</code>	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
<code>bf.prior</code>	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors.
<code>p.adjust.method</code>	Adjustment method for <i>p</i> -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".

	package	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d_</code>
	palette	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d_</code>
	ggtheme	A function, ggplot2 theme name. Default value is <code>ggplot2::theme_bw()</code> . Any of the ggplot2 themes, or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> , etc.).
	ggstatsplot.layer	Logical that decides whether theme_ggstatsplot theme elements are to be displayed along with the selected ggtheme (Default: TRUE). theme_ggstatsplot is an opinionated theme layer that override some aspects of the selected ggtheme.
	ggplot.component	A ggplot component to be added to the plot prepared by ggstatsplot. This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a ggplot2 function or a list of ggplot2 functions.
	subtitle	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
	caption	The text for the plot caption.
plotgrid.args		A list of additional arguments to <code>cowplot::plot_grid</code> .
title.text		String or plotmath expression to be drawn as title for the <i>combined plot</i> .
title.args		A list of additional arguments provided to title, caption and sub, resp.
caption.text		String or plotmath expression to be drawn as the caption for the <i>combined plot</i> .
caption.args		A list of additional arguments provided to title, caption and sub, resp.
sub.text		The label with which the <i>combined plot</i> should be annotated. Can be a plotmath expression.
sub.args		A list of additional arguments provided to title, caption and sub, resp.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggcorrmat.html

See Also

[ggcorrmat](#), [ggscatterstats](#), [grouped_ggscatterstats](#)

Examples

```
# for reproducibility
set.seed(123)

# for plot
ggstatsplot::grouped_ggcorrmat(
  data = iris,
  grouping.var = Species,
  type = "robust",
  p.adjust.method = "holm"
)

# for dataframe
```

```
ggstatsplot::grouped_ggcorrmat(
  data = ggplot2::msleep,
  grouping.var = vore,
  type = "bayes",
  output = "dataframe"
)
```

grouped_ggdotplotstats

Grouped histograms for distribution of a labeled numeric variable

Description

Maturing

Helper function for `ggstatsplot::ggdotplotstats` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots2`.

Usage

```
grouped_ggdotplotstats(
  data,
  x,
  y,
  grouping.var,
  title.prefix = NULL,
  output = "plot",
  ...,
  plotgrid.args = list(),
  title.text = NULL,
  title.args = list(size = 16, fontface = "bold"),
  caption.text = NULL,
  caption.args = list(size = 10),
  sub.text = NULL,
  sub.args = list(size = 12)
)
```

Arguments

<code>data</code>	A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will not be accepted.
<code>x</code>	A numeric variable from the dataframe <code>data</code> .
<code>y</code>	Label or grouping variable.
<code>grouping.var</code>	A single grouping variable (can be entered either as a bare name <code>x</code> or as a string <code>"x"</code>).
<code>title.prefix</code>	Character string specifying the prefix text for the fixed plot title (name of each factor level) (Default: <code>NULL</code>). If <code>NULL</code> , the variable name entered for <code>grouping.var</code> will be used.
<code>output</code>	If <code>"expression"</code> , will return expression with statistical details, while <code>"dataframe"</code> will return a dataframe containing the results.

- ...
- Arguments passed on to [ggdotplotstats](#)
- `point.args` A list of additional aesthetic arguments passed to `geom_point`.
- `type` Type of statistic expected ("parametric" or "nonparametric" or "robust" or "bayes"). Corresponding abbreviations are also accepted: "p" (for parametric), "np" (nonparametric), "r" (robust), or "bf" resp.
- `tr` Trim level for the mean when carrying out robust tests. If you get error stating "Standard error cannot be computed because of Winsorized variance of 0 (e.g., due to ties). Try to decrease the trimming level.", try to play around with the value of `tr`, which is by default set to 0.1. Lowering the value might help.
- `centrality.k` Integer denoting the number of decimal places expected for centrality parameter label. (Default: 2L).
- `centrality.line.args` A list of additional aesthetic arguments to be passed to the `geom_line` used to display the lines corresponding to the centrality parameter and test value.
- `centrality.label.args` A list of additional aesthetic arguments to be passed to the `geom_label` used to display the label corresponding to the centrality parameter and test value.
- `xlab` Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
- `subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.
- `caption` The text for the plot caption.
- `test.value` A number specifying the value of the null hypothesis (Default: 0).
- `bf.prior` A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors.
- `bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).
- `effsize.type` Type of effect size needed for *parametric* tests. The argument can be "d" (for Cohen's *d*) or "g" (for Hedge's *g*).
- `conf.level` Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
- `nboot` Number of bootstrap samples for computing confidence interval for the effect size (Default: 100).
- `k` Number of digits after decimal point (should be an integer) (Default: k = 2L).
- `results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
- `centrality.plotting` Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the type argument (**mean** for parametric, **median** for non-parametric, **trimmed mean** for robust, and **MAP estimator** for Bayes).
- `ggplot.component` A ggplot component to be added to the plot prepared by `ggstatsplot`. This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a `ggplot2` function or a list of `ggplot2` functions.
- `ggtheme` A function, `ggplot2` theme name. Default value is `ggplot2::theme_bw()`. Any of the `ggplot2` themes, or themes from extension packages are allowed

	(e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> , etc.).
<code>ggstatsplot.layer</code>	Logical that decides whether <code>theme_ggstatsplot</code> theme elements are to be displayed along with the selected <code>ggtheme</code> (Default: TRUE). <code>theme_ggstatsplot</code> is an opinionated theme layer that override some aspects of the selected <code>ggtheme</code> .
<code>ylab</code>	Labels for x- and y- axis variables, respectively (Defaults: "regression coefficient" and "term").
<code>plotgrid.args</code>	A list of additional arguments to <code>cowplot::plot_grid</code> .
<code>title.text</code>	String or plotmath expression to be drawn as title for the <i>combined plot</i> .
<code>title.args</code>	A list of additional arguments provided to title, caption and sub, resp.
<code>caption.text</code>	String or plotmath expression to be drawn as the caption for the <i>combined plot</i> .
<code>caption.args</code>	A list of additional arguments provided to title, caption and sub, resp.
<code>sub.text</code>	The label with which the <i>combined plot</i> should be annotated. Can be a plotmath expression.
<code>sub.args</code>	A list of additional arguments provided to title, caption and sub, resp.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggdotplotstats.html

See Also

[grouped_gghistostats](#), [ggdotplotstats](#), [gghistostats](#)

Examples

```
# for reproducibility
set.seed(123)

# removing factor level with very few no. of observations
df <- dplyr::filter(.data = ggplot2::mpg, cyl %in% c("4", "6", "8"))

# plot
ggstatsplot::grouped_ggdotplotstats(
  data = df,
  x = cty,
  y = manufacturer,
  grouping.var = cyl,
  test.value = 15.5,
  title.prefix = "cylinder count",
  ggplot.component = ggplot2::scale_x_continuous(
    sec.axis = ggplot2::dup_axis(),
    limits = c(12, 24),
    breaks = seq(12, 24, 2)
  )
)
```

grouped_gghistostats *Grouped histograms for distribution of a numeric variable*

Description

Maturing

Helper function for `ggstatsplot::gghistostats` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots2`.

Usage

```
grouped_gghistostats(
  data,
  x,
  grouping.var,
  binwidth = NULL,
  title.prefix = NULL,
  output = "plot",
  ...,
  plotgrid.args = list(),
  title.text = NULL,
  title.args = list(size = 16, fontface = "bold"),
  caption.text = NULL,
  caption.args = list(size = 10),
  sub.text = NULL,
  sub.args = list(size = 12)
)
```

Arguments

<code>data</code>	A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will not be accepted.
<code>x</code>	A numeric variable from the dataframe <code>data</code> .
<code>grouping.var</code>	A single grouping variable (can be entered either as a bare name <code>x</code> or as a string <code>"x"</code>).
<code>binwidth</code>	The width of the histogram bins. Can be specified as a numeric value, or a function that calculates width from <code>x</code> . The default is to use the $\max(x) - \min(x) / \sqrt{N}$. You should always check this value and explore multiple widths to find the best to illustrate the stories in your data.
<code>title.prefix</code>	Character string specifying the prefix text for the fixed plot title (name of each factor level) (Default: <code>NULL</code>). If <code>NULL</code> , the variable name entered for <code>grouping.var</code> will be used.
<code>output</code>	If <code>"expression"</code> , will return expression with statistical details, while <code>"dataframe"</code> will return a dataframe containing the results.
<code>...</code>	Arguments passed on to gghistostats
<code>normal.curve</code>	A logical value that decides whether to super-impose a normal curve using <code>stats::dnorm(mean(x), sd(x))</code> . Default is <code>FALSE</code> .
<code>normal.curve.args</code>	A list of additional aesthetic arguments to be passed to the normal curve.

- `bar.fill` Character input that decides which color will uniformly fill all the bars in the histogram (Default: "grey50").
- `type` Type of statistic expected ("parametric" or "nonparametric" or "robust" or "bayes"). Corresponding abbreviations are also accepted: "p" (for parametric), "np" (nonparametric), "r" (robust), or "bf" resp.
- `test.value` A number specifying the value of the null hypothesis (Default: 0).
- `bf.prior` A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors.
- `effsize.type` Type of effect size needed for *parametric* tests. The argument can be "d" (for Cohen's *d*) or "g" (for Hedge's *g*).
- `conf.level` Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
- `nboot` Number of bootstrap samples for computing confidence interval for the effect size (Default: 100).
- `tr` Trim level for the mean when carrying out robust tests. If you get error stating "Standard error cannot be computed because of Winsorized variance of 0 (e.g., due to ties). Try to decrease the trimming level.", try to play around with the value of `tr`, which is by default set to 0.1. Lowering the value might help.
- `k` Number of digits after decimal point (should be an integer) (Default: $k = 2L$).
- `centrality.k` Integer denoting the number of decimal places expected for centrality parameter label. (Default: $2L$).
- `centrality.line.args` A list of additional aesthetic arguments to be passed to the `geom_line` used to display the lines corresponding to the centrality parameter and test value.
- `centrality.label.args` A list of additional aesthetic arguments to be passed to the `geom_label` used to display the label corresponding to the centrality parameter and test value.
- `xlab` Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
- `subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.
- `caption` The text for the plot caption.
- `bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).
- `ggtheme` A function, ggplot2 theme name. Default value is `ggplot2::theme_bw()`. Any of the ggplot2 themes, or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.).
- `ggstatsplot.layer` Logical that decides whether `theme_ggstatsplot` theme elements are to be displayed along with the selected `ggtheme` (Default: TRUE). `theme_ggstatsplot` is an opinionated theme layer that override some aspects of the selected `ggtheme`.
- `results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
- `centrality.plotting` Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function

decides which central tendency measure to show depending on the type argument (**mean** for parametric, **median** for non-parametric, **trimmed mean** for robust, and **MAP estimator** for Bayes).

`ggplot.component` A ggplot component to be added to the plot prepared by `ggstatsplot`. This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a ggplot2 function or a list of ggplot2 functions.

<code>plotgrid.args</code>	A list of additional arguments to <code>cowplot::plot_grid</code> .
<code>title.text</code>	String or plotmath expression to be drawn as title for the <i>combined plot</i> .
<code>title.args</code>	A list of additional arguments provided to title, caption and sub, resp.
<code>caption.text</code>	String or plotmath expression to be drawn as the caption for the <i>combined plot</i> .
<code>caption.args</code>	A list of additional arguments provided to title, caption and sub, resp.
<code>sub.text</code>	The label with which the <i>combined plot</i> should be annotated. Can be a plotmath expression.
<code>sub.args</code>	A list of additional arguments provided to title, caption and sub, resp.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/gghistostats.html

See Also

[gghistostats](#), [ggdotplotstats](#), [grouped_ggdotplotstats](#)

Examples

```
# for reproducibility
set.seed(123)

# plot
ggstatsplot::grouped_gghistostats(
  data = iris,
  x = Sepal.Length,
  test.value = 5,
  grouping.var = Species,
  bar.fill = "orange",
  ggplot.component = list(
    ggplot2::scale_x_continuous(breaks = seq(3, 9, 1), limits = (c(3, 9))),
    ggplot2::scale_y_continuous(breaks = seq(0, 25, 5), limits = (c(0, 25)))
  ),
  plotgrid.args = list(nrow = 1, labels = c("(i)", "(ii)", "(iii)")),
)
```

grouped_ggpiestats *Grouped pie charts with statistical tests*

Description

Helper function for `ggstatsplot::ggpiestats` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots`.

Usage

```
grouped_ggpiestats(
  data,
  x,
  y = NULL,
  counts = NULL,
  grouping.var,
  title.prefix = NULL,
  output = "plot",
  ...,
  plotgrid.args = list(),
  title.text = NULL,
  title.args = list(size = 16, fontface = "bold"),
  caption.text = NULL,
  caption.args = list(size = 10),
  sub.text = NULL,
  sub.args = list(size = 12)
)
```

Arguments

<code>data</code>	A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will not be accepted.
<code>x</code>	The variable to use as the rows in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped.
<code>y</code>	The variable to use as the columns in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped. Default is NULL. If NULL, one-sample proportion test (a goodness of fit test) will be run for the x variable. Otherwise an appropriate association test will be run. This argument can not be NULL for <code>ggbarstats</code> function.
<code>counts</code>	A string naming a variable in data containing counts, or NULL if each row represents a single observation.
<code>grouping.var</code>	A single grouping variable (can be entered either as a bare name <code>x</code> or as a string <code>"x"</code>).
<code>title.prefix</code>	Character string specifying the prefix text for the fixed plot title (name of each factor level) (Default: NULL). If NULL, the variable name entered for <code>grouping.var</code> will be used.
<code>output</code>	Character that describes what is to be returned: can be <code>"plot"</code> (default) or <code>"subtitle"</code> or <code>"caption"</code> . Setting this to <code>"subtitle"</code> will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> ,

then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when type = "parametric" and bf.message = TRUE, otherwise this will return a NULL.

...

Arguments passed on to `ggpiestats`

`proportion.test` Decides whether proportion test for x variable is to be carried out for each level of y (Default: TRUE). In `ggbarstats`, only *p*-values from this test will be displayed.

`perc.k` Numeric that decides number of decimal places for percentage labels (Default: 0).

`label` Character decides what information needs to be displayed on the label in each pie slice. Possible options are "percentage" (default), "counts", "both".

`label.args` Additional aesthetic arguments that will be passed to `geom_label`.

`label.repel` Whether labels should be repelled using `ggrepel` package. This can be helpful in case the labels are overlapping.

`legend.title` Title text for the legend.

`results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.

`conf.level` Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).

`k` Number of digits after decimal point (should be an integer) (Default: $k = 2L$).

`bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).

`subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.

`caption` The text for the plot caption.

`ggtheme` A function, `ggplot2` theme name. Default value is `ggplot2::theme_bw()`. Any of the `ggplot2` themes, or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.).

`ggstatsplot.layer` Logical that decides whether `theme_ggstatsplot` theme elements are to be displayed along with the selected `ggtheme` (Default: TRUE). `theme_ggstatsplot` is an opinionated theme layer that override some aspects of the selected `ggtheme`.

`package` Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d`

`palette` Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d`

`ggplot.component` A `ggplot` component to be added to the plot prepared by `ggstatsplot`. This argument is primarily helpful for `grouped_` variants of all primary functions. Default is NULL. The argument should be entered as a `ggplot2` function or a list of `ggplot2` functions.

`ratio` A vector of proportions: the expected proportions for the proportion test (should sum to 1). Default is NULL, which means the null is equal theoretical proportions across the levels of the nominal variable. This means if there are two levels this will be `ratio = c(0.5, 0.5)` or if there are four levels this will be `ratio = c(0.25, 0.25, 0.25, 0.25)`, etc.

	paired	Logical indicating whether data came from a within-subjects or repeated measures design study (Default: FALSE). If TRUE, McNemar's test expression will be returned. If FALSE, Pearson's chi-square test will be returned.
	sampling.plan	Character describing the sampling plan. Possible options are "indepMulti" (independent multinomial; default), "poisson", "jointMulti" (joint multinomial), "hypergeom" (hypergeometric). For more, see <code>?BayesFactor::contingen</code>
	fixed.margin	For the independent multinomial sampling plan, which margin is fixed ("rows" or "cols"). Defaults to "rows".
	prior.concentration	Specifies the prior concentration parameter, set to 1 by default. It indexes the expected deviation from the null hypothesis under the alternative, and corresponds to Gunel and Dickey's (1974) "a" parameter.
plotgrid.args		A list of additional arguments to <code>cowplot::plot_grid</code> .
title.text		String or plotmath expression to be drawn as title for the <i>combined plot</i> .
title.args		A list of additional arguments provided to title, caption and sub, resp.
caption.text		String or plotmath expression to be drawn as the caption for the <i>combined plot</i> .
caption.args		A list of additional arguments provided to title, caption and sub, resp.
sub.text		The label with which the <i>combined plot</i> should be annotated. Can be a plotmath expression.
sub.args		A list of additional arguments provided to title, caption and sub, resp.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggpiestats.html

See Also

[ggbarstats](#), [ggpiestats](#), [grouped_ggbarstats](#)

Examples

```
# grouped one-sample proportion test
# let's skip statistical analysis
ggstatsplot::grouped_ggpiestats(
  data = mtcars,
  grouping.var = am,
  x = cyl,
  results.subtitle = FALSE
)
```

grouped_ggscatterstats

Scatterplot with marginal distributions for all levels of a grouping variable

Description

Grouped scatterplots from `ggplot2` combined with marginal histograms/boxplots/density plots with statistical details added as a subtitle.

Usage

```
grouped_ggscatterstats(
  data,
  x,
  y,
  grouping.var,
  label.var = NULL,
  label.expression = NULL,
  title.prefix = NULL,
  output = "plot",
  ...,
  plotgrid.args = list(),
  title.text = NULL,
  title.args = list(size = 16, fontface = "bold"),
  caption.text = NULL,
  caption.args = list(size = 10),
  sub.text = NULL,
  sub.args = list(size = 12)
)
```

Arguments

data	A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will not be accepted.
x	The column in data containing the explanatory variable to be plotted on the x-axis. Can be entered either as a character string (e.g., "x") or as a bare expression (e.g, x).
y	The column in data containing the response (outcome) variable to be plotted on the y-axis. Can be entered either as a character string (e.g., "y") or as a bare expression (e.g, y).
grouping.var	A single grouping variable (can be entered either as a bare name x or as a string "x").
label.var	Variable to use for points labels. Can be entered either as a character string (e.g., "var1") or as a bare expression (e.g, var1).
label.expression	An expression evaluating to a logical vector that determines the subset of data points to label. This argument can be entered either as a character string (e.g., "y < 4 & z < 20") or as a bare expression (e.g., y < 4 & z < 20).
title.prefix	Character string specifying the prefix text for the fixed plot title (name of each factor level) (Default: NULL). If NULL, the variable name entered for grouping.var will be used.
output	If "expression", will return expression with statistical details, while "dataframe" will return a dataframe containing the results.
...	Arguments passed on to ggscatterstats
	point.label.args A list of additional aesthetic arguments to be passed to <code>ggrepel::geom_label_repel</code> geom used to display the labels.
	smooth.line.args A list of additional aesthetic arguments to be passed to <code>ggplot2::geom_smooth</code> geom used to display the regression line.
	point.args A list of additional aesthetic arguments to be passed to <code>ggplot2::geom_point</code> geom used to display the raw data points.

- `marginal` Decides whether `ggExtra::ggMarginal()` plots will be displayed; the default is `TRUE`.
- `point.width.jitter` Degree of jitter in x and y direction, respectively. Defaults to 0 (0%) of the resolution of the data. Note that the jitter should not be specified in the `point.args` because this information will be passed to two different geoms: one displaying the points and the other displaying the labels for these points.
- `point.height.jitter` Degree of jitter in x and y direction, respectively. Defaults to 0 (0%) of the resolution of the data. Note that the jitter should not be specified in the `point.args` because this information will be passed to two different geoms: one displaying the points and the other displaying the labels for these points.
- `marginal.type` Type of marginal distribution to be plotted on the axes ("histogram", "boxplot", "density", "violin", "densigram").
- `marginal.size` Integer describing the relative size of the marginal plots compared to the main plot. A size of 5 means that the main plot is 5x wider and 5x taller than the marginal plots.
- `xfill` Character describing color fill for x and y axes marginal distributions (default: "#009E73" (for x) and "#D55E00" (for y)). Note that the defaults are colorblind-friendly.
- `yfill` Character describing color fill for x and y axes marginal distributions (default: "#009E73" (for x) and "#D55E00" (for y)). Note that the defaults are colorblind-friendly.
- `type` Type of association between paired samples required ("parametric": Pearson's product moment correlation coefficient" or "nonparametric": Spearman's rho" or "robust": percentage bend correlation coefficient" or "bayes": Bayes Factor for Pearson's r "). Corresponding abbreviations are also accepted: "p" (for parametric/pearson), "np" (nonparametric/spearman), "r" (robust), "bf" (for bayes factor), resp.
- `conf.level` Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
- `bf.prior` A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors.
- `beta` bending constant (Default: 0.1). For more, see `WRS2::pbcor()`.
- `k` Number of digits after decimal point (should be an integer) (Default: `k = 2L`).
- `ggtheme` A function, `ggplot2` theme name. Default value is `ggplot2::theme_bw()`. Any of the `ggplot2` themes, or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.).
- `ggstatsplot.layer` Logical that decides whether `theme_ggstatsplot` theme elements are to be displayed along with the selected `ggtheme` (Default: `TRUE`). `theme_ggstatsplot` is an opinionated theme layer that override some aspects of the selected `ggtheme`.
- `bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: `TRUE`).
- `results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: `TRUE`). If set to `FALSE`, only the plot will be returned.
- `xlab` Labels for x and y axis variables. If `NULL` (default), variable names for x and y will be used.

	ylab	Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
	subtitle	The text for the plot subtitle. Will work only if results.subtitle = FALSE.
	caption	The text for the plot caption.
	ggplot.component	A ggplot component to be added to the plot prepared by ggstatsplot. This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a ggplot2 function or a list of ggplot2 functions.
plotgrid.args		A list of additional arguments to cowplot::plot_grid.
title.text		String or plotmath expression to be drawn as title for the <i>combined plot</i> .
title.args		A list of additional arguments provided to title, caption and sub, resp.
caption.text		String or plotmath expression to be drawn as the caption for the <i>combined plot</i> .
caption.args		A list of additional arguments provided to title, caption and sub, resp.
sub.text		The label with which the <i>combined plot</i> should be annotated. Can be a plotmath expression.
sub.args		A list of additional arguments provided to title, caption and sub, resp.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggscatterstats.html

See Also

[ggscatterstats](#), [ggcorrmat](#), [grouped_ggcorrmat](#)

Examples

```
# to ensure reproducibility
set.seed(123)
library(ggstatsplot)

# basic function call
ggstatsplot::grouped_ggscatterstats(
  data = dplyr::filter(movies_long, genre == "Comedy" | genre == "Drama"),
  x = length,
  y = rating,
  method = "lm",
  formula = y ~ x + I(x^3),
  grouping.var = genre
)

# using labeling
# (also show how to modify basic plot from within function call)
grouped_ggscatterstats(
  data = dplyr::filter(ggplot2::mpg, cyl != 5),
  x = displ,
  y = hwy,
  grouping.var = cyl,
  title.prefix = "Cylinder count",
  type = "robust",
  label.var = manufacturer,
  label.expression = hwy > 25 & displ > 2.5,
```

```

ggplot.component = ggplot2::scale_y_continuous(sec.axis = ggplot2::dup_axis())
)

# labeling without expression

ggstatsplot::grouped_ggscatterstats(
  data = dplyr::filter(
    .data = movies_long,
    rating == 7,
    genre %in% c("Drama", "Comedy")
  ),
  x = budget,
  y = length,
  grouping.var = genre,
  bf.message = FALSE,
  label.var = "title",
  marginal = FALSE,
  title.prefix = "Genre",
  caption.text = "All movies have IMDB rating equal to 7."
)

```

grouped_ggwithinstats *Violin plots for group or condition comparisons in within-subjects designs repeated across all levels of a grouping variable.*

Description

A combined plot of comparison plot created for levels of a grouping variable.

Usage

```

grouped_ggwithinstats(
  data,
  x,
  y,
  grouping.var,
  outlier.label = NULL,
  title.prefix = NULL,
  output = "plot",
  ...,
  plotgrid.args = list(),
  title.text = NULL,
  title.args = list(size = 16, fontface = "bold"),
  caption.text = NULL,
  caption.args = list(size = 10),
  sub.text = NULL,
  sub.args = list(size = 12)
)

```

Arguments

data A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will **not** be accepted.

<code>x</code>	The grouping variable from the dataframe data.
<code>y</code>	The response (a.k.a. outcome or dependent) variable from the dataframe data.
<code>grouping.var</code>	A single grouping variable (can be entered either as a bare name <code>x</code> or as a string " <code>x</code> ").
<code>outlier.label</code>	Label to put on the outliers that have been tagged. This can't be the same as <code>x</code> argument.
<code>title.prefix</code>	Character string specifying the prefix text for the fixed plot title (name of each factor level) (Default: NULL). If NULL, the variable name entered for <code>grouping.var</code> will be used.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
<code>...</code>	Arguments passed on to <code>ggwithinstats</code>
<code>point.path</code>	Logical that decides whether individual data points and means, respectively, should be connected using <code>geom_path</code> . Both default to TRUE. Note that <code>point.path</code> argument is relevant only when there are two groups (i.e., in case of a <i>t</i> -test). In case of large number of data points, it is advisable to set <code>point.path = FALSE</code> as these lines can overwhelm the plot.
<code>centrality.path</code>	Logical that decides whether individual data points and means, respectively, should be connected using <code>geom_path</code> . Both default to TRUE. Note that <code>point.path</code> argument is relevant only when there are two groups (i.e., in case of a <i>t</i> -test). In case of large number of data points, it is advisable to set <code>point.path = FALSE</code> as these lines can overwhelm the plot.
<code>centrality.path.args</code>	A list of additional aesthetic arguments passed on to <code>geom_path</code> connecting raw data points and mean points.
<code>point.path.args</code>	A list of additional aesthetic arguments passed on to <code>geom_path</code> connecting raw data points and mean points.
<code>type</code>	Type of statistic expected ("parametric" or "nonparametric" or "robust" or "bayes"). Corresponding abbreviations are also accepted: "p" (for parametric), "np" (nonparametric), "r" (robust), or "bf" resp.
<code>pairwise.comparisons</code>	Logical that decides whether pairwise comparisons are to be displayed (default: TRUE). Please note that only significant comparisons will be shown by default. To change this behavior, select appropriate option with <code>pairwise.display</code> argument. The pairwise comparison dataframes are prepared using the <code>pairwiseComparisons::pairwise_comparisons</code> function. For more details about pairwise comparisons, see the documentation for that function.
<code>pairwise.display</code>	Decides which pairwise comparisons to display. Available options are "significant" (abbreviation accepted: "s") or "non-significant" (abbreviation accepted: "ns") or "everything"/"all". The default is "significant". You can use this argument to make sure that your plot is not uber-cluttered when you have multiple groups being compared and scores of pairwise comparisons being displayed.
<code>p.adjust.method</code>	Adjustment method for <i>p</i> -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".

- `effsize.type` Type of effect size needed for *parametric* tests. The argument can be "eta" (partial eta-squared) or "omega" (partial omega-squared).
- `bf.prior` A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors.
- `bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).
- `results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
- `xlab` Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
- `ylab` Labels for x and y axis variables. If NULL (default), variable names for x and y will be used.
- `caption` The text for the plot caption.
- `subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.
- `sample.size.label` Logical that decides whether sample size information should be displayed for each level of the grouping variable x (Default: TRUE).
- `k` Number of digits after decimal point (should be an integer) (Default: k = 2L).
- `conf.level` Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
- `nboot` Number of bootstrap samples for computing confidence interval for the effect size (Default: 100).
- `tr` Trim level for the mean when carrying out robust tests. If you get error stating "Standard error cannot be computed because of Winsorized variance of 0 (e.g., due to ties). Try to decrease the trimming level.", try to play around with the value of `tr`, which is by default set to 0.1. Lowering the value might help.
- `centrality.plotting` Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the type argument (**mean** for parametric, **median** for non-parametric, **trimmed mean** for robust, and **MAP estimator** for Bayes).
- `centrality.point.args` A list of additional aesthetic arguments to be passed to `ggplot2::geom_point` and `ggrepel::geom_label_repel` geoms, which are involved in mean plotting.
- `centrality.label.args` A list of additional aesthetic arguments to be passed to `ggplot2::geom_point` and `ggrepel::geom_label_repel` geoms, which are involved in mean plotting.
- `notch` A logical. If FALSE (default), a standard box plot will be displayed. If TRUE, a notched box plot will be used. Notches are used to compare groups; if the notches of two boxes do not overlap, this suggests that the medians are significantly different. In a notched box plot, the notches extend $1.58 * IQR / \sqrt{n}$, where IQR: Inter-Quartile Range. This gives a roughly 95% confidence interval for comparing medians.
- `notchwidth` For a notched box plot, width of the notch relative to the body (default 0.5).
- `outlier.tagging` Decides whether outliers should be tagged (Default: FALSE).

<code>outlier.coef</code>	Coefficient for outlier detection using Tukey's method. With Tukey's method, outliers are below (1st Quartile) or above (3rd Quartile) <code>outlier.coef</code> times the Inter-Quartile Range (IQR) (Default: 1.5).
<code>outlier.label.args</code>	A list of additional aesthetic arguments to be passed to <code>ggrepel::geom_label_repel</code> for outlier label plotting.
<code>violin.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_violin</code> .
<code>ggsignif.args</code>	A list of additional aesthetic arguments to be passed to <code>ggsignif::geom_signif</code> .
<code>ggtheme</code>	A function, ggplot2 theme name. Default value is <code>ggplot2::theme_bw()</code> . Any of the ggplot2 themes, or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> , etc.).
<code>ggstatsplot.layer</code>	Logical that decides whether <code>theme_ggstatsplot</code> theme elements are to be displayed along with the selected <code>ggtheme</code> (Default: TRUE). <code>theme_ggstatsplot</code> is an opinionated theme layer that override some aspects of the selected <code>ggtheme</code> .
<code>package</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d)</code> .
<code>palette</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d)</code> .
<code>ggplot.component</code>	A ggplot component to be added to the plot prepared by <code>ggstatsplot</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is NULL. The argument should be entered as a ggplot2 function or a list of ggplot2 functions.
<code>plotgrid.args</code>	A list of additional arguments to <code>cowplot::plot_grid</code> .
<code>title.text</code>	String or plotmath expression to be drawn as title for the <i>combined plot</i> .
<code>title.args</code>	A list of additional arguments provided to title, caption and sub, resp.
<code>caption.text</code>	String or plotmath expression to be drawn as the caption for the <i>combined plot</i> .
<code>caption.args</code>	A list of additional arguments provided to title, caption and sub, resp.
<code>sub.text</code>	The label with which the <i>combined plot</i> should be annotated. Can be a plotmath expression.
<code>sub.args</code>	A list of additional arguments provided to title, caption and sub, resp.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggwithinstats.html

See Also

[ggwithinstats](#), [ggbetweenstats](#), [grouped_ggbetweenstats](#)

Examples

```
# to get reproducible results from bootstrapping
set.seed(123)
library(ggstatsplot)

# the most basic function call
ggstatsplot::grouped_ggwithinstats(
  data = VR_dilemma,
```

```
x = modality,  
y = score,  
grouping.var = order,  
ggplot.component = ggplot2::scale_y_continuous(  
  breaks = seq(0, 1, 0.1),  
  limits = c(0, 1)  
)  
)
```

iris_long

Edgar Anderson's Iris Data in long format.

Description

Edgar Anderson's Iris Data in long format.

Usage

```
iris_long
```

Format

A data frame with 600 rows and 5 variables

- id. Dummy identity number for each flower (150 flowers in total).
- Species. The species are *Iris setosa*, *versicolor*, and *virginica*.
- condition. Factor giving a detailed description of the attribute (Four levels: "Petal.Length", "Petal.Width", "Sepal.Length", "Sepal.Width").
- attribute. What attribute is being measured ("Sepal" or "Petal").
- measure. What aspect of the attribute is being measured ("Length" or "Width").
- value. Value of the measurement.

Details

This famous (Fisher's or Anderson's) iris data set gives the measurements in centimeters of the variables sepal length and width and petal length and width, respectively, for 50 flowers from each of 3 species of iris. The species are *Iris setosa*, *versicolor*, and *virginica*.

This is a modified dataset from `datasets` package.

Examples

```
dim(iris_long)  
head(iris_long)  
dplyr::glimpse(iris_long)
```

`movies_long`*Movie information and user ratings from IMDB.com (long format).*

Description

Movie information and user ratings from IMDB.com (long format).

Usage

```
movies_long
```

Format

A data frame with 1,579 rows and 8 variables

- title. Title of the movie.
- year. Year of release.
- budget. Total budget (if known) in US dollars
- length. Length in minutes.
- rating. Average IMDB user rating.
- votes. Number of IMDB users who rated this movie.
- mpaa. MPAA rating.
- genre. Different genres of movies (action, animation, comedy, drama, documentary, romance, short).

Details

Modified dataset from `ggplot2movies` package.

The internet movie database, <https://imdb.com/>, is a website devoted to collecting movie data supplied by studios and fans. It claims to be the biggest movie database on the web and is run by amazon.

Movies were are identical to those selected for inclusion in `movies_wide` but this dataset has been constructed such that every movie appears in one and only one genre category.

Source

<https://CRAN.R-project.org/package=ggplot2movies>

Examples

```
dim(movies_long)
head(movies_long)
dplyr::glimpse(movies_long)
```

`movies_wide`*Movie information and user ratings from IMDB.com (wide format).*

Description

Movie information and user ratings from IMDB.com (wide format).

Usage

```
movies_wide
```

Format

A data frame with 1,579 rows and 13 variables

- `title`. Title of the movie.
- `year`. Year of release.
- `budget`. Total budget in millions of US dollars
- `length`. Length in minutes.
- `rating`. Average IMDB user rating.
- `votes`. Number of IMDB users who rated this movie.
- `mpaa`. MPAA rating.
- `action`, `animation`, `comedy`, `drama`, `documentary`, `romance`, `short`. Binary variables representing if movie was classified as belonging to that genre.
- `NumGenre`. The number of different genres a film was classified in an integer between one and four

Details

Modified dataset from `ggplot2movies` package.

The internet movie database, <https://imdb.com/>, is a website devoted to collecting movie data supplied by studios and fans. It claims to be the biggest movie database on the web and is run by amazon.

Movies were selected for inclusion if they had a known length and had been rated by at least one imdb user. Small categories such as documentaries and NC-17 movies were removed.

Source

<https://CRAN.R-project.org/package=ggplot2movies>

Examples

```
dim(movies_wide)
head(movies_wide)
dplyr::glimpse(movies_wide)
```

theme_ggstatsplot	<i>Default theme used in all ggstatsplot package plots</i>
-------------------	--

Description

Common theme used across all plots generated in ggstatsplot and *assumed* by the author to be aesthetically pleasing to the user/reader.

Usage

```
theme_ggstatsplot(ggtheme = ggplot2::theme_bw(), ggstatsplot.layer = TRUE)
```

```
theme_corrmat()
```

```
theme_pie(ggtheme = ggplot2::theme_bw(), ggstatsplot.layer = TRUE)
```

Arguments

`ggtheme` A function, ggplot2 theme name. Default value is `ggplot2::theme_bw()`. Any of the ggplot2 themes, or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.).

`ggstatsplot.layer` Logical that decides whether `theme_ggstatsplot` theme elements are to be displayed along with the selected `ggtheme` (Default: TRUE). `theme_ggstatsplot` is an opinionated theme layer that override some aspects of the selected `ggtheme`.

Value

A ggplot2 object with the `theme_ggstatsplot` theme overlaid.

References

https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/theme_ggstatsplot.html

Titanic_full	<i>Titanic dataset.</i>
--------------	-------------------------

Description

Titanic dataset.

Usage

```
Titanic_full
```

Format

A data frame with 2201 rows and 5 variables

- id. Dummy identity number for each person.
- Class. 1st, 2nd, 3rd, Crew.
- Sex. Male, Female.
- Age. Child, Adult.
- Survived. No, Yes.

Details

This data set provides information on the fate of passengers on the fatal maiden voyage of the ocean liner 'Titanic', summarized according to economic status (class), sex, age and survival.

This is a modified dataset from datasets package.

Examples

```
dim(Titanic_full)
head(Titanic_full)
dplyr::glimpse(Titanic_full)
```

VR_dilemma

Virtual reality moral dilemmas.

Description

Virtual reality moral dilemmas.

Usage

VR_dilemma

Format

A data frame with 68 rows and 4 variables

- id. Dummy identity number for each participant.
- order. The order in which the participants completed the two sessions: "text_first" (0) or "text_second" (1).
- modality. Describes how the moral dilemmas were presented to the participants: either in text format ("text") or in Virtual Reality ("vr").
- score. Proportion of "utilitarian" decisions. In other words, of the 4 decisions, how many affirmative were responses. Range: 0 (all utilitarian) - 1 (none utilitarian).

Details

Dataset from a study where participants completed identical moral dilemmas in two different sessions held on separate days: in one session, they read text description of the scenario, while in another session they completed the same scenarios in Virtual Reality (videos: <https://www.youtube.com/watch?v=ebdU3HhhYs8>). The study investigated if there was a discrepancy between how people judged the same scenarios while reading them in text versus experiencing them in virtual reality.

Source

<https://psyarxiv.com/ry3ap/>

Examples

```
dim(VR_dilemma)
head(VR_dilemma)
dplyr::glimpse(VR_dilemma)
```

Index

- * **datasets**
 - bugs_long, 4
 - bugs_wide, 5
 - iris_long, 68
 - movies_long, 69
 - movies_wide, 70
 - Titanic_full, 71
 - VR_dilemma, 72
- _PACKAGE (ggstatsplot-package), 3
- align_plots(), 7
- bugs_long, 4
- bugs_wide, 5
- combine_plots, 6
- combine_plots2, 3, 9
- cowplot::plot_grid, 6
- ggbarstats, 3, 11, 34, 43, 44, 60
- ggbetweenstats, 3, 14, 41, 46, 48, 67
- ggcoefstats, 3, 18
- ggcorrmat, 3, 22, 37, 50, 51, 63
- ggdotplotstats, 3, 25, 31, 53, 54, 57
- gghistostats, 3, 28, 28, 54, 55, 57
- ggpiestats, 3, 13, 31, 44, 59, 60
- ggscatterstats, 3, 25, 34, 51, 61, 63
- ggstatsplot (ggstatsplot-package), 3
- ggstatsplot-package, 3
- ggwithinstats, 3, 17, 37, 48, 65, 67
- grouped_ggbarstats, 13, 34, 42, 60
- grouped_ggbetweenstats, 17, 41, 45, 67
- grouped_ggcorrmat, 25, 37, 49, 63
- grouped_ggdotplotstats, 28, 31, 52, 57
- grouped_gghistostats, 28, 31, 54, 55
- grouped_ggpiestats, 13, 34, 44, 58
- grouped_ggscatterstats, 25, 37, 51, 60
- grouped_ggwithinstats, 17, 41, 48, 64
- iris_long, 68
- movies_long, 69
- movies_wide, 70
- plot_grid, 6
- theme_corrmat (theme_ggstatsplot), 71
- theme_ggstatsplot, 71
- theme_pie (theme_ggstatsplot), 71
- Titanic_full, 71
- VR_dilemma, 72
- WRS2::pbcor(), 24, 35, 50, 62