

Quick start for the sommer package

Giovanny Covarrubias-Pazaran

2017-10-28

The sommer package was developed to provide R users a powerful and reliable multivariate mixed model solver. The package is focused in problems of the type $p > n$ (more random effect levels than observations). This package allows the user to fit mixed models with the advantage of specifying the variance-covariance structure for the random effects, and specify heterogeneous variances, and obtain other parameters such as BLUPs, BLUEs, residuals, fitted values, variances for fixed and random effects, etc.

The purpose of this quick start guide is to show the flexibility of the package under certain common scenarios:

- 1) Univariate homogeneous variance models
- 2) Univariate heterogeneous variance models
- 3) Univariate unstructured variance models
- 4) Multivariate homogeneous variance models
- 5) Multivariate heterogeneous variance models

Background

The core of the package are the `mmer2` (formula-based) and `mmer` (matrix-based) functions which solve the mixed model equations. The functions are an interface to call the NR Direct-Inversion Newton-Raphson (Tunnicliffe 1989; Gilmour et al. 1995; Lee et al. 2016) or the EMMA efficient mixed model association algorithm (Kang et al. 2008). Since version 2.0 sommer can handle multivariate models. Following Maier et al. (2015), the multivariate (and by extension the univariate) mixed model implemented has the form:

$$y_1 = X_1\beta_1 + Z_1u_1 + \epsilon_1 \quad y_2 = X_2\beta_2 + Z_2u_2 + \epsilon_2 \quad \dots \quad y_t = X_t\beta_t + Z_tu_t + \epsilon_t$$

where y_i is a vector of trait phenotypes, β_i is a vector of fixed effects, u_i is a vector of random effects for individuals and ϵ_i are residuals for trait ‘i’ ($i = 1, \dots, t$). The random effects ($u_1 \dots u_t$ and ϵ_i) are assumed to be normally distributed with mean zero. X and Z are incidence matrices for fixed and random effects respectively. The distribution of the multivariate response and the phenotypic variance covariance (V) are:

$$Y = X\beta + ZU + \epsilon$$

$$Y \sim MVN(X\beta, V)$$

$$\mathbf{Y} = \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_t \end{bmatrix}$$

$$\mathbf{X} = \begin{bmatrix} X_1 & \dots & \dots \\ \dots & \dots & \dots \\ \dots & \dots & X_t \end{bmatrix}$$

$$\mathbf{V} = \begin{bmatrix} Z_1 K \sigma_{g_1}^2 Z'_1 + Z_1 I \sigma_{\epsilon_1}^2 Z'_1 & \dots & Z_1 K \sigma_{g_{1,t}} Z'_t + Z_1 I \sigma_{\epsilon_{1,t}} Z'_t \\ \dots & \dots & \dots \\ Z_t K \sigma_{g_{1,t}}^2 Z'_t + Z_t I \sigma_{\epsilon_{1,t}}^2 Z'_t & \dots & Z_t K \sigma_{g_t}^2 Z'_t + Z_t I \sigma_{\epsilon_t}^2 Z'_t \end{bmatrix}$$

where K is the relationship or covariance matrix for the k th random effect ($u=1, \dots, k$), and $R=I$ is an identity matrix for the residual term. The terms $\sigma_{g_i}^2$ and $\sigma_{\epsilon_i}^2$ denote the genetic (or any of the k th random terms) and residual variance of trait ‘i’, respectively and $\sigma_{g_{ij}}$ and $\sigma_{\epsilon_{ij}}$ the genetic (or any of the k th random terms) and

residual covariance between traits ‘i’ and ‘j’ ($i=1,\dots,t$, and $j=1,\dots,t$). The algorithm implemented optimizes the log likelihood:

$$\log L = 1/2 * \ln(|V|) + \ln(X'V|X) + Y'PY$$

where $||$ is the determinant of a matrix. And the REML estimates are updated using a Newton optimization algorithm of the form:

$$\theta^{k+1} = \theta^k + (H^k)^{-1} * \frac{dL}{d\sigma_i^2} | \theta^k$$

Where, θ is the vector of variance components for random effects and covariance components among traits, H^{-1} is the inverse of the Hessian matrix of second derivatives for the kth cycle, $\frac{dL}{d\sigma_i^2}$ is the vector of first derivatives of the likelihood with respect to the variance-covariance components. The Eigen decomposition of the relationship matrix proposed by Lee and Van Der Werf (2016) was included in the Newton-Raphson algorithm to improve time efficiency. Additionally, the popular pin function to estimate standard errors for linear combinations of variance components (i.e. heritabilities and genetic correlations) was added to the package as well.

The function `mmer` takes the Zs and Ks for each random effect and construct the neccesary structure inside and estimates the variance components by ML/REML using any of the 4 methods available in sommer. The `mmer2` function is enabled to work in a model-based fashion so user don’t have to build the Z’s and K matrices. Please refer to the canonical papers listed in the Literature section to check how the algorithms work. We have tested widely the methods to make sure they provide the same solution when the likelihood behaves well but for complex problems they might lead to slightly different answers. If you have any concern please contact me at cova_ruber@live.com.mx.

In the following section we will go in detail over several examples on how to use mixed models in univariate and multivariate case and their use in quantitative genetics.

1) Univariate homogeneous variance models

This type of models refer to single response models where a variable of interest (i.e. genotypes) needs to be analized as interacting with a 2nd random effect (i.e. environments), but you assume that across environments the genotypes have the same variance component. This is the so-called compound simmetry (CS) model.

```
library(sommer)
data(example)
head(example)

##           Name   Env Loc Year    Block Yield    Weight
## 33 Manistee(MSL292-A) CA.2013 CA.2013 CA.2013.1     4 -1.904711
## 65          C002024-9W CA.2013 CA.2013 CA.2013.1     5 -1.446958
## 66 Manistee(MSL292-A) CA.2013 CA.2013 CA.2013.2     5 -1.516271
## 67          MSL007-B CA.2011 CA.2011 CA.2011.2     5 -1.435510
## 68          MSR169-8Y CA.2013 CA.2013 CA.2013.1     5 -1.469051
## 103         AC05153-1W CA.2013 CA.2013 CA.2013.1     6 -1.307167

ans1 <- mmer2(Yield~Env,
                 random= ~ Name + Env:Name,
                 rcov= ~ units,
                 data=example, silent = TRUE)
summary(ans1)

## =====
##      Multivariate Linear Mixed Model fit by REML
## ***** sommer 3.0 *****
## =====
```

```

##          logLik      AIC      BIC Method Converge
## Value -20.14537 46.29075 55.95182     MNR     TRUE
## =====
## Variance-Covariance components:
##           VarComp VarCompSE Zratio
## Name.Yield-Yield    3.682     1.691  2.177
## Env:Name.Yield-Yield 5.173     1.495  3.459
## units.Yield-Yield   4.366     0.647  6.749
## =====
## Fixed effects:
##
## $Yield
##           Estimate Std. Error t value
## (Intercept) 16.496351  0.6855001 24.064695
## EnvCA.2012 -5.776759  0.7558178 -7.643057
## EnvCA.2013 -6.380479  0.7960514 -8.015159
##
## =====
## Groups and observations:
##           Observ Groups
## Name       185     41
## Env:Name   185    123
## =====
## Use the '$' sign to access results and parameters

```

2) Univariate heterogeneous variance models

Very often in multi-environment trials, the assumption that the genetic variance or the residual variance is the same across locations may be too naive. Because of that, specifying a general genetic component and a location specific genetic variance is the way to go. This require a CS+DIAG model.

```

data(example)
head(example)

##           Name Env Loc Year Block Yield Weight
## 33 Manistee(MSL292-A) CA.2013 CA 2013 CA.2013.1 4 -1.904711
## 65 C002024-9W CA.2013 CA 2013 CA.2013.1 5 -1.446958
## 66 Manistee(MSL292-A) CA.2013 CA 2013 CA.2013.2 5 -1.516271
## 67 MSL007-B CA.2011 CA 2011 CA.2011.2 5 -1.435510
## 68 MSR169-8Y CA.2013 CA 2013 CA.2013.1 5 -1.469051
## 103 AC05153-1W CA.2013 CA 2013 CA.2013.1 6 -1.307167

ans1 <- mmer2(Yield~Env,
               random= ~Name + at(Env):Name,
               rcov= ~ at(Env):units,
               data=example, silent = TRUE)
summary(ans1)

## =====
##      Multivariate Linear Mixed Model fit by REML
## ***** sommer 3.0 *****
## =====
##          logLik      AIC      BIC Method Converge
## Value -15.42982 36.85964 46.52071     MNR     TRUE
## =====

```

```

## Variance-Covariance components:
##                               VarComp VarCompSE Zratio
## Name.Yield-Yield          2.962   1.4963  1.980
## CA.2011:Name.Yield-Yield 10.148   4.5108  2.250
## CA.2012:Name.Yield-Yield  1.879   1.8699  1.005
## CA.2013:Name.Yield-Yield  6.629   2.5027  2.649
## CA.2013:units.Yield-Yield 2.560   0.6398  4.001
## CA.2011:units.Yield-Yield 4.943   1.5246  3.242
## CA.2012:units.Yield-Yield 5.725   1.3119  4.364
## =====
## Fixed effects:
##
## $Yield
##           Estimate Std. Error t value
## (Intercept) 16.507678  0.8268665 19.964138
## EnvCA.2012 -5.816890  0.8575814 -6.782902
## EnvCA.2013 -6.412433  0.9356490 -6.853460
##
## =====
## Groups and observations:
##           Observ Groups
## Name        185    41
## CA.2011:Name 185    41
## CA.2012:Name 185    41
## CA.2013:Name 185    41
## =====
## Use the '$' sign to access results and parameters

```

As you can see the special function `at` or `diag` can be used to indicate that there's a different variance for the genotypes in each environment. Same was done for the residual. The difference between `at` and `diag` is that the `at` function can be used to specify the levels or specific environments where the variance is different.

3) Unstructured variance models

A more relaxed assumption than the CS+DIAG model is the unstructured model (US) which assumes that among the levels of certain factor (i.e. Environments) there's a covariance structure of a second random effect (i.e. Genotypes). This can be done in sommer using the `us(.)` function:

```

data(example)
head(example)

##           Name Env Loc Year     Block Yield   Weight
## 33 Manistee(MSL292-A) CA.2013 CA.2013 CA.2013.1      4 -1.904711
## 65             C002024-9W CA.2013 CA.2013 CA.2013.1      5 -1.446958
## 66 Manistee(MSL292-A) CA.2013 CA.2013 CA.2013.2      5 -1.516271
## 67             MSL007-B CA.2011 CA.2011 CA.2011.2      5 -1.435510
## 68             MSR169-8Y CA.2013 CA.2013 CA.2013.1      5 -1.469051
## 103            AC05153-1W CA.2013 CA.2013 CA.2013.1      6 -1.307167

ans3 <- mmerr2(Yield~Env,
                 random=~ us(Env):Name,
                 rcov=~ at(Env):units,
                 data=example, silent=TRUE)
summary(ans3)

```

```

## =====
## Multivariate Linear Mixed Model fit by REML
## ***** sommer 3.0 *****
## =====
##      logLik      AIC      BIC Method Converge
## Value -11.4997 28.99939 38.66046    MNR     TRUE
## =====
## Variance-Covariance components:
##                                         VarComp VarCompSE Zratio
## Env:Name!Env.CA.2011:CA.2011.Yield-Yield 15.6650   5.4206 2.8899
## Env:Name!Env.CA.2012:CA.2011.Yield-Yield  6.1109   2.4858 2.4583
## Env:Name!Env.CA.2013:CA.2011.Yield-Yield  6.3841   3.0659 2.0823
## Env:Name!Env.CA.2012:CA.2012.Yield-Yield  4.5309   1.8217 2.4872
## Env:Name!Env.CA.2013:CA.2012.Yield-Yield  0.3916   1.5244 0.2569
## Env:Name!Env.CA.2013:CA.2013.Yield-Yield  8.5978   2.4844 3.4607
## CA.2013:units.Yield-Yield                2.5570   0.6391 4.0008
## CA.2011:units.Yield-Yield                4.9699   1.5323 3.2434
## CA.2012:units.Yield-Yield                5.6723   1.3001 4.3631
## =====
## Fixed effects:
##
## $Yield
##             Estimate Std. Error t value
## (Intercept) 16.331260  0.8137093 20.070141
## EnvCA.2012 -5.695867  0.7403739 -7.693229
## EnvCA.2013 -6.271133  0.8191001 -7.656125
##
## =====
## Groups and observations:
##             Observ Groups
## Env:Name!Env.CA.2011:CA.2011    185    41
## Env:Name!Env.CA.2012:CA.2011    185    82
## Env:Name!Env.CA.2013:CA.2011    185    82
## Env:Name!Env.CA.2012:CA.2012    185    41
## Env:Name!Env.CA.2013:CA.2012    185    82
## Env:Name!Env.CA.2013:CA.2013    185    41
## =====
## Use the '$' sign to access results and parameters

```

As can be seen the `us(Env)` indicates that the genotypes (Name) can have a covariance structure among environments (Env).

4) Multivariate homogeneous variance models

Currently there's a great push for multi-response models. This is motivated by the correlation that certain variables hide and that could benefit in the prediction perspective. In sommer to specify multivariate models the response requires the use of the `cbind()` function in the response, and the `us(trait)`, `diag(trait)`, or `at(trait)` functions in the random part of the model.

```

data(example)
head(example)

```

```

##           Name Env Loc Year     Block Yield   Weight
## 33 Manistee(MSL292-A) CA.2013 CA.2013 CA.2013.1    4 -1.904711

```

```

## 65          C002024-9W CA.2013  CA 2013 CA.2013.1      5 -1.446958
## 66  Manistee(MSL292-A) CA.2013  CA 2013 CA.2013.2      5 -1.516271
## 67          MSL007-B CA.2011  CA 2011 CA.2011.2      5 -1.435510
## 68          MSR169-8Y CA.2013  CA 2013 CA.2013.1      5 -1.469051
## 103         AC05153-1W CA.2013  CA 2013 CA.2013.1      6 -1.307167

ans1 <- mmmer2(cbind(Yield, Weight) ~ Env,
               random= ~ us(trait):Name + us(trait):Env:Name,
               rcov= ~ us(trait):units,
               data=example, silent = TRUE)
summary(ans1)

## =====
## Multivariate Linear Mixed Model fit by REML
## **** sommer 3.0 ****
## =====
##      logLik      AIC      BIC Method Converge
## Value 167.0252 -322.0505 -298.5695    MNR     TRUE
## =====
## Variance-Covariance components:
##                               VarComp VarCompSE Zratio
## Name.Yield-Yield      3.7091  1.68159  2.206
## Name.Yield-Weight      0.9071  0.37954  2.390
## Name.Weight-Weight     0.2244  0.08777  2.556
## Env:Name.Yield-Yield   5.0922  1.47905  3.443
## Env:Name.Yield-Weight   1.0269  0.30773  3.337
## Env:Name.Weight-Weight   0.2101  0.06663  3.153
## units.Yield-Yield      4.3838  0.64953  6.749
## units.Yield-Weight      0.9078  0.14148  6.416
## units.Weight-Weight     0.2280  0.03378  6.750
## =====
## Fixed effects:
##
## $Yield
##           Estimate Std. Error t value
## (Intercept) 14.741985  0.6783206 21.733063
## EnvCA.2012 -3.199172  0.7474097 -4.280347
## EnvCA.2013 -4.003349  0.7850509 -5.099477
##
## $Weight
##           Estimate Std. Error t value
## (Intercept) 0.5847374  0.1497090 3.905826
## EnvCA.2012 -0.9711517  0.1592564 -6.098038
## EnvCA.2013 -1.1643244  0.1681079 -6.926052
##
## =====
## Groups and observations:
##       Observ Groups
## Name      185     41
## Env:Name  185    123
## =====
## Use the '$' sign to access results and parameters

```

You may notice that we have added the `us(trait)` behind the random effects. This is to indicate the structure that should be assumed in the multivariate model. The `diag(trait)` used behind a random effect

(i.e. Name) indicates that for the traits modeled (Yield and Weight) there's no a covariance component and should not be estimated, whereas `us(trait)` assumes that for such random effect, there's a covariance component to be estimated (i.e. covariance between Yield and Weight for the random effect Name). Same applies for the residual part (rcov).

5) Multivariate heterogeneous variance models

This is just an extension of the univariate heterogeneous variance models but at the multivariate level. This would be a CS+DIAG multivariate model:

```

data(example)
head(example)

##           Name Env Loc Year   Block Yield    Weight
## 33 Manistee(MSL292-A) CA.2013 CA 2013 CA.2013.1     4 -1.904711
## 65             C002024-9W CA.2013 CA 2013 CA.2013.1     5 -1.446958
## 66 Manistee(MSL292-A) CA.2013 CA 2013 CA.2013.2     5 -1.516271
## 67             MSL007-B CA.2011 CA 2011 CA.2011.2     5 -1.435510
## 68             MSR169-8Y CA.2013 CA 2013 CA.2013.1     5 -1.469051
## 103            AC05153-1W CA.2013 CA 2013 CA.2013.1     6 -1.307167

ans1 <- mmer2(cbind(Yield, Weight) ~ Env,
              random= ~ us(trait):Name + us(trait):at(Env):Name,
              rcov= ~ us(trait):at(Env):units,
              data=example, silent = TRUE)
summary(ans1)

## =====
## Multivariate Linear Mixed Model fit by REML
## **** sommer 3.0 ****
## =====
##      logLik      AIC      BIC Method Converge
## Value 177.8154 -343.6309 -320.1498     MNR      TRUE
## =====
## Variance-Covariance components:
##                               VarComp VarCompSE Zratio
## Name.Yield-Yield          3.32291  1.45386 2.2856
## Name.Yield-Weight          0.79475  0.32648 2.4343
## Name.Weight-Weight         0.19103  0.07509 2.5442
## CA.2011:Name.Yield-Yield  8.69943  4.00992 2.1695
## CA.2011:Name.Yield-Weight 1.77753  0.83835 2.1203
## CA.2011:Name.Weight-Weight 0.35939  0.17885 2.0094
## CA.2012:Name.Yield-Yield  2.57327  1.95113 1.3189
## CA.2012:Name.Yield-Weight 0.33267  0.39866 0.8345
## CA.2012:Name.Weight-Weight 0.03842  0.08600 0.4467
## CA.2013:Name.Yield-Yield  5.46657  2.16184 2.5287
## CA.2013:Name.Yield-Weight 1.34662  0.50455 2.6689
## CA.2013:Name.Weight-Weight 0.32893  0.12203 2.6954
## CA.2013:units.Yield-Yield 2.56131  0.63996 4.0023
## CA.2013:units.Yield-Weight 0.44569  0.12645 3.5246
## CA.2013:units.Weight-Weight 0.12232  0.03057 4.0009
## CA.2011:units.Yield-Yield  4.93845  1.52314 3.2423
## CA.2011:units.Yield-Weight 0.99446  0.32150 3.0932
## CA.2011:units.Weight-Weight 0.23982  0.07394 3.2433
## CA.2012:units.Yield-Yield  5.73841  1.31504 4.3637

```

```

## CA.2012:units.Yield-Weight  1.27999  0.30150 4.2454
## CA.2012:units.Weight-Weight 0.31804  0.07285 4.3657
## =====
## Fixed effects:
##
## $Yield
##           Estimate Std. Error   t value
## (Intercept) 14.498157  0.7889029 18.377621
## EnvCA.2012 -3.009537  0.8264035 -3.641728
## EnvCA.2013 -3.731629  0.8754507 -4.262524
##
## $Weight
##           Estimate Std. Error   t value
## (Intercept) 0.5746062  0.1682642  3.414905
## EnvCA.2012 -0.9334404  0.1697663 -5.498384
## EnvCA.2013 -1.1375574  0.1914161 -5.942851
##
## =====
## Groups and observations:
##           Observ Groups
## Name        185    41
## CA.2011:Name 185    41
## CA.2012:Name 185    41
## CA.2013:Name 185    41
## =====
## Use the '$' sign to access results and parameters

```

Any number of random effects can be specified with different structures.

6) Including special functions

Several random effects require the use of covariance structures that specify a special relationship among the levels of such random effect. The sommer package includes the `g()` function to include such known covariance structures:

```

data(example)
head(example)

##           Name Env Loc Year     Block Yield   Weight
## 33 Manistee(MSL292-A) CA.2013 CA 2013 CA.2013.1      4 -1.904711
## 65          C002024-9W CA.2013 CA 2013 CA.2013.1      5 -1.446958
## 66 Manistee(MSL292-A) CA.2013 CA 2013 CA.2013.2      5 -1.516271
## 67          MSL007-B CA.2011 CA 2011 CA.2011.2      5 -1.435510
## 68          MSR169-8Y CA.2013 CA 2013 CA.2013.1      5 -1.469051
## 103         AC05153-1W CA.2013 CA 2013 CA.2013.1      6 -1.307167

K[1:4,1:4]

##           Manistee(MSL292-A) C002024-9W MSL007-B MSR169-8Y
## Manistee(MSL292-A)                 1       0       0       0
## C002024-9W                   0       1       0       0
## MSL007-B                     0       0       1       0
## MSR169-8Y                     0       0       0       1

ans1 <- mmmer2(Yield ~ Env,
  random= ~ g(Name) + at(Env):g(Name),

```

```

    rcov= ~ at(Env):units,
    G=list(Name=K),
    data=example, silent = TRUE)
summary(ans1)

## =====
## Multivariate Linear Mixed Model fit by REML
## ***** sommer 3.0 *****
## =====
##      logLik      AIC      BIC Method Converge
## Value -15.42982 36.85964 46.52071     MNR      TRUE
## =====
## Variance-Covariance components:
##                               VarComp VarCompSE Zratio
## g(Name).Yield-Yield        2.962   1.4963  1.980
## CA.2011:g(Name).Yield-Yield 10.148   4.5108  2.250
## CA.2012:g(Name).Yield-Yield  1.879   1.8699  1.005
## CA.2013:g(Name).Yield-Yield  6.629   2.5027  2.649
## CA.2013:units.Yield-Yield   2.560   0.6398  4.001
## CA.2011:units.Yield-Yield    4.943   1.5246  3.242
## CA.2012:units.Yield-Yield    5.725   1.3119  4.364
## =====
## Fixed effects:
##
## $Yield
##           Estimate Std. Error t value
## (Intercept) 16.507678  0.8268665 19.964138
## EnvCA.2012 -5.816890  0.8575814 -6.782902
## EnvCA.2013 -6.412433  0.9356490 -6.853460
##
## =====
## Groups and observations:
##          Observ Groups
## g(Name)       185    41
## CA.2011:g(Name) 185    41
## CA.2012:g(Name) 185    41
## CA.2013:g(Name) 185    41
## =====
## Use the '$' sign to access results and parameters

```

and for multivariate models:

```

data(example)
head(example)

##          Name Env Loc Year Block Yield Weight
## 33 Manistee(MSL292-A) CA.2013 CA 2013 CA.2013.1    4 -1.904711
## 65             C002024-9W CA.2013 CA 2013 CA.2013.1    5 -1.446958
## 66 Manistee(MSL292-A) CA.2013 CA 2013 CA.2013.2    5 -1.516271
## 67             MSL007-B CA.2011 CA 2011 CA.2011.2    5 -1.435510
## 68             MSR169-8Y CA.2013 CA 2013 CA.2013.1    5 -1.469051
## 103            AC05153-1W CA.2013 CA 2013 CA.2013.1    6 -1.307167
K[1:4,1:4]

##          Manistee(MSL292-A) C002024-9W MSL007-B MSR169-8Y

```

```

## Manistee(MSL292-A)           1       0       0       0
## C002024-9W                   0       1       0       0
## MSL007-B                      0       0       1       0
## MSR169-8Y                     0       0       0       1

ans1 <- mmmer2(cbind(Yield, Weight) ~ Env,
                 random= ~ us(trait):g(Name) + us(trait):at(Env):g(Name),
                 rcov= ~ us(trait):at(Env):units,
                 G=list(Name=K),
                 data=example, silent = TRUE)
summary(ans1)

## =====
## Multivariate Linear Mixed Model fit by REML
## ***** sommer 3.0 *****
## =====
##      logLik      AIC      BIC Method Converge
## Value 177.8154 -343.6309 -320.1498    MNR     TRUE
## =====
## Variance-Covariance components:
##                               VarComp VarCompSE Zratio
## g(Name).Yield-Yield      3.32291  1.45386 2.2856
## g(Name).Yield-Weight     0.79475  0.32648 2.4343
## g(Name).Weight-Weight   0.19103  0.07509 2.5442
## CA.2011:g(Name).Yield-Yield 8.69943  4.00992 2.1695
## CA.2011:g(Name).Yield-Weight 1.77753  0.83835 2.1203
## CA.2011:g(Name).Weight-Weight 0.35939  0.17885 2.0094
## CA.2012:g(Name).Yield-Yield 2.57327  1.95113 1.3189
## CA.2012:g(Name).Yield-Weight 0.33267  0.39866 0.8345
## CA.2012:g(Name).Weight-Weight 0.03842  0.08600 0.4467
## CA.2013:g(Name).Yield-Yield 5.46657  2.16184 2.5287
## CA.2013:g(Name).Yield-Weight 1.34662  0.50455 2.6689
## CA.2013:g(Name).Weight-Weight 0.32893  0.12203 2.6954
## CA.2013:units.Yield-Yield  2.56131  0.63996 4.0023
## CA.2013:units.Yield-Weight  0.44569  0.12645 3.5246
## CA.2013:units.Weight-Weight 0.12232  0.03057 4.0009
## CA.2011:units.Yield-Yield  4.93845  1.52314 3.2423
## CA.2011:units.Yield-Weight  0.99446  0.32150 3.0932
## CA.2011:units.Weight-Weight 0.23982  0.07394 3.2433
## CA.2012:units.Yield-Yield  5.73841  1.31504 4.3637
## CA.2012:units.Yield-Weight  1.27999  0.30150 4.2454
## CA.2012:units.Weight-Weight 0.31804  0.07285 4.3657
## =====
## Fixed effects:
## 
## $Yield
##             Estimate Std. Error t value
## (Intercept) 14.498157  0.7889029 18.377621
## EnvCA.2012 -3.009537  0.8264035 -3.641728
## EnvCA.2013 -3.731629  0.8754507 -4.262524
## 
## $Weight
##             Estimate Std. Error t value
## (Intercept) 0.5746062  0.1682642 3.414905
## EnvCA.2012 -0.9334404  0.1697663 -5.498384

```

```

## EnvCA.2013 -1.1375574 0.1914161 -5.942851
##
## =====
## Groups and observations:
##          Observ Groups
## g(Name)      185    41
## CA.2011:g(Name) 185    41
## CA.2012:g(Name) 185    41
## CA.2013:g(Name) 185    41
## =====
## Use the '$' sign to access results and parameters

```

Notice that the `g()` function is applied at the random effect called “Name”, and the covariance structure is provided in the argument “G”. In the example, we used a diagonal covariance structure for demonstration purposes but any dense covariance matrix can be used.

Other special functions such as `and()` for overlay models, `eig()` for an eigen decomposition of the covariance matrix, `grp()` for customized random effects providing an incidence matrix, are available. Take a look a the help page for each of these special functions.

Keep in mind that sommer uses direct inversion (DI) algorithm which can be very slow for large datasets. The package is focused in problems of the type $p > n$ (more random effect levels than observations) and models with dense covariance structures. For example, for experiment with dense covariance structures with low-replication (i.e. 2000 records from 1000 individuals replicated twice with a covariance structure of 1000x1000) sommer will be faster than MME-based software. Also for genomic problems with large number of random effect levels, i.e. 300 individuals (n) with 100,000 genetic markers (p). For highly replicated trials with small covariance structures or $n > p$ (i.e. 2000 records from 200 individuals replicated 10 times with covariance structure of 200x200) asreml or other MME-based algorithms will be much faster and we recommend you to opt for those software.

Literature

Covarrubias-Pazaran G. 2016. Genome assisted prediction of quantitative traits using the R package sommer. PLoS ONE 11(6):1-15.

Bernardo Rex. 2010. Breeding for quantitative traits in plants. Second edition. Stemma Press. 390 pp.

Gilmour et al. 1995. Average Information REML: An efficient algorithm for variance parameter estimation in linear mixed models. Biometrics 51(4):1440-1450.

Henderson C.R. 1975. Best Linear Unbiased Estimation and Prediction under a Selection Model. Biometrics vol. 31(2):423-447.

Kang et al. 2008. Efficient control of population structure in model organism association mapping. Genetics 178:1709-1723.

Lee et al. 2015. MTG2: An efficient algorithm for multivariate linear mixed model analysis based on genomic information. Cold Spring Harbor. doi: <http://dx.doi.org/10.1101/027201>.

Searle. 1993. Applying the EM algorithm to calculating ML and REML estimates of variance components. Paper invited for the 1993 American Statistical Association Meeting, San Francisco.

Yu et al. 2006. A unified mixed-model method for association mapping that accounts for multiple levels of relatedness. Genetics 38:203-208.

Abdollahi Arpanahi R, Morota G, Valente BD, Kranis A, Rosa GJM, Gianola D. 2015. Assessment of bagging GBLUP for whole genome prediction of broiler chicken traits. Journal of Animal Breeding and Genetics 132:218-228.

Tunnicliffe W. 1989. On the use of marginal likelihood in time series model estimation. JRSS 51(1):15-27.