

Package ‘tidyHeatmap’

September 11, 2020

Type Package

Title A Tidy Implementation of Heatmap

Version 1.1.5

Maintainer Stefano Mangiola <mangiolastefano@gmail.com>

Description This is a tidy implementation for heatmap. At the moment it is based on the (great) package 'ComplexHeatmap'. The goal of this package is to interface a tidy data frame with this powerful tool. Some of the advantages are: Row and/or columns colour annotations are easy to integrate just specifying one parameter (column names). Custom grouping of rows is easy to specify providing a grouped tbl. For example: df %>% group_by(...). Labels size adjusted by row and column total number. Default use of Brewer and Viridis palettes.

License GPL-3

URL <https://www.r-project.org>,
<https://github.com/stemangiola/tidyHeatmap>

BugReports <https://github.com/stemangiola/tidyHeatmap>

Depends R (>= 3.6)

Imports methods,

stats,
utils,
dplyr (>= 0.8.5),
magrittr (>= 1.5),
tidyR (>= 1.0.3),
rlang (>= 0.4.5),
purrr (>= 0.3.3),
ComplexHeatmap (>= 2.2.0),
viridis (>= 0.5.1),
circlize (>= 0.4.8),
RColorBrewer (>= 1.1),
grid,
grDevices,
lifecycle (>= 0.2.0)

Suggests spelling,
testthat,
vdiffr,

BiocManager,
 knitr,
 rmarkdown,
 qpdf,
 covr,
 roxygen2
VignetteBuilder knitr
RdMacros lifecycle
Biarch true
biocViews AssayDomain, Infrastructure
Encoding UTF-8
LazyData true
RoxygenNote 7.1.1
Language en-US

R topics documented:

add_annotation	3
add_attr	4
add_bar	4
add_bar,InputHeatmap-method	5
add_class	6
add_line	6
add_line,InputHeatmap-method	7
add_point	8
add_tile	9
annot_to_list	10
as_matrix	10
check_if_counts_is_na	11
check_if_duplicated_genes	11
check_if_wrong_input	12
drop_class	12
error_if_log_transformed	13
get_abundance_norm_if_exists	13
get_elements	14
get_elements_features	14
get_elements_features_abundance	15
get_sample_counts	15
get_sample_transcript	16
get_sample_transcript_counts	16
get_x_y_annotation_columns	17
heatmap	17
ifelse2_pipe	20
ifelse_pipe	21
input_heatmap	21
N52	22
parse_formula	23
pasilla	23
prepend	23

quo_names	24
save_pdf	24
save_pdf,Heatmap-method	25
save_pdf,InputHeatmap-method	26
scale_design	26
scale_robust	27
select_closest_pairs	27

Index**28**

add_annotation	<i>add_annotation</i>
----------------	-----------------------

Description

`add_annotation()` takes a `tbl` object and easily produces a `ComplexHeatmap` plot, with integration with `tibble` and `dplyr` frameworks.

Usage

```
add_annotation(
  my_input_heatmap,
  annotation,
  type = rep("tile", length(quo_names(annotation))),
  palette_discrete = list(),
  palette_continuous = list()
)
```

Arguments

my_input_heatmap	A ‘InputHeatmap‘ formatted as <SAMPLE> <TRANSCRIPT> <COUNT> <...>
annotation	Vector of quotes
type	A character vector of the set c("tile", "point", "bar", "line")
palette_discrete	A list of character vectors. This is the list of palettes that will be used for horizontal and vertical discrete annotations. The discrete classification of annotations depends on the column type of your input tibble (e.g., character and factor).
palette_continuous	A list of character vectors. This is the list of palettes that will be used for horizontal and vertical continuous annotations. The continuous classification of annotations depends on the column type of your input tibble (e.g., integer, numerical, double).

Details

To be added.

Value

A ‘ComplexHeatmap‘ object

<code>add_attr</code>	<i>Add attribute to abject</i>
-----------------------	--------------------------------

Description

Add attribute to abject

Usage

```
add_attr(var, attribute, name)
```

Arguments

<code>var</code>	A tibble
<code>attribute</code>	An object
<code>name</code>	A character name of the attribute

Value

A tibble with an additional attribute

<code>add_bar</code>	<i>Adds a bar annotation layer to a ‘InputHeatmap’, that on evaluation creates a ‘ComplexHeatmap’</i>
----------------------	---

Description

`add_bar()` from a ‘InputHeatmap’ object, adds a bar annotation layer.

Usage

```
add_bar(.data, .column, palette = NULL)
```

Arguments

<code>.data</code>	A ‘tbl_df’ formatted as <ELEMENT> <FEATURE> <VALUE> <...>
<code>.column</code>	Vector of quotes
<code>palette</code>	A character vector of colors This is the list of palettes that will be used for horizontal and vertical discrete annotations. The discrete classification of annotations depends on the column type of your input tibble (e.g., character and factor).

Details

Maturing

It uses ‘ComplexHeatmap’ as visualisation tool.

Value

A ‘InputHeatmap‘ object that gets evaluated to a ‘ComplexHeatmap‘

Examples

```
library(dplyr)

hm =
tidyHeatmap::N52 %>%
tidyHeatmap::heatmap(
  .row = symbol_ct,
  .column = UBR,
  .value = `read count normalised log`
)
hm %>% add_bar()
```

add_bar, InputHeatmap-method
add_bar

Description

`add_bar`

Usage

```
## S4 method for signature 'InputHeatmap'
add_bar(.data, .column, palette = NULL)
```

Arguments

.data	A ‘tbl_df‘ formatted as <ELEMENT> <FEATURE> <VALUE> <...>
.column	Vector of quotes
palette	A character vector of colors This is the list of palettes that will be used for horizontal and vertical discrete annotations. The discrete classification of annotations depends on the column type of your input tibble (e.g., character and factor).

Value

A ‘add_bar‘ object

`add_class`*Add class to abject***Description**

Add class to abject

Usage

```
add_class(var, name)
```

Arguments

<code>var</code>	A tibble
<code>name</code>	A character name of the attribute

Value

A tibble with an additional attribute

`add_line`*Adds a line annotation layer to a ‘InputHeatmap’, that on evaluation creates a ‘ComplexHeatmap’***Description**

`add_line()` from a ‘InputHeatmap’ object, adds a line annotation layer.

Usage

```
add_line(.data, .column, palette = NULL)
```

Arguments

<code>.data</code>	A ‘tbl_df’ formatted as <ELEMENT> <FEATURE> <VALUE> <...>
<code>.column</code>	Vector of quotes
<code>palette</code>	A character vector of colors This is the list of palettes that will be used for horizontal and vertical discrete annotations. The discrete classification of annotations depends on the column type of your input tibble (e.g., character and factor).

Details**Maturing**

It uses ‘ComplexHeatmap’ as visualisation tool.

Value

A ‘InputHeatmap’ object that gets evaluated to a ‘ComplexHeatmap’

Examples

```
library(dplyr)

hm =
tidyHeatmap::N52 %>%
tidyHeatmap::heatmap(
  .row = symbol_ct,
  .column = UBR,
  .value = `read count normalised log`
)
hm %>% add_line()
```

add_line, InputHeatmap-method
add_line

Description

`add_line`

Usage

```
## S4 method for signature 'InputHeatmap'
add_line(.data, .column, palette = NULL)
```

Arguments

<code>.data</code>	A ‘tbl_df‘ formatted as <ELEMENT> <FEATURE> <VALUE> <...>
<code>.column</code>	Vector of quotes
<code>palette</code>	A character vector of colors This is the list of palettes that will be used for horizontal and vertical discrete annotations. The discrete classification of annotations depends on the column type of your input tibble (e.g., character and factor).

Value

A ‘add_line‘ object

add_point	<i>Adds a point annotation layer to a ‘InputHeatmap’, that on evaluation creates a ‘ComplexHeatmap’</i>
-----------	---

Description

add_point() from a ‘InputHeatmap‘ object, adds a point annotation layer.

Usage

```
add_point(.data, .column, palette = NULL)

## S4 method for signature 'InputHeatmap'
add_point(.data, .column, palette = NULL)
```

Arguments

.data	A ‘tbl_df‘ formatted as <ELEMENT> <FEATURE> <VALUE> <...>
.column	Vector of quotes
palette	A character vector of colors This is the list of palettes that will be used for horizontal and vertical discrete annotations. The discrete classification of annotations depends on the column type of your input tibble (e.g., character and factor).

Details

Maturing

It uses ‘ComplexHeatmap‘ as visualisation tool.

Value

A ‘InputHeatmap‘ object that gets evaluated to a ‘ComplexHeatmap‘
A ‘add_point‘ object

Examples

```
library(dplyr)

hm =
tidyHeatmap::N52 %>%
tidyHeatmap::heatmap(
  .row = symbol_ct,
  .column = UBR,
  .value = `read count normalised log`
)
hm %>% add_point()
```

add_tile	<i>Adds a tile annotation layer to a ‘InputHeatmap’, that on evaluation creates a ‘ComplexHeatmap’</i>
----------	--

Description

add_tile() from a ‘InputHeatmap’ object, adds a tile annotation layer.

Usage

```
add_tile(.data, .column, palette = NULL)

## S4 method for signature 'InputHeatmap'
add_tile(.data, .column, palette = NULL)
```

Arguments

.data	A ‘tbl_df‘ formatted as <ELEMENT> <FEATURE> <VALUE> <...>
.column	Vector of quotes
palette	A character vector of colors This is the list of palettes that will be used for horizontal and vertical discrete annotations. The discrete classification of annotations depends on the column type of your input tibble (e.g., character and factor).

Details

Maturing

It uses ‘ComplexHeatmap’ as visualisation tool.

Value

A ‘InputHeatmap‘ object that gets evaluated to a ‘ComplexHeatmap‘
A ‘add_tile‘ object

Examples

```
library(dplyr)

hm =
tidyHeatmap::N52 %>%
tidyHeatmap::heatmap(
  .row = symbol_ct,
  .column = UBR,
  .value = `read count normalised log`
)
hm %>% add_tile(CAPRA_TOTAL)
```

annot_to_list *annot_to_list*

Description

annot_to_list

Usage

```
annot_to_list(.data)
```

Arguments

.data A data frame

Value

A list

as_matrix *Get matrix from tibble*

Description

Get matrix from tibble

Usage

```
as_matrix(tbl, rownames = NULL, do_check = TRUE)
```

Arguments

tbl A tibble
rownames A character string of the rownames
do_check A boolean

Value

A matrix

```
check_if_counts_is_na  Check whether there are NA counts
```

Description

Check whether there are NA counts

Usage

```
check_if_counts_is_na(.data, .abundance)
```

Arguments

.data	A tibble of read counts
.abundance	A character name of the read count column

Value

A tbl

```
check_if_duplicated_genes
```

Check whether there are duplicated genes/transcripts

Description

Check whether there are duplicated genes/transcripts

Usage

```
check_if_duplicated_genes(.data, .sample, .transcript, .abundance)
```

Arguments

.data	A tibble of read counts
.sample	A character name of the sample column
.transcript	A character name of the transcript/gene column
.abundance	A character name of the read count column

Value

A tbl

`check_if_wrong_input` *Check whether there are NA counts*

Description

Check whether there are NA counts

Usage

```
check_if_wrong_input(.data, list_input, expected_type)
```

Arguments

<code>.data</code>	A tibble of read counts
<code>list_input</code>	A list
<code>expected_type</code>	A character string

Value

A `tbl`

`drop_class` *Remove class to abject*

Description

Remove class to abject

Usage

```
drop_class(var, name)
```

Arguments

<code>var</code>	A tibble
<code>name</code>	A character name of the class

Value

A tibble with an additional attribute

```
error_if_log_transformed
```

Check whether a numeric vector has been log transformed

Description

Check whether a numeric vector has been log transformed

Usage

```
error_if_log_transformed(x, .abundance)
```

Arguments

x	A numeric vector
.abundance	A character name of the transcript/gene abundance column

Value

NA

```
get_abundance_norm_if_exists
```

Get column names either from user or from attributes

Description

Get column names either from user or from attributes

Usage

```
get_abundance_norm_if_exists(.data, .abundance)
```

Arguments

.data	A tibble
.abundance	A character name of the abundance column

Value

A list of column enquo or error

`get_elements` *Get column names either from user or from attributes*

Description

Get column names either from user or from attributes

Usage

```
get_elements(.data, .element, of_samples = TRUE)
```

Arguments

<code>.data</code>	A tibble
<code>.element</code>	A character name of the sample column
<code>of_samples</code>	A boolean

Value

A list of column enquo or error

`get_elements_features` *Get column names either from user or from attributes*

Description

Get column names either from user or from attributes

Usage

```
get_elements_features(.data, .element, .feature, of_samples = TRUE)
```

Arguments

<code>.data</code>	A tibble
<code>.element</code>	A character name of the sample column
<code>.feature</code>	A character name of the transcript/gene column
<code>of_samples</code>	A boolean

Value

A list of column enquo or error

```
get_elements_features_abundance
```

Get column names either from user or from attributes

Description

Get column names either from user or from attributes

Usage

```
get_elements_features_abundance(  
  .data,  
  .element,  
  .feature,  
  .abundance,  
  of_samples = TRUE  
)
```

Arguments

.data	A tibble
.element	A character name of the sample column
.feature	A character name of the transcript/gene column
.abundance	A character name of the read count column
of_samples	A boolean

Value

A list of column enquo or error

```
get_sample_counts
```

Get column names either from user or from attributes

Description

Get column names either from user or from attributes

Usage

```
get_sample_counts(.data, .sample, .abundance)
```

Arguments

.data	A tibble
.sample	A character name of the sample column
.abundance	A character name of the read count column

Value

A list of column enquo or error

`get_sample_transcript` *Get column names either from user or from attributes*

Description

Get column names either from user or from attributes

Usage

```
get_sample_transcript(.data, .sample, .transcript)
```

Arguments

<code>.data</code>	A tibble
<code>.sample</code>	A character name of the sample column
<code>.transcript</code>	A character name of the transcript/gene column

Value

A list of column enquo or error

`get_sample_transcript_counts`
Get column names either from user or from attributes

Description

Get column names either from user or from attributes

Usage

```
get_sample_transcript_counts(.data, .sample, .transcript, .abundance)
```

Arguments

<code>.data</code>	A tibble
<code>.sample</code>	A character name of the sample column
<code>.transcript</code>	A character name of the transcript/gene column
<code>.abundance</code>	A character name of the read count column

Value

A list of column enquo or error

```
get_x_y_annotation_columns
  get_x_y_annotation_columns
```

Description

`get_x_y_annotation_columns`

Usage

```
get_x_y_annotation_columns(.data, .column, .row, .abundance)
```

Arguments

.data	A ‘tbl‘ formatted as <SAMPLE> <TRANSCRIPT> <COUNT> <...>
.column	The name of the column horizontally presented in the heatmap
.row	The name of the column vertically presented in the heatmap
.abundance	The name of the transcript/gene abundance column

Value

A list

heatmap	<i>Creates a ‘InputHeatmap‘ object from ‘tbl_df‘ on evaluation creates a ‘ComplexHeatmap‘</i>
---------	---

Description

`heatmap()` takes a `tbl` object and easily produces a `ComplexHeatmap` plot, with integration with `tibble` and `dplyr` frameworks.

Usage

```
heatmap(
  .data,
  .row,
  .column,
  .value,
  transform = NULL,
  .scale = "row",
  palette_value = c("#440154FF", "#21908CFF", "#fefada"),
  palette_grouping = list(),
  annotation = NULL,
  type = rep("tile", length(quo_names(annotation))),
  palette_discrete = list(),
  palette_continuous = list(),
  ...
)
```

```
heatmap_(
  .data,
  .row,
  .column,
  .value,
  transform = NULL,
  .scale = "row",
  palette_value = c("#440154FF", "#21908CFF", "#fefada"),
  palette_grouping = list(),
  annotation = NULL,
  type = rep("tile", length(quo_names(annotation))),
  palette_discrete = list(),
  palette_continuous = list(),
  ...
)

## S4 method for signature 'tbl'
heatmap(
  .data,
  .row,
  .column,
  .value,
  transform = NULL,
  .scale = "row",
  palette_value = c("#440154FF", "#21908CFF", "#fefada"),
  palette_grouping = list(),
  annotation = NULL,
  type = rep("tile", length(quo_names(annotation))),
  palette_discrete = list(),
  palette_continuous = list(),
  ...
)

## S4 method for signature 'tbl_df'
heatmap(
  .data,
  .row,
  .column,
  .value,
  transform = NULL,
  .scale = "row",
  palette_value = c("#440154FF", "#21908CFF", "#fefada"),
  palette_grouping = list(),
  annotation = NULL,
  type = rep("tile", length(quo_names(annotation))),
  palette_discrete = list(),
  palette_continuous = list(),
  ...
)

## S4 method for signature 'tidybulk'
```

```
heatmap(
  .data,
  .row,
  .column,
  .value,
  transform = NULL,
  .scale = "row",
  palette_value = c("#440154FF", "#21908CFF", "#fefada"),
  palette_grouping = list(),
  annotation = NULL,
  type = rep("tile", length(quo_names(annotation))),
  palette_discrete = list(),
  palette_continuous = list(),
  ...
)
```

Arguments

.data	A ‘tbl_df‘ formatted as <ELEMENT> <FEATURE> <VALUE> <...>
.row	The name of the column vertically presented in the heatmap
.column	The name of the column horizontally presented in the heatmap
.value	The name of the column for the value of the element/feature pair
transform	A function, used to transform .value row-wise (e.g., transform = log1p)
.scale	A character string. Possible values are c("none", "row", "column", "both")
palette_value	A character vector This is the palette that will be used as gradient for .value. For example c("red", "white", "blue"). For higher flexibility you can use circlize::colorRamp2(c(-2, -1, 0, 1, 2), viridis::magma(5))
palette_grouping	A list of character vectors. This is the list of palettes that will be used for grouping. For example list(RColorBrewer::brewer.pal(8, "Accent")) or list(c("#B3E2CD", "#FDCDAC", "#CBD5E8")) or list(c("black", "red"))
annotation	DEPRECATED. please use the annotation functions add_* function (\(* one of tile, point, bar, line \)).
type	DEPRECATED. please use the annotation functions add_* function (\(* one of tile, point, bar, line \)).
palette_discrete	DEPRECATED. please use the annotation functions add_* function (\(* one of tile, point, bar, line \)).
palette_continuous	DEPRECATED. please use the annotation functions add_* function (\(* one of tile, point, bar, line \)).
...	Further arguments to be passed to ComplexHeatmap::Heatmap

Details

Maturing

This function takes a `tbl` as an input and creates a ‘ComplexHeatmap‘ plot. The information is stored in a ‘InputHeatmap‘ object that is updated along the pipe statement, for example adding annotation layers.

Value

- A ‘InputHeatmap‘ objects that gets evaluated to a ‘ComplexHeatmap‘ object
- A ‘InputHeatmap‘ object
- A ‘InputHeatmap‘ object
- A ‘InputHeatmap‘ object
- A ‘InputHeatmap‘ object

Examples

```
library(dplyr)

tidyHeatmap::N52 %>%
group_by(`Cell type`) %>%
tidyHeatmap::heatmap(
  .row = symbol_ct,
  .column = UBR,
  .value = `read count normalised log`,
)
```

ifelse2_pipe

This is a generalisation of ifelse that accepts an object and return an objects

Description

This is a generalisation of ifelse that accepts an object and return an objects

Usage

```
ifelse2_pipe(.x, .p1, .p2, .f1, .f2, .f3 = NULL)
```

Arguments

.x	A tibble
.p1	A boolean
.p2	ELSE IF condition
.f1	A function
.f2	A function
.f3	A function

Value

A tibble

ifelse_pipe	<i>This is a generalisation of ifelse that accepts an object and return an objects</i>
-------------	--

Description

This is a generalisation of ifelse that accepts an object and return an objects

Usage

```
ifelse_pipe(.x, .p, .f1, .f2 = NULL)
```

Arguments

.x	A tibble
.p	A boolean
.f1	A function
.f2	A function

Value

A tibble

input_heatmap	<i>input_heatmap</i>
---------------	----------------------

Description

input_heatmap() takes a `tbl` object and easily produces a ComplexHeatmap plot, with integration with `tibble` and `dplyr` frameworks.

Usage

```
input_heatmap(  
  .data,  
  .horizontal,  
  .vertical,  
  .abundance,  
  transform = NULL,  
  .scale = "row",  
  palette_value = c("#440154FF", "#21908CFF", "#fefada"),  
  palette_grouping = list(),  
  ...  
)
```

Arguments

.data	A ‘tbl‘ formatted as <SAMPLE> <TRANSCRIPT> <COUNT> <...>
.horizontal	The name of the column horizontally presented in the heatmap
.vertical	The name of the column vertically presented in the heatmap
.abundance	The name of the transcript/gene abundance column
transform	A function, used to transform .value, for example log1p
.scale	A character string. Possible values are c("none", "row", "column", "both")
palette_value	A character vector, or a function for higher customisation (colorRamp2). This is the palette that will be used as gradient for abundance. If palette_value is a vector of hexadecimal colours, it should have 3 values. If you want more customisation, you can pass to palette_value a function, that is derived as for example ‘colorRamp2(c(-2, 0, 2), palette_value)‘
palette_grouping	A list of character vectors. This is the list of palettes that will be used for grouping
...	Further arguments to be passed to ComplexHeatmap::Heatmap

Details

To be added.

Value

A ‘ComplexHeatmap‘ object

Description

Example data set N52

Usage

N52

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 520 rows and 15 columns.

parse_formula	<i>formula parser</i>
---------------	-----------------------

Description

.formula parser

Usage

```
parse_formula(fm)
```

Arguments

fm	a formula
----	-----------

Value

A character vector

pasilla	<i>Example data set Pasilla</i>
---------	---------------------------------

Description

Example data set Pasilla

Usage

```
pasilla
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 504 rows and 8 columns.

prepend	<i>From rlang deprecated</i>
---------	------------------------------

Description

From rlang deprecated

Usage

```
prepend(x, values, before = 1)
```

Arguments

<code>x</code>	An array
<code>values</code>	An array
<code>before</code>	A boolean

Value

An array

<code>quo_names</code>	<i>Convert array of quosure (e.g. c(col_a, col_b)) into character vector</i>
------------------------	--

Description

Convert array of quosure (e.g. c(col_a, col_b)) into character vector

Usage

```
quo_names(v)
```

Arguments

<code>v</code>	A array of quosures (e.g. c(col_a, col_b))
----------------	--

Value

A character vector

<code>save_pdf</code>	<i>Save plot on PDF file</i>
-----------------------	------------------------------

Description

`save_pdf()` takes as input a Heatmap from ComplexHeatmap and save it to PDF file

Usage

```
save_pdf(
  .heatmap,
  filename,
  width = NULL,
  height = NULL,
  units = c("in", "cm", "mm")
)
```

Arguments

.heatmap	A ‘Heatmap’
filename	A character string. The name of the output file/path
width	A ‘double’. Plot width
height	A ‘double’. Plot height
units	A character string ("in", "cm", or "mm")

Details**Maturing**

It simply save an ‘Heatmap’ to a PDF file use pdf() function in the back end

Value

NA

Examples

```
library(dplyr)
tidyHeatmap::heatmap(
  dplyr::group_by(tidyHeatmap::pasilla,location, type),
  .column = sample,
  .row = symbol,
  .value = `count normalised adjusted`,
) %>%
  save_pdf(tempfile())
```

save_pdf,Heatmap-method
save_pdf

Description

save_pdf

Usage

```
## S4 method for signature 'Heatmap'
save_pdf(
  .heatmap,
  filename,
  width = NULL,
  height = NULL,
  units = c("in", "cm", "mm")
)
```

Arguments

.heatmap	A ‘Heatmap’
filename	A character string. The name of the output file/path
width	A ‘double’. Plot width
height	A ‘double’. Plot height
units	A character string ("in", "cm", or "mm")

save_pdf , InputHeatmap-method
save_pdf

Description

save_pdf

Usage

```
## S4 method for signature 'InputHeatmap'
save_pdf(
  .heatmap,
  filename,
  width = NULL,
  height = NULL,
  units = c("in", "cm", "mm")
)
```

Arguments

.heatmap	A ‘Heatmap’
filename	A character string. The name of the output file/path
width	A ‘double’. Plot width
height	A ‘double’. Plot height
units	A character string. units ("in", "cm", or "mm")

scale_design *Scale design matrix*

Description

Scale design matrix

Usage

scale_design(df, .formula)

Arguments

df	A tibble
.formula	a formula

Value

A tibble

scale_robust *Scale counts in a robust way against sd == 0*

Description

Scale counts in a robust way against sd == 0

Usage

scale_robust(y)

Arguments

y	A numerical array
---	-------------------

Value

A scaled and centred numerical array

select_closest_pairs *Sub function of remove_redundancy_elements_though_reduced_dimensions*

Description

Sub function of remove_redundancy_elements_though_reduced_dimensions

Usage

select_closest_pairs(df)

Arguments

df	A tibble
----	----------

Value

A tibble with pairs to drop

Index

- * datasets
 - N52, 22
 - pasilla, 23
- add_annotation, 3
- add_attr, 4
- add_bar, 4
- add_bar, InputHeatmap-method, 5
- add_class, 6
- add_line, 6
- add_line, InputHeatmap-method, 7
- add_point, 8
- add_point, InputHeatmap-method
 - (add_point), 8
- add_tile, 9
- add_tile, InputHeatmap-method
 - (add_tile), 9
- annot_to_list, 10
- as_matrix, 10
- check_if_counts_is_na, 11
- check_if_duplicated_genes, 11
- check_if_wrong_input, 12
- drop_class, 12
- error_if_log_transformed, 13
- get_abundance_norm_if_exists, 13
- get_elements, 14
- get_elements_features, 14
- get_elements_features_abundance, 15
- get_sample_counts, 15
- get_sample_transcript, 16
- get_sample_transcript_counts, 16
- get_x_y_annotation_columns, 17
- heatmap, 17
- heatmap, tbl-method (heatmap), 17
- heatmap, tbl_df-method (heatmap), 17
- heatmap, tidybulk-method (heatmap), 17
- heatmap_(heatmap), 17
- ifelse2_pipe, 20
- ifelse_pipe, 21
- input_heatmap, 21
- N52, 22
- parse_formula, 23
- pasilla, 23
- prepend, 23
- quo_names, 24
- save_pdf, 24
- save_pdf, Heatmap-method, 25
- save_pdf, InputHeatmap-method, 26
- scale_design, 26
- scale_robust, 27
- select_closest_pairs, 27