

# Distance-sampling analysis in unmarked

Richard Chandler  
Department of Natural Resources Conservation  
University of Massachusetts Amherst

April 8, 2010

## Abstract

Distance-sampling is a wildlife sampling technique used to estimate population size or density. Describing how density varies spatially is often of equal interest; however, conventional methods of analysis do not allow for explicit modeling of both density and detection probability. The function `distsamp` implements the multinomial-Poisson mixture model of Royle et. al [1], which was developed to overcome this limitation. This model requires that line- or point-transects are spatially replicated and that distance data are recorded in discrete intervals. This document describes how to format data, fit models, and manipulate results in package `unmarked`. It does not cover the statistical theory and assumptions underlying distance-sampling, which the user is expected to be familiar with.

## 1 Introduction

Spatial variation in density is common to virtually all wildlife populations, and describing this variation is a central objective of much research. To accurately estimate and model density, it is often necessary to account for individuals present but not detected. Distance from observer is a ubiquitous source of variation in detection probability, and thus distance-sampling has become a commonly used survey methodology. Numerous options exist for analyzing distance-sampling data, but here the focus is on the model of Royle et al. [1], which assumes that multiple transects have been surveyed and distance data are recorded in discrete intervals. The details of the model formulation are as follows:

The latent transect-level abundance distribution is currently assumed to be

$$N_i \sim \text{Poisson}(\lambda) \quad i = 1, \dots, M \quad (1)$$

The detection process is modeled as

$$y_{ij} \sim \text{Multinomial}(N_i, \pi_{ij}) \quad i = 1, \dots, M \quad j = 1, \dots, J \quad (2)$$

where  $\pi_{ij}$  is the multinomial cell probability for transect  $i$  in distance class  $j$ . These are computed by integrating a detection function such as the half-normal (with shape parameter  $\sigma$ ) over each distance interval.

Parameters  $\lambda$  and  $\sigma$  can be vectors affected by transect-specific covariates using the log link.

## 2 Importing, formatting, and summarizing data

The first step is to import the data into R. The simplest option is to use the `read.csv` function to import a .csv file that has been formatted so that each row represents a transect, and columns describe either the number of individuals detected in each distance interval or transect-specific covariates. Alternatively, if data were not recorded in discrete distance intervals, a .csv file could be imported that contains a row for each individual detected and columns for the distances and transect names. This could then be converted to transect-level data using the function `formatDistData`. For example,

```
> library(unmarked)
> dists <- read.csv(system.file("csv", "distdata.csv",
  package = "unmarked"))
> head(dists, 10)
```

```

      distance transect
1         1         a
2        18         a
3         7         a
4         2         a
5        13         b
6         3         b
7         5         b
8        10         b
9         6         c
10        9         c
> levels(dists$transect) <- c(levels(dists$transect), "g")
> levels(dists$transect)
[1] "a" "b" "c" "d" "e" "f" "g"
> yDat <- formatDistData(dists, distCol = "distance", transectNameCol = "transect",
      dist.breaks = c(0, 5, 10, 15, 20))
> yDat
  y.1 y.2 y.3 y.4
a   2  1  0  1
b   2  1  1  0
c   2  2  0  0
d   2  1  1  0
e   1  0  1  2
f   2  1  1  0
g   0  0  0  0

```

Here we have created an object called `yDat` that contains counts for each transect (row) in each distance interval (columns). Note the method used to include transect "g", which was surveyed but where no individuals were detected. It is important that all surveyed transects are included in the analysis.

Suppose there also exists transect-specific covariate data.

```

> (covs <- data.frame(canopyHt = c(5, 8, 3, 2, 4, 7, 5),
      habitat = c("A", "A", "A", "A", "B", "B", "B"), row.names = letters[1:7]))
  canopyHt habitat
a         5      A
b         8      A
c         3      A
d         2      A
e         4      B
f         7      B
g         5      B

```

The function `unmarkedFrameDS` can now be used to organize these data along with their metadata (study design (line- or point-transect), distance class break points, transect lengths, and units of measurement) into an object to be used as the `data` argument in `distsamp`. By organizing the data this way, the user does not need to repetitively specify these arguments during each call to `distsamp`, thereby reducing the potential for errors and facilitating data summary and manipulation.

```

> umf <- unmarkedFrameDS(y = as.matrix(yDat), siteCovs = covs,
      survey = "line", dist.breaks = c(0, 5, 10, 15, 20),
      tlength = rep(100, 7), unitsIn = "m")

```

Note that there is no `obsCovs` argument, meaning that distance-interval-level covariates cannot be included in the analysis. The call to `unmarkedFrameDS` indicates that the data were collected on seven line transects, each 100 meters long, and detections were tabulated into distance intervals defined by the `dist.breaks` cutpoints. It is important that both transect lengths and distance break points are provided in the same units specified by `unitsIn`.

We can look at these data, summarize them, and plot them using a variety of methods.

```

> umf

```

```

Data frame representation of unmarkedFrame object.
  y.1 y.2 y.3 y.4 canopyHt habitat
a   2   1   0   1       5       A
b   2   1   1   0       8       A
c   2   2   0   0       3       A
d   2   1   1   0       2       A
e   1   0   1   2       4       B
f   2   1   1   0       7       B
g   0   0   0   0       5       B
> summary(umf)
unmarkedFrameDS Object

line-transect survey design
Distance class cutpoints (m): 0 5 10 15 20

7 sites
Maximum number of distance classes per site: 4
Mean number of distance classes per site: 4
Sites with at least one detection: 6

Tabulation of y observations:
  0   1   2 <NA>
11  10   7   0

Site-level covariates:
  canopyHt   habitat
Min.   :2.000   A:4
1st Qu.:3.500   B:3
Median :5.000
Mean   :4.857
3rd Qu.:6.000
Max.   :8.000
> hist(umf, xlab = "distance (m)", main = "", cex.lab = 0.8,
      cex.axis = 0.8)

```




Figure 1: Histogram of detection distances.

### 3 Model fitting

Now that we have put our data into an object of class `unmarkedFrameDS`, we are ready to fit some models with `distsamp`. The first argument is a `formula` which specifies the detection covariates followed by the density (or abundance) covariates. The only other required argument is the `data`, but several other optional arguments exist. By default, the half-normal detection function is used to model density in animals / ha. The detection function can be selected using the `keyfun` argument. The response can be changed from "density", to "abund" with the `output` argument. When modeling density, the output units can be changed from "ha" to "kmsq" using the `unitsOut` argument. `distsamp` also includes the arguments `starts`, `method`, and `control`, which are common to all unmarked fitting functions.

Below are a series of models that demonstrate `distsamp`'s arguments and defaults.

```
> hn_Null <- distsamp(~1 ~ 1, umf)
> hn_Null <- distsamp(~1 ~ 1, umf, keyfun = "halfnorm",
  output = "density", unitsOut = "ha")
> haz_Null <- distsamp(~1 ~ 1, umf, keyfun = "hazard")
> hn_Hab.Ht <- distsamp(~canopyHt ~ habitat, umf)
```

The first two models are the same, a null half-normal detection function with density returned in animals / ha (on the log-scale). The third model uses the hazard-rate detection function, and the fourth model includes covariates affecting the Poisson mean ( $\lambda$ ) and the half-normal shape parameter ( $\sigma$ ).

Once a model has been fit, typing it's name will display parameter estimate information and AIC. A summary method shows extra details including the scale on which parameters were estimated and convergence results.

```
> summary(haz_Null)
Call:
distsamp(formula = ~1 ~ 1, data = umf, keyfun = "hazard")

Density (log-scale):
```

```

Estimate   SE    z P(>|z|)
      2.96 0.959 3.09 0.00198

Detection (log-scale):
Estimate   SE    z P(>|z|)
      1.44 2.37 0.606  0.544

Hazard-rate(scale) (log-scale):
Estimate   SE    z P(>|z|)
     -0.0223 1.21 -0.0184  0.985

AIC: 65.17091
Sample size: 7
optim convergence code: 0
optim iterations: 25
Bootstrap iterations: 0

Survey design: line-transect
Detection function: hazard
UnitsIn: m
UnitsOut: ha

```

## 4 Manipulating results

Back-transforming estimates to the original scale and obtaining standard errors via the delta method is easily accomplished:

```

> names(haz_Null)
[1] "state" "det"  "scale"
> backTransform(haz_Null, type = "state")
Backtransformed linear combination(s) of Density estimate(s)

Estimate   SE LinComb (Intercept)
      19.4 18.6    2.96             1

Transformation: exp
> backTransform(haz_Null, type = "det")
Backtransformed linear combination(s) of Detection estimate(s)

Estimate   SE LinComb shape(Intercept)
      4.21 9.99    1.44                 1

Transformation: exp
> backTransform(haz_Null, type = "scale")
Backtransformed linear combination(s) of Hazard-rate(scale) estimate(s)

Estimate   SE LinComb scale
      0.978 1.18 -0.0223    1

Transformation: exp
> backTransform(linearComb(hn_Hab.Ht["det"], c(0, 5)))
Backtransformed linear combination(s) of Detection estimate(s)

Estimate   SE LinComb sigma(Intercept) sigmacanopyHt
      0.933 0.49 -0.0698                0                5

Transformation: exp

```

The first back-transformation returns population density, since this is the default state parameter modeled when `distsamp`'s `output` argument is set to 'density'. The second back-transformation returns the hazard-rate shape parameter, and third is the hazard-rate scale parameter. When covariates are present, `backTransform` in conjunction with `linearComb` should be used.

Parameters that do not occur in the likelihood may also be of interest. For example, the number of individuals occurring in the sampled plots (local population size) is a fundamental parameter in monitoring and conservation efforts. The following commands can be used to derive this parameter from our model of density:

```
> site.level.density <- predict(hn_Hab.Ht, type = "state")$Predicted
> plotArea.inHectares <- 100 * 40/10000
> site.level.abundance <- site.level.density * plotArea.inHectares
> (N.hat <- sum(site.level.abundance))
[1] 39.06128
```

To estimate the standard error of `N.hat`, or any other derived parameter, we can use a parametric bootstrap approach. First we define a function to estimate `N.hat`, and then we apply this function to numerous models fit to data simulated from our original model.

```
> getN.hat <- function(fit) {
  d <- predict(fit, type = "state")$Predicted
  a <- d * (100 * 40/10000)
  N.hat <- c(N.hat = sum(a))
  return(N.hat)
}
> pb <- parboot(hn_Hab.Ht, statistic = getN.hat, nsim = 25,
  report = 5)
t0 = 39.06128
34.7, 45.5, 24.9, 21.8, 36.7
41.5, 50, 25.7, 54.8, 34.4
38.7, 50.8, 48.7, 41.1, 36.6
60.1, 18, 37.3, 39.4, 38.1
50.3, 65.3, 31.6, 32.2, 47.4
> pb
Call:
parboot(object = hn_Hab.Ht, statistic = getN.hat, nsim = 25, report = 5)

Parametric Bootstrap Statistics:
      t0 mean(t0 - t_B) StdDev(t0 - t_B) Pr(t_B > t0)
N.hat 39.1          -1.17           11.6          0.462

t_B quantiles:
      0% 2.5% 25% 50% 75% 97.5% 100%
N.hat 18  20  34  39  49   62   65

t0 = Original statistic computed from data
t_B = Vector of bootstrap samples
```

Here, `t_B` is an approximation of the sampling distribution for `N.hat`, conditioned on our fitted model. The standard deviation of `t_B` is the standard error of `N.hat` and confidence intervals can be calculated from its quantiles. Note that in practice `nsim` should be set to a much larger value and a goodness-of-fit test should be performed before making inference from a fitted model. Parametric bootstrapping can be used for the latter by supplying a fit statistic such as `SSE` instead of `getN.hat`. See `?parboot` and `vignette('Overview')` for examples.

## 5 Prediction and plotting

A `predict` method exists for all `unmarkedFit` objects, which is useful when multiple covariate combinations exist. This method also facilitates plotting. Suppose we wanted model predictions from the covariate model along the range of covariate values studied. First we need make new data.frames holding the desired covariate combinations. Note that column names must match those of the original data, and factor variables must contain the same levels.

```

> (habConstant <- data.frame(canopyHt = seq(2, 8, length = 20),
  habitat = factor("A", levels = c("A", "B"))))
  canopyHt habitat
1  2.000000      A
2  2.315789      A
3  2.631579      A
4  2.947368      A
5  3.263158      A
6  3.578947      A
7  3.894737      A
8  4.210526      A
9  4.526316      A
10 4.842105      A
11 5.157895      A
12 5.473684      A
13 5.789474      A
14 6.105263      A
15 6.421053      A
16 6.736842      A
17 7.052632      A
18 7.368421      A
19 7.684211      A
20 8.000000      A
> (htConstant <- data.frame(canopyHt = 5, habitat = factor(c("A",
  "B"))))
  canopyHt habitat
1         5      A
2         5      B

```

Now predict can be used to estimate density and  $\sigma$  for each row of our new data.frames.

```

> (Elambda <- predict(hn_Hab.Ht, type = "state", newdata = htConstant,
  appendData = TRUE))
  Predicted      SE canopyHt habitat
1  16.22835 5.058481      5      A
2  10.91326 4.370499      5      B
> head(Esigma <- predict(hn_Hab.Ht, type = "det", newdata = habConstant,
  appendData = TRUE))
  Predicted      SE canopyHt habitat
1  10.76998 4.259541 2.000000      A
2  10.72259 3.968438 2.315789      A
3  10.67541 3.693948 2.631579      A
4  10.62844 3.439012 2.947368      A
5  10.58167 3.207199 3.263158      A
6  10.53511 3.002718 3.578947      A

```

Once predictions have been made, plotting is straight-forward. Figure~2a, shows density as a function of habitat type, and Figure~2b shows that  $\sigma$  is not related to canopy height.

```

> par(mfrow = c(1, 2))
> with(Elambda, {
  x <- barplot(Predicted, names = habitat, xlab = "Habitat",
    ylab = "Density (animals / ha)", ylim = c(0,
      25), cex.names = 0.7, cex.lab = 0.7, cex.axis = 0.7)
  arrows(x, Predicted, x, Predicted + SE, code = 3,
    angle = 90, length = 0.05)
  box()
})
> with(Esigma, {
  plot(canopyHt, Predicted, type = "l", xlab = "Canopy height",
    ylab = expression(paste("Half-normal shape parameter (",
      sigma, ")"), sep = ""), ylim = c(0, 20),

```

```

    cex = 0.7, cex.lab = 0.7, cex.axis = 0.7)
  lines(canopyHt, Predicted + SE, lty = 2)
  lines(canopyHt, Predicted - SE, lty = 2)
})

```




Figure 2: Predicted covariate relationships.

Plots of the detection function parameters can be less informative than plots of the detection functions themselves. To do the latter, we can plug predicted values of  $\sigma$  at given covariate values into the `gxhn` function. For instance, Figure~3a shows to the half-normal function at a canopy height of 2m. This was plotted by setting  $\sigma$  to 10.8, the predicted value shown above. The available detection functions are described on the `detFuns` help page. Probability density functions such as `dxhn` can be plotted with the distance histogram using the `hist` method for `unmarkedFitDS` objects (Figure~3b). This only works for models without detection covariates; however, probability density functions at specific covariate values can be added in a fashion similar to that above (Figure~3b).

```

> par(mfrow = c(1, 2))
> plot(function(x) gxhn(x, sigma = 10.8), 0, 20, xlab = "Distance (m)",
      ylab = "Detection prob. at 2m canopy ht.", cex.lab = 0.7,
      cex.axis = 0.7, las = 1)
> hist(hn_Null, xlab = "Distance (m)", ylab = "Probability density",
      main = "", ylim = c(0, 0.1), cex.lab = 0.7, cex.axis = 0.7,
      las = 1)
> plot(function(x) dxhn(x, sigma = 10.8), 0, 20, add = TRUE,
      col = "blue")
> plot(function(x) dxhn(x, sigma = 9.9), 0, 20, add = TRUE,
      col = "green")
> legend("topright", c("Canopy ht. = 2m", "Null", "Canopy ht. = 8m"),
      col = c("blue", "black", "green"), lty = 1, cex = 0.4)

```




Figure 3: Detection and probability density functions.

This document has emphasized methods tailored to distance-sampling analysis; however, the more general methods available in package `unmarked` can also be applied to `distsamp` related objects. For example, model-selection, model-averaging, and goodness-of-fit evaluation can be accomplished using the `modSel` and `parboot` methods.

## References

- [1] J. A. Royle, D. K. Dawson, and S. Bates. Modeling abundance effects in distance sampling. *Ecology*, 85:1591–1597, 2004.