

Package ‘lucidr’

March 10, 2026

Title 'Lucide' Icons for 'R'

Version 0.1.0

Description A lightweight wrapper for the 'Lucide' icon library
<<https://lucide.dev>>. Embed beautiful and consistent 'SVG' icons
inline in any 'R' web application.

License MIT + file LICENSE

URL <https://github.com/hyperverse-r/lucidr>

BugReports <https://github.com/hyperverse-r/lucidr/issues>

Depends R (>= 3.5)

Imports htmltools

Suggests htmxr, plumber2, testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.3.3

NeedsCompilation no

Author Arthur Bréant [aut, cre]

Maintainer Arthur Bréant <arthur@thinkr.fr>

Repository CRAN

Date/Publication 2026-03-10 11:30:02 UTC

Contents

lucide	2
lucide_list	3
Index	4

`lucide`*Lucide icon*

Description

Renders a 'Lucide' icon as an inline 'SVG' element.

Usage

```
lucide(  
  name,  
  size = 24,  
  color = "currentColor",  
  stroke_width = 2,  
  class = NULL,  
  ...  
)
```

Arguments

<code>name</code>	Icon name (e.g. "chevron-right", "house", "settings"). See https://lucide.dev/icons/ for the full list.
<code>size</code>	Icon size in pixels. Applied to both width and height. Default 24.
<code>color</code>	Icon colour. Any valid CSS colour value. Default "currentColor" (inherits from parent element).
<code>stroke_width</code>	Stroke width. Default 2.
<code>class</code>	Additional CSS classes to add to the <svg> element.
<code>...</code>	Additional HTML attributes passed to the <svg> element.

Value

An `htmltools::tags` object (inline <svg>).

Examples

```
lucide("house")  
lucide("chevron-right", size = 16, color = "red")  
lucide("settings", stroke_width = 1.5, class = "my-icon")
```

`lucide_list`*List available Lucide icons*

Description

Returns the names of all icons bundled in this version of 'lucidr'.

Usage

```
lucide_list()
```

Value

A character vector of icon names.

Examples

```
head(lucide_list(), 10)  
length(lucide_list())
```

Index

`htmltools::tags`, [2](#)

`lucide`, [2](#)

`lucide_list`, [3](#)