

Package ‘obrasgovr’

July 24, 2026

Title Access the 'ObrasGov' Open Data API

Version 0.1.0

Description Provides a modern interface to the Brazilian federal government's 'ObrasGov' open data application programming interface (<<https://api-publica.obrasgov.gestao.gov.br>>). Retrieves data about public infrastructure projects, physical execution, contracts, commitments, geometries, feasibility studies, and project status histories. Results are returned as tidy tibbles with typed date columns, preserved nested relationships, pagination metadata, and optional multi-page collection.

License MIT + file LICENSE

URL <https://github.com/StrategicProjects/obrasgovr>,
<https://strategicprojects.github.io/obrasgovr/>,
<https://api-publica.obrasgov.gestao.gov.br/obras/docs>

BugReports <https://github.com/StrategicProjects/obrasgovr/issues>

Depends R (>= 4.1.0)

Imports cli, httr2 (>= 1.2.2), purrr (>= 1.0.0), rlang (>= 1.1.0),
tibble (>= 3.2.0)

Suggests covr, dplyr, knitr, rmarkdown, testthat (>= 3.2.0), tidyr

VignetteBuilder knitr

Config/Needs/website pkgdown

Config/testthat/edition 3

Encoding UTF-8

Language en-US

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Andre Leite [aut, cre] (ORCID: <<https://orcid.org/0000-0002-4718-9766>>),
Marcos Wasiliew [aut],
Hugo Vasconcelos [aut] (ORCID: <<https://orcid.org/0000-0001-6249-0920>>),
Carlos Amorim [aut] (ORCID: <<https://orcid.org/0000-0001-6315-8305>>),
Diogo Bezerra [aut] (ORCID: <<https://orcid.org/0000-0002-1216-8674>>)

Maintainer Andre Leite <leite@castlab.org>
Repository CRAN
Date/Publication 2026-07-24 09:30:09 UTC

Contents

get_commitments	2
get_contracts	3
get_feasibility_studies	4
get_geometries	6
get_last_update	7
get_physical_execution	8
get_projects	9
get_status_history	10
list_filters	11
list_resources	12
result_metadata	13
Index	14

get_commitments	<i>Retrieve budget commitments</i>
-----------------	------------------------------------

Description

Retrieve budget commitments

Usage

```
get_commitments(  
  ...,  
  page = 1L,  
  page_size = 50L,  
  all_pages = FALSE,  
  page_limit = Inf,  
  base_url = .obrasgovr_base_url()  
)  
  
obter_empenhos(  
  ...,  
  pagina = 1L,  
  tamanho_da_pagina = 50L,  
  todas_paginas = FALSE,  
  limite_paginas = Inf,  
  base_url = .obrasgovr_base_url()  
)
```

Arguments

...	Named filters. See <code>list_filters("commitments")</code> .
page	First page to retrieve, starting at 1.
page_size	Number of records per page, between 1 and 200.
all_pages	If TRUE, retrieves successive pages starting at page.
page_limit	Maximum number of pages to retrieve when <code>all_pages</code> is TRUE. Use <code>Inf</code> to retrieve every available page.
base_url	HTTPS base URL. By default, uses the <code>obrasgovr.base_url</code> option or the official API environment.
pagina, tamanho_da_pagina, todas_paginas, limite_paginas	Portuguese aliases for <code>page</code> , <code>page_size</code> , <code>all_pages</code> , and <code>page_limit</code> , respectively. These arguments are available only in the Portuguese function alias.

Value

A tibble containing budget commitments and financial execution amounts.

See Also

Other API resources: [get_contracts\(\)](#), [get_feasibility_studies\(\)](#), [get_geometries\(\)](#), [get_last_update\(\)](#), [get_physical_execution\(\)](#), [get_projects\(\)](#), [get_status_history\(\)](#)

Examples

```
if (interactive()) {
  get_commitments(id_projeto_investimento = "134851.26-07")
}
```

get_contracts	<i>Retrieve contracts</i>
---------------	---------------------------

Description

Retrieve contracts

Usage

```
get_contracts(
  ...,
  page = 1L,
  page_size = 50L,
  all_pages = FALSE,
  page_limit = Inf,
  base_url = .obrasgovr_base_url()
)
```

```
obter_contratos(
  ...,
  pagina = 1L,
  tamanho_da_pagina = 50L,
  todas_paginas = FALSE,
  limite_paginas = Inf,
  base_url = .obrasgovr_base_url()
)
```

Arguments

...	Named filters. See <code>list_filters("contracts")</code> .
page	First page to retrieve, starting at 1.
page_size	Number of records per page, between 1 and 200.
all_pages	If TRUE, retrieves successive pages starting at page.
page_limit	Maximum number of pages to retrieve when <code>all_pages</code> is TRUE. Use <code>Inf</code> to retrieve every available page.
base_url	HTTPS base URL. By default, uses the <code>obrasgovr.base_url</code> option or the official API environment.
pagina, tamanho_da_pagina, todas_paginas, limite_paginas	Portuguese aliases for <code>page</code> , <code>page_size</code> , <code>all_pages</code> , and <code>page_limit</code> , respectively. These arguments are available only in the Portuguese function alias.

Value

A tibble containing contracts linked to infrastructure projects.

See Also

Other API resources: [get_commitments\(\)](#), [get_feasibility_studies\(\)](#), [get_geometries\(\)](#), [get_last_update\(\)](#), [get_physical_execution\(\)](#), [get_projects\(\)](#), [get_status_history\(\)](#)

Examples

```
if (interactive()) {
  get_contracts(id_projeto_investimento = "134851.26-07")
}
```

```
get_feasibility_studies
```

Retrieve feasibility studies

Description

Retrieve feasibility studies

Usage

```

get_feasibility_studies(
  ...,
  page = 1L,
  page_size = 50L,
  all_pages = FALSE,
  page_limit = Inf,
  base_url = .obrasgovr_base_url()
)

obter_estudos_viabilidade(
  ...,
  pagina = 1L,
  tamanho_da_pagina = 50L,
  todas_paginas = FALSE,
  limite_paginas = Inf,
  base_url = .obrasgovr_base_url()
)

```

Arguments

...	Named filters. See <code>list_filters("feasibility_studies")</code> .
page	First page to retrieve, starting at 1.
page_size	Number of records per page, between 1 and 200.
all_pages	If TRUE, retrieves successive pages starting at page.
page_limit	Maximum number of pages to retrieve when <code>all_pages</code> is TRUE. Use <code>Inf</code> to retrieve every available page.
base_url	HTTPS base URL. By default, uses the <code>obrasgovr.base_url</code> option or the official API environment.
pagina, tamanho_da_pagina, todas_paginas, limite_paginas	Portuguese aliases for <code>page</code> , <code>page_size</code> , <code>all_pages</code> , and <code>page_limit</code> , respectively. These arguments are available only in the Portuguese function alias.

Value

A tibble containing feasibility studies linked to projects.

See Also

Other API resources: [get_commitments\(\)](#), [get_contracts\(\)](#), [get_geometries\(\)](#), [get_last_update\(\)](#), [get_physical_execution\(\)](#), [get_projects\(\)](#), [get_status_history\(\)](#)

Examples

```

if (interactive()) {
  get_feasibility_studies(id_projeto_investimento = "134851.26-07")
}

```

get_geometries	<i>Retrieve geometries</i>
----------------	----------------------------

Description

Retrieve geometries

Usage

```
get_geometries(
  ...,
  page = 1L,
  page_size = 50L,
  all_pages = FALSE,
  page_limit = Inf,
  base_url = .obrasgovr_base_url()
)

obter_geometrias(
  ...,
  pagina = 1L,
  tamanho_da_pagina = 50L,
  todas_paginas = FALSE,
  limite_paginas = Inf,
  base_url = .obrasgovr_base_url()
)
```

Arguments

...	Named filters. See <code>list_filters("geometries")</code> .
page	First page to retrieve, starting at 1.
page_size	Number of records per page, between 1 and 200.
all_pages	If TRUE, retrieves successive pages starting at page.
page_limit	Maximum number of pages to retrieve when <code>all_pages</code> is TRUE. Use <code>Inf</code> to retrieve every available page.
base_url	HTTPS base URL. By default, uses the <code>obrasgovr.base_url</code> option or the official API environment.
pagina, tamanho_da_pagina, todas_paginas, limite_paginas	Portuguese aliases for <code>page</code> , <code>page_size</code> , <code>all_pages</code> , and <code>page_limit</code> , respectively. These arguments are available only in the Portuguese function alias.

Value

A tibble containing geometries and territorial identifiers.

See Also

Other API resources: [get_commitments\(\)](#), [get_contracts\(\)](#), [get_feasibility_studies\(\)](#), [get_last_update\(\)](#), [get_physical_execution\(\)](#), [get_projects\(\)](#), [get_status_history\(\)](#)

Examples

```
if (interactive()) {  
  get_geometries(sg_uf = "PE", page_size = 10)  
}
```

get_last_update	<i>Retrieve the data update timestamp</i>
-----------------	---

Description

Retrieve the data update timestamp

Usage

```
get_last_update(base_url = .obrasgovr_base_url())  
  
obter_data_atualizacao(base_url = .obrasgovr_base_url())
```

Arguments

base_url	HTTPS base URL. By default, uses the obrasgovr.base_url option or the official API environment.
----------	---

Value

A POSIXct value in the UTC time zone.

See Also

Other API resources: [get_commitments\(\)](#), [get_contracts\(\)](#), [get_feasibility_studies\(\)](#), [get_geometries\(\)](#), [get_physical_execution\(\)](#), [get_projects\(\)](#), [get_status_history\(\)](#)

Examples

```
if (interactive()) {  
  get_last_update()  
}
```

get_physical_execution

Retrieve physical execution data

Description

Retrieve physical execution data

Usage

```
get_physical_execution(
  ...,
  page = 1L,
  page_size = 50L,
  all_pages = FALSE,
  page_limit = Inf,
  base_url = .obrasgovr_base_url()
)

obter_execucao_fisica(
  ...,
  pagina = 1L,
  tamanho_da_pagina = 50L,
  todas_paginas = FALSE,
  limite_paginas = Inf,
  base_url = .obrasgovr_base_url()
)
```

Arguments

...	Named filters. See <code>list_filters("physical_execution")</code> .
page	First page to retrieve, starting at 1.
page_size	Number of records per page, between 1 and 200.
all_pages	If TRUE, retrieves successive pages starting at page.
page_limit	Maximum number of pages to retrieve when <code>all_pages</code> is TRUE. Use <code>Inf</code> to retrieve every available page.
base_url	HTTPS base URL. By default, uses the <code>obrasgovr.base_url</code> option or the official API environment.
pagina, tamanho_da_pagina, todas_paginas, limite_paginas	Portuguese aliases for <code>page</code> , <code>page_size</code> , <code>all_pages</code> , and <code>page_limit</code> , respectively. These arguments are available only in the Portuguese function alias.

Value

A tibble containing execution percentages, instruments, and dates.

See Also

Other API resources: [get_commitments\(\)](#), [get_contracts\(\)](#), [get_feasibility_studies\(\)](#), [get_geometries\(\)](#), [get_last_update\(\)](#), [get_projects\(\)](#), [get_status_history\(\)](#)

Examples

```
if (interactive()) {
  get_physical_execution(id_projeto_investimento = "134851.26-07")
}
```

get_projects	<i>Retrieve infrastructure projects</i>
--------------	---

Description

Retrieves infrastructure projects and their nested relationships, including executors, recipients, funding sources, policy areas, and point geometries.

Usage

```
get_projects(
  ...,
  page = 1L,
  page_size = 50L,
  all_pages = FALSE,
  page_limit = Inf,
  base_url = .obrasgovr_base_url()
)

obter_projetos(
  ...,
  pagina = 1L,
  tamanho_da_pagina = 50L,
  todas_paginas = FALSE,
  limite_paginas = Inf,
  base_url = .obrasgovr_base_url()
)
```

Arguments

...	Named filters accepted by the resource. See the complete list with <code>list_filters("projects")</code> . Filter names and categorical values are kept in Portuguese because they are defined by the ObrasGov API.
page	First page to retrieve, starting at 1.
page_size	Number of records per page, between 1 and 200.
all_pages	If TRUE, retrieves successive pages starting at page.

`page_limit` Maximum number of pages to retrieve when `all_pages` is TRUE. Use `Inf` to retrieve every available page.

`base_url` HTTPS base URL. By default, uses the `obrasgovr.base_url` option or the official API environment.

`pagina`, `tamanho_da_pagina`, `todas_paginas`, `limite_paginas` Portuguese aliases for `page`, `page_size`, `all_pages`, and `page_limit`, respectively. These arguments are available only in the Portuguese function alias.

Value

A tibble. One-to-many relationships are preserved in list-columns. Use `result_metadata()` to inspect pagination information.

See Also

Other API resources: `get_commitments()`, `get_contracts()`, `get_feasibility_studies()`, `get_geometries()`, `get_last_update()`, `get_physical_execution()`, `get_status_history()`

Examples

```
if (interactive()) {
  get_projects(uf_principal = "PE", page_size = 10)
}
```

<code>get_status_history</code>	<i>Retrieve project status histories</i>
---------------------------------	--

Description

Retrieves the histories of cancelled or suspended projects, including reasons and remedial actions.

Usage

```
get_status_history(
  ...,
  page = 1L,
  page_size = 50L,
  all_pages = FALSE,
  page_limit = Inf,
  base_url = .obrasgovr_base_url()
)

obter_historico_situacao(
  ...,
  pagina = 1L,
  tamanho_da_pagina = 50L,
  todas_paginas = FALSE,
```

```

    limite_paginas = Inf,
    base_url = .obrasgovr_base_url()
  )

```

Arguments

...	Named filters. See <code>list_filters("status_history")</code> .
page	First page to retrieve, starting at 1.
page_size	Number of records per page, between 1 and 200.
all_pages	If TRUE, retrieves successive pages starting at page.
page_limit	Maximum number of pages to retrieve when <code>all_pages</code> is TRUE. Use Inf to retrieve every available page.
base_url	HTTPS base URL. By default, uses the <code>obrasgovr.base_url</code> option or the official API environment.
pagina, tamanho_da_pagina, todas_paginas, limite_paginas	Portuguese aliases for <code>page</code> , <code>page_size</code> , <code>all_pages</code> , and <code>page_limit</code> , respectively. These arguments are available only in the Portuguese function alias.

Value

A tibble containing project status histories.

See Also

Other API resources: [get_commitments\(\)](#), [get_contracts\(\)](#), [get_feasibility_studies\(\)](#), [get_geometries\(\)](#), [get_last_update\(\)](#), [get_physical_execution\(\)](#), [get_projects\(\)](#)

Examples

```

if (interactive()) {
  get_status_history(id_projeto_investimento = "134851.26-07")
}

```

list_filters	<i>List filters accepted by a resource</i>
--------------	--

Description

Lists the filters published in the OpenAPI contract supported by this package. Unknown filters are rejected before a request is sent to prevent silently incorrect queries. Filter names and categorical values remain in Portuguese because they are part of the upstream API contract.

Usage

```

list_filters(resource)

obrasgov_filtros(recurso)

```

Arguments

resource	A resource name returned by <code>list_resources()</code> . Portuguese resource names used by earlier package versions are also accepted.
recurso	Portuguese alias for resource, available only in <code>obrasgov_filtros()</code> .

Value

A tibble containing filter names, expected types, and allowed values when applicable.

Examples

```
list_filters("projects")
```

list_resources	<i>List available ObrasGov API resources</i>
----------------	--

Description

List available ObrasGov API resources

Usage

```
list_resources()
obrasgov_recurso()
```

Value

A tibble containing each resource name, its corresponding function, API endpoint, and whether it is paginated.

Examples

```
list_resources()
```

result_metadata	<i>Retrieve pagination metadata</i>
-----------------	-------------------------------------

Description

Retrieve pagination metadata

Usage

```
result_metadata(x)
```

```
obrasgov_metadados(x)
```

Arguments

x A tibble returned by a paginated package function.

Value

A list containing the resource, totals reported by the API, and retrieved pages; NULL for other objects.

Examples

```
result_metadata(tibble::tibble())
```

Index

* API resources

- [get_commitments](#), [2](#)
 - [get_contracts](#), [3](#)
 - [get_feasibility_studies](#), [4](#)
 - [get_geometries](#), [6](#)
 - [get_last_update](#), [7](#)
 - [get_physical_execution](#), [8](#)
 - [get_projects](#), [9](#)
 - [get_status_history](#), [10](#)
- [get_commitments](#), [2](#)
- [get_commitments\(\)](#), [4](#), [5](#), [7](#), [9–11](#)
- [get_contracts](#), [3](#)
- [get_contracts\(\)](#), [3](#), [5](#), [7](#), [9–11](#)
- [get_feasibility_studies](#), [4](#)
- [get_feasibility_studies\(\)](#), [3](#), [4](#), [7](#), [9–11](#)
- [get_geometries](#), [6](#)
- [get_geometries\(\)](#), [3–5](#), [7](#), [9–11](#)
- [get_last_update](#), [7](#)
- [get_last_update\(\)](#), [3–5](#), [7](#), [9–11](#)
- [get_physical_execution](#), [8](#)
- [get_physical_execution\(\)](#), [3–5](#), [7](#), [10](#), [11](#)
- [get_projects](#), [9](#)
- [get_projects\(\)](#), [3–5](#), [7](#), [9](#), [11](#)
- [get_status_history](#), [10](#)
- [get_status_history\(\)](#), [3–5](#), [7](#), [9](#), [10](#)
- [list_filters](#), [11](#)
- [list_resources](#), [12](#)
- [list_resources\(\)](#), [12](#)
- [obrasgov_filtros](#) ([list_filters](#)), [11](#)
- [obrasgov_filtros\(\)](#), [12](#)
- [obrasgov_metadados](#) ([result_metadata](#)), [13](#)
- [obrasgov_recursos](#) ([list_resources](#)), [12](#)
- [obter_contratos](#) ([get_contracts](#)), [3](#)
- [obter_data_atualizacao](#)
 - ([get_last_update](#)), [7](#)
- [obter_empenhos](#) ([get_commitments](#)), [2](#)

- [obter_estudos_viabilidade](#)
 - ([get_feasibility_studies](#)), [4](#)
- [obter_execucao_fisica](#)
 - ([get_physical_execution](#)), [8](#)
- [obter_geometrias](#) ([get_geometries](#)), [6](#)
- [obter_historico_situacao](#)
 - ([get_status_history](#)), [10](#)
- [obter_projetos](#) ([get_projects](#)), [9](#)
- [result_metadata](#), [13](#)
- [result_metadata\(\)](#), [10](#)